



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Knowledge Center

[cms.cluster Section](#)

12/17/2025

cms.cluster Section

- cmsPathStorage
- dbConnectionUrl
- dbDataColumnType
- dbDriverClass
- dbIdColumnType
- dbJndiName
- dbPassword
- dbTimestampColumnType
- dbUsername
- host
- jgroupsConfiguration
- port
- repositoryName
- type

cmsPathStorage

Default Value: ./knowledge

Valid Values:

Changes Take Effect: After restart

Discontinued: 9.0.000.15

Path to store repository

dbConnectionUrl

Default Value:

Valid Values:

Changes Take Effect: At start/restart

Database connection string for the selected persistent storage. Examples:

for Microsoft SQL: jdbc:jtds:sqlserver://[host of MS SQL server]:[port of MS SQL server; 1433 by default];databaseName=[CMS DB name]

for Oracle: jdbc:oracle:thin:[userName]/[password]@[host of Oracle DB]:[port of Oracle DB; 1521 by default]:[SID. for example ORCL]

for PostgreSQL: jdbc:postgresql://[host of PostgreSQL server]:[port of PostgreSQL server; 5432 by default]/[CMS DB name]

dbDataColumnType

Default Value: BINARY

Valid Values:

Changes Take Effect: After restart

Discontinued: 9.0.000.15

Database type for DATA_COLUMN

dbDriverClass

Default Value:

Valid Values:

Changes Take Effect: After restart

Discontinued: 9.0.000.15

JDBC driver class

dbIdColumnType

Default Value: VARCHAR(255)

Valid Values:

Changes Take Effect: After restart

Discontinued: 9.0.000.15

Database type for ID_COLUMN

dbJndiName

Default Value: java:comp/env/jdbc/knowledge

Valid Values:

Changes Take Effect: After restart

Discontinued: 9.0.000.15

JNDI database name

dbPassword

Default Value:

Valid Values:

Changes Take Effect: At start/restart

Password for user for access JDBC database.

dbTimestampColumnType

Default Value: BIGINT

Valid Values:

Changes Take Effect: After restart

Discontinued: 9.0.000.15

Database type for TIMESTAMP_COLUMN

dbUsername

Default Value:

Valid Values:

Changes Take Effect: At start/restart

Name of user for access JDBC database.

host

Default Value: 127.0.0.1

Valid Values:

Changes Take Effect: After restart

Discontinued: 9.0.000.15

Cassandra host

jgroupsConfiguration

Default Value: TCP

Valid Values:

Changes Take Effect: At start/restart

Determine the communication approach used to interact between a servers.

port

Default Value: 9160

Valid Values: Any integer greater than 0 and less than 65535 inclusively

Changes Take Effect: After restart

Discontinued: 9.0.000.15

Cassandra port

repositoryName

Default Value: Genesys Knowledge Repository

Valid Values:

Changes Take Effect: After restart

Discontinued: 9.0.000.15

Repository name

type

Default Value: mssql

Valid Values: mssql, oracle, postgre

Changes Take Effect: At start/restart

Type of persistent storage provider used for Knowledge Center CMS repository.