



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## Knowledge Center

cms-ucs Section

12/19/2025

## cms-ucs Section

- [asynsync-delay](#)
- [config-synchro-mode](#)
- [enabled](#)
- [fieldcode-format-locale](#)
- [postpone-synchro-delay](#)
- [replace-blank-fieldcode](#)
- [screening-rules-sync-delay](#)
- [standard-responses-sync-delay](#)
- [synchronize-screening-rules](#)
- [synchronize-standard-responses](#)

### asynsync-delay

**Default Value:** 1000

**Valid Values:** Any integer greater than 0

**Changes Take Effect:** Immediately

**Introduced:** 9.0.000.15

Delay before retry, if previous synchronization failed.

### config-synchro-mode

**Default Value:** periodically

**Valid Values:** periodically, on-config-even, both

**Changes Take Effect:** At start/restart

**Introduced:** 9.0.000.15

Configuration server SRL synchronization mode.

### enabled

**Default Value:** true

**Valid Values:**

**Changes Take Effect:** Immediately

**Introduced:** 9.0.000.15

Enables authoring of screening rules and standard responses.

## fieldcode-format-locale

**Default Value:**

**Valid Values:** Any valid Java locale in the `language_COUNTRY` format (<two letter code of ISO 639>\_<two letter code of ISO 3166>)

**Changes Take Effect:** Immediately

**Introduced:** 9.0.000.15

When specified, defines the locale that must be used to format date, time, currency, and percent values in Field Codes. If not specified, the server uses the default platform.

## postpone-synchro-delay

**Default Value:** 1000

**Valid Values:** Any integer greater than 0

**Changes Take Effect:** Immediately

**Introduced:** 9.0.000.15

Delay for postpone synchronization with config server.

## replace-blank-fieldcode

**Default Value:** false

**Valid Values:**

**Changes Take Effect:** Immediately

**Introduced:** 9.0.000.15

Specifies whether field code names will be displayed in a response where the field code does not have any content. If set to true, this option applies to responses generated by desktops, but not to automated responses generated by E-mail Server (ACK, AutoResponse).

## screening-rules-sync-delay

**Default Value:** 10000

**Valid Values:** Any integer greater than 0

**Changes Take Effect:** Immediately

**Introduced:** 9.0.000.15

If the option `synchronize-screening-rules` is enabled, this option specifies, in milliseconds, the delay after which synchronization of the screening rules occurs.

## standard-responses-sync-delay

**Default Value:** 10000

**Valid Values:**

**Changes Take Effect:** Immediately

**Introduced:** 9.0.000.15

If the option `synchronize-standard-responses` is enabled, this option specifies, in milliseconds, the delay after which synchronization of standard responses occurs.

## synchronize-screening-rules

**Default Value:** false

**Valid Values:**

**Changes Take Effect:** Immediately

**Introduced:** 9.0.000.15

Enables (true) or disables (false) the synchronization of screening rules from the UCS database to Business Attributes in the Configuration Server. If enabled, synchronization occurs shortly after any change to the screening rules.

## synchronize-standard-responses

**Default Value:** false

**Valid Values:**

**Changes Take Effect:** Immediately

**Introduced:** 9.0.000.15

Enables (true) or disables (false) the synchronization of standard responses from the CMS database to Business Attributes in the Configuration Server. If enabled, synchronization occurs shortly after any change to standard responses.