



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Web Real-Time Communications

ems Section

5/4/2025

## ems Section

- [logconfig.MFSINK](#)
- [metricsconfig.MFSINK](#)

This content is under development and might not be comprehensive or completely up to date. For full information, see [Configuration Options](#) in the *Deployment Guide*.

### logconfig.MFSINK

**Default Value:** `*|*|*`

**Valid Values:** Pipe-delimited ranges for log levels, module IDs, and specifier IDs. Ranges can be comma-separated integers or ranges of integers or `"*"`.

**Changes Take Effect:** immediately

Controls the log messages that are sent to the MF sink. The format is "levels|moduleIDs|specifierIDs" (repeated if necessary). The values between the pipes can be in the format: "m-n,o,p" (for example, "0-4, 5, 6"). The wildcard character "\*" can also be used to indicate all valid numbers. For example: `"*|*|*"` indicates that all log messages should be sent to the sink. Alternatively, `"0,1|0-10|*|4|*|*"` indicates that CRITICAL(0) and ERROR(1) level messages with module IDs in the range 0-10 will be sent to the sink; and all INFO(4) level messages will be sent as well.

### metricsconfig.MFSINK

**Default Value:** `*`

**Valid Values:** Comma-separated list of metric values or ranges. A metric value must be between 0 and 141 inclusive. The values `"*"` and blank are also allowed.

**Changes Take Effect:** immediately

Specifies the metrics that are delivered to the MF Sink. `"*"` indicates that all metrics will be sent to the sink. Alternatively, `"5-10,50-55,70,71"` indicates that metrics with IDs 5, 6, 7, 8, 9, 10, 50, 51, 52, 53, 54, 55, 70, and 71 will be sent to the MF sink.