



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Platform SDK Developer's Guide

CfgObjectiveTable

5/3/2025

---

## Contents

- 1 CfgObjectiveTable
  - 1.1 Description
  - 1.2 Filter Keys
  - 1.3 Attributes
  - 1.4 XML Representation
  - 1.5 See Also

# CfgObjectiveTable

## Description

Objective Tables are collections of Objective Records.

## Filter Keys

Filter Name	Type	Description
dbid	int	A unique identifier of an objective table. If specified, Configuration Server will return information only about this objective table.
name	string	Name of an objective table. Shall be specified as a character string. If specified, Configuration Server will return information only about the objective table(s) with that name.
tenant_dbid	int	A unique identifier of a tenant. If specified, Configuration Server will return information only about the objective tables that belong to this tenant.
state	int	Current state of an objective table (see <a href="#">CfgObjectState</a> ). If specified, Configuration Server will return information only about objective tables that are currently in this state.

## Attributes

- DBID — An identifier of this object in the Configuration Database. Generated by Configuration Server and is unique within an object type. Identifiers of deleted objects are not used again. Read-only.
- tenantDBID — A unique identifier of the [CfgTenant](#) to which this objective table is allocated. Mandatory. Once specified, cannot be changed.
- name — A pointer to the name of the objective table. Mandatory. Must be unique within the tenant environment.

- description — A pointer to the description of the objective table.
- objectiveRecords — A pointer to the list of identifiers of objective records comprising this objective table.
- state — Current object state. Mandatory. Refer to [CfgObjectState](#).
- userProperties — A pointer to the list of user-defined properties. Parameter userProperties has the following structure: Each key-value pair of the primary list (TKVList \*userProperties) uses the key for the name of a user-defined section, and the value for a secondary list, that also has the TKVList structure and specifies the properties defined within that section.
- prepaidCost — A flat rate for the cost per call
- timeZoneDBID — A [CfgTimeZone](#) associated with this Cost Contract
- timeStart — The date on which to start the Volume Rate Contract.
- timeEnd — The date on which to end the Volume Rate Contract.
- type — Objective Table type. Refer to [CfgObjectiveTableType](#).

## XML Representation

### Tip

This XML was created using the Configuration Server 7.5 schema.

```
<CfgObjectiveTable>
  <DBID value="1002" />
  <tenantDBID value="101" />
  <name value="XYZCostContract" />
  <objectiveRecords>
    <CfgObjectiveTableRecord>
      <mediaTypeDBID value="1001" />
      <serviceTypeDBID value="1023" />
      <customerSegmentDBID value="1024" />
      <objectiveThreshold value="0" />
      <objectiveDelta value="0" />
      <contractDBID value="111" />
    </CfgObjectiveTableRecord>
  </objectiveRecords>
  <state value="1" />
  <userProperties>
    <list_pair key="_WIZARD_">
      <str_pair key="_ProgID_" value="CfgWizard_CBR.CfgObjectiveTableWizard" />
    </list_pair>
  </userProperties>
  <prepaidCost value="725" />
  <timeZoneDBID value="115" />
  <timeStart value="1169649000" />
  <timeEnd value="1172447999" />
  <type value="2" />
</CfgObjectiveTable>
```

## See Also

[CfgDeltaObjectiveTable](#)

[CfgEnumeratorValue](#)