



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Platform SDK Developer's Guide

CfgRole

12/20/2025

Contents

- 1 CfgRole
 - 1.1 Description
 - 1.2 Attributes
 - 1.3 See Also

CfgRole

Description

A *Role* defines what tasks, if any, a user (either an individual User, or member of an Access Group) can or cannot perform on an object for which that user has corresponding permissions.

Attributes

- DBID — An identifier of this object in the Configuration Database. Generated by Configuration Server and is unique within an object type. Identifiers of deleted objects are not used again. Read-only.
- tenantDBID — A unique identifier of the [Tenant](#) that this role belongs to. Mandatory. Once specified, cannot be changed.
- name — The name of the role. Mandatory. Must be unique within the tenant.
- description — A text description of this role.
- state — Current object state. Mandatory. Refer to [CfgObjectState](#).
- userProperties — A pointer to the list of user-defined properties. Parameter userProperties has the following structure: Each key-value pair of the primary list (TKVList *userProperties) uses the key for the name of a user-defined section, and the value for a secondary list, that also has the TKVList structure and specifies the properties defined within that section.
- members — A list of members belonging to this role. Refer to [CfgRoleMember](#).

See Also

[CfgRoleMember](#)

[CfgDeltaRole](#)