



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Platform SDK Developer's Guide

CfgRouteType

12/19/2025

# CfgRouteType

## Values

| Mnemonic                    | ID | Flag | Short Description       | Log Name                 | Long Description                                          |
|-----------------------------|----|------|-------------------------|--------------------------|-----------------------------------------------------------|
| CFGNoRoute                  | 0  | 0    | 'Unknown Route Type'    | Unknown                  | The value of the corresponding parameter has not changed. |
| CFGDefault                  | 1  | 0    | 'Default'               | Default                  |                                                           |
| CFGLabel                    | 2  | 0    | 'Label'                 | Label                    |                                                           |
| CFGOverwriteDNIS            | 3  | 0    | 'Overwrite DNIS'        | OverwriteDNIS            |                                                           |
| CFGDDD                      | 4  | 0    | 'DDD'                   | DDD                      |                                                           |
| CFGIDDD                     | 5  | 0    | 'IDDD'                  | IDDD                     |                                                           |
| CFGDirect                   | 6  | 0    | 'Direct'                | Direct                   |                                                           |
| CFGReject                   | 7  | 0    | 'Reject'                | Reject                   |                                                           |
| CFGAnnouncement             | 8  | 0    | 'Announcement'          | Announcement             |                                                           |
| CFGPostFeature              | 9  | 0    | 'Post Feature'          | PostFeature              |                                                           |
| CFGDirectAgent              | 10 | 0    | 'Direct Agent'          | DirectAgent              |                                                           |
| CFGUseExternalProtocol      | 11 | 0    | 'Use External Protocol' | UseExternalProtocol      |                                                           |
| CFGGetFromDN                | 12 | 0    | 'Get From DN'           | GetFromDN                |                                                           |
| CFGXRouteTypeDefault        | 13 | 0    | 'Default'               | XRouteTypeDefault        |                                                           |
| CFGXRouteTypeRoute          | 14 | 0    | 'Route'                 | XRouteTypeRoute          |                                                           |
| CFGXRouteTypeDirect         | 15 | 0    | 'Direct'                | XRouteTypeDirect         |                                                           |
| CFGXRouteTypeReRoute        | 16 | 0    | 'Re-Route'              | XRouteTypeReroute        |                                                           |
| CFGXRouteTypeDirectUII      | 17 | 0    | 'Direct UII'            | XRouteTypeDirectUII      |                                                           |
| CFGXRouteTypeDirectANI      | 18 | 0    | 'Direct ANI'            | XRouteTypeDirectANI      |                                                           |
| CFGXRouteTypeDirectNoToken  | 19 | 0    | 'Direct No Token'       | XRouteTypeDirectNoToken  |                                                           |
| CFGXRouteTypeDNISPooling    | 20 | 0    | 'DNIS Pooling'          | XRouteTypeDNISPooling    |                                                           |
| CFGXRouteTypeDirectDNISnANI | 21 | 0    | 'Direct DNIS and ANI'   | XRouteTypeDirectDNISnANI |                                                           |
| CFGXRouteTypeDirectDigits   | 22 | 0    | 'Direct Digits'         | XRouteTypeDirectDigits   |                                                           |
| CFGXRouteTypeForbidden      | 23 | 0    | 'Forbidden'             | XRouteTypeForbidden      |                                                           |
| CFGXRouteTypeISCCProtocol   | 24 | 0    | 'ISCC defined'          | XRouteTypeISCCProtocol   |                                                           |

---

| Mnemonic                         | ID | Flag | Short Description        | Log Name                      | Long Description |
|----------------------------------|----|------|--------------------------|-------------------------------|------------------|
|                                  |    |      | protocol'                |                               |                  |
| CFGXRouteTypePullBack            | 13 | 0    | 'PullBack'               | XRouteTypePullback            |                  |
| CFGXRouteTypeDirectNetworkCallID | 26 | 0    | 'Direct Network Call ID' | XRouteTypeDirectNetworkCallID |                  |

## Comments

Values from 13 to 25 must be shown on GUI if property Target Type under AccessCodes is set to TargetISCC only, meantime the values from 1 to 12 must be hidden.

For explanations of routing types, refer to the latest version of the *T-Server Developer's Guide*.