



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Platform SDK Developer's Guide

CfgStatInterval

5/4/2025

Contents

- [1 CfgStatInterval](#)
 - [1.1 Description](#)
 - [1.2 Attributes](#)
 - [1.3 Comments](#)

CfgStatInterval

Description

Use a *Statistical Interval* to associate each Statistical Interval with certain Statistical Values.

Attributes

- intervalCount - Interval's number. Once specified, cannot be changed. The first interval has number 1. First interval is always counted from the start of business time set by startTime in [CfgStatDay](#).
- statValue1 - Statistical values for this interval. Cannot be negative.
- statValue2 - Statistical values for this interval. Cannot be negative.
- statValue3 - Statistical values for this interval. Cannot be negative.
- statValue4 - Statistical values for this interval. Cannot be negative.

Comments

For the missing intervals, the stat values shall be assumed to be zero.

The current version of Configuration Server does not verify correspondence between the values of intervalCount and the current settings of intervalLength, startTime and endTime in [CfgStatDay](#). Such verification may be added in one of the next releases. At the moment, it is users' responsibility to make sure the values of intervalCount make sense.