



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Platform SDK Developer's Guide

TNetworkPrivateService

12/17/2025

---

## Contents

- 1 TNetworkPrivateService
  - 1.1 Description
  - 1.2 Parameters
  - 1.3 Return Values

# TNetworkPrivateService

## Description

Initiates a request to perform a device-specific service.

## Parameters

| Name          | Description                                                                                                                                      |
|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| server        | Local server handle to the T-Server in question.                                                                                                 |
| serviceID     | Service identifier for the information being passed.                                                                                             |
| ctrl_dn       | DN of the controlling party, for a premise T-Server, or the route point where the call was initially routed, for a network T-Server.             |
| conn_id       | Connection ID of the call in question.                                                                                                           |
| home_location | A pointer to the name of the remote location that carries out the request in the form of <SwitchName> or <T-ServerApplicationName>@<SwitchName>. |
| reasons       | A pointer to a data structure which provides additional information associated with this action.                                                 |
| extensions    | A pointer to an additional data structure.                                                                                                       |

## Return Values

Standard (See standard-return-values.)