



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Platform SDK Developer's Guide

TCompleteConference

12/17/2025

Contents

- 1 TCompleteConference
 - 1.1 Description
 - 1.2 Parameters
 - 1.3 Return Values

TCompleteConference

Description

Completes a previously initiated conference by merging the held call specified by the parameter `held_conn_id` with the active consultation call specified by the parameter `current_conn_id` on behalf of the telephony object specified by `dn`. Assigns `held_conn_id` to the resulting conference call. Clears the consultation call specified by the parameter `current_conn_id`.

Parameters

Name	Description
<code>server</code>	Local server handle to the T-Server in question.
<code>dn</code>	Directory number of the telephony object on whose behalf the conference is made.
<code>held_conn_id</code>	Connection identifier of the original call; will be assigned to the resulting conference call.
<code>current_conn_id</code>	Connection identifier of the consultation call; the consultation call will be deleted after completion of operation.
<code>reasons</code>	A pointer to a data structure that provides additional information associated with this action.
<code>extensions</code>	A pointer to an additional data structure.

Return Values

Standard (See [standard-return-values](#).)