



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Platform SDK Developer's Guide

[TMakePredictiveCall](#)

Contents

- 1 TMakePredictiveCall
 - 1.1 Description
 - 1.2 Parameters
 - 1.3 Return Values

TMakePredictiveCall

Description

Originates a predictive call from the telephony object specified by the parameter `dn` to the called party specified by the parameter `destination`.

A predictive call occurs before any agent-subscriber interaction. For example, if the call is answered by a fax machine, no agent connection is made. Agent connection is made only if there is an actual subscriber present on the line.

Parameters

Name	Description
<code>server</code>	Local server handle to the T-Server in question.
<code>dn</code>	Directory number of the telephony object from which the call is requested to be made. (See note below.)
<code>destination</code>	Directory number of the party to be dialed.
<code>ring_timeout</code>	Timeout, in seconds, after which the call should be considered unanswered.
<code>user_data</code>	A pointer to the user data that should be attached to the call.
<code>reasons</code>	A pointer to a data structure that provides additional information associated with this action.
<code>extensions</code>	A pointer to an additional data structure. <code>TMakePredictiveCall()</code> uses the following extensions: <code>VoiceDest</code> , <code>AnsMachine</code> , and <code>FaxDest</code> . To specify a Calling Party Number (CPN), it may also use <code>CPNType</code> , <code>CPNPlan</code> , <code>CPNPresentation</code> , <code>CPNScreening</code> , and <code>CPNDigits</code> .

Return Values

Standard (See [standard-return-values](#).)

Important

When selection of a target DN depends on the results of the call answer detection, T-Server generates `EventDialing` and `EventQueued` for the call origination DN specified by the `dn` parameter. Then, T-Server diverts a call to the target DN specified for this call type in the `extensions` parameter and generates `EventDiverted` for the DN specified by the `dn` parameter and appropriate events for the target DN.