



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

T-Server Reference Guide

TAddressInfoStatus

12/19/2025

TAddressInfoStatus

Syntax

```
typedef union {
    AssociationInfoType      AssociationStatus;
    AddressStatusInfoType    AddressStatus;
    MsgWaitingInfoType       MsgWaitingStatus;
    TForwardMode             CallForwardingStatus;
    TAgentWorkMode           AgentStatus;
    int                      NumberOfAgentsInQueue;
    int                      NumberOfAvailableAgentsInQueue;
    int                      NumberOfCallsInQueue;
    TAddressType             AddressType;
    TForwardMode             SendAllCallsStatus;
    int                      NumberOfIdleClassifiers;
    int                      NumberOfClassifiersInUse;
    int                      NumberOfIdleTrunks;
    int                      NumberOfTrunksInUse;
    int                      NumberOfListElements;
} TAddressInfoStatus;
```

Attributes

- AssociationStatus — See [AssociationInfoType](#).
- AddressStatus — See [AddressStatusInfoType](#).
- MsgWaitingStatus — See [MsgWaitingInfoType](#).
- CallForwardingStatus — See [TForwardMode](#).
- AgentStatus — See [TAgentWorkMode](#).
- NumberOfAgentsInQueue — Specifies the number of agents currently logged in a queue.
- NumberOfAvailableAgentsInQueue — Specifies the number of agents in a queue currently ready to receive a call.
- NumberOfCallsInQueue — Specifies the number of calls in a queue.
- AddressType — See [TAddressType](#).
- SendAllCallsStatus — See [TForwardMode](#).
- NumberOfIdleClassifiers — Specifies the number of idle classifiers.
- NumberOfClassifiersInUse — Specifies the number of classifiers in use.
- NumberOfIdleTrunks — Specifies the number of idle trunks.
- NumberOfTrunksInUse — Specifies the number of trunks in use.
- NumberOfListElements — Specifies the number of list elements. The value is passed in the TEvent

attribute Extensions.