



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# T-Server Reference Guide

TCompleteTransfer

12/19/2025

---

## Contents

- 1 TCompleteTransfer
  - 1.1 Description
  - 1.2 Parameters
  - 1.3 Return Values
  - 1.4 Comments

# TCompleteTransfer

## Description

On behalf of the telephony object specified by the parameter `dn`, completes a previously initiated two-step transfer by merging the held call specified by the parameter `conn_id` with the active consultation call specified by the parameter `current_conn_id`. Assigns `held_conn_id` to the resulting call. Releases the telephony object specified by the parameter `dn` from both calls and clears the consultation call specified by the parameter `current_conn_id`.

## Parameters

| Name                         | Description                                                                                     |
|------------------------------|-------------------------------------------------------------------------------------------------|
| <code>server</code>          | Local server handle to the T-Server in question.                                                |
| <code>dn</code>              | Directory number of the telephony object on whose behalf the transfer is made.                  |
| <code>held_conn_id</code>    | Connection identifier of the original call; will be assigned to the resulting transferred call. |
| <code>current_conn_id</code> | Connection identifier of the consultation call; will be deleted after completion of operation.  |
| <code>reasons</code>         | A pointer to a data structure that provides additional information associated with this action. |
| <code>extensions</code>      | A pointer to an additional data structure.                                                      |

## Return Values

Standard (See [standard-return-values](#).)

## Comments

The transfer may be completed both before and after the consulted party answers.