



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# T-Server Reference Guide

TListenDisconnect

---

## Contents

- 1 TListenDisconnect
  - 1.1 Description
  - 1.2 Parameters
  - 1.3 Return Values

# TListenDisconnect

## Description

On an existing conference call, sets Deaf mode for the party specified by the parameter `listener_dn`. For example, if two agents wish to consult privately, the subscriber may temporarily be placed in Deaf mode.

## Parameters

| Name                     | Description   |
|--------------------------|---|
| <code>server</code>      | Local server handle to the T-Server in question.  |
| <code>dn</code>          | Directory number of the telephony object on whose behalf this request is made; must be a party in the specified call. |
| <code>listener_dn</code> | Directory number of the telephony object that is requested to be set to Deaf mode.                                    |
| <code>conn_id</code>     | Connection identifier of the call from which the telephony object is requested to be released.                        |
| <code>reasons</code>     | A pointer to a data structure that provides additional information associated with this action.                       |
| <code>extensions</code>  | A pointer to an additional data structure.  |

## Return Values

Standard (See [standard-return-values](#).)