



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

T-Server Reference Guide

TMediaType

12/21/2025

Contents

- 1 TMediaType
 - 1.1 Syntax
 - 1.2 Values
 - 1.3 Comments

TMediaType

Syntax

```
typedef enum {  
    TMediaVoice           = 0,  
    TMediaVoIP            = 1,  
    TMediaEMail           = 2,  
    TMediaVMail           = 3,  
    TMediaSMail           = 4,  
    TMediaChat            = 5,  
    TMediaVideo           = 6,  
    TMediaCobrowsing      = 7,  
    TMediaWhiteboard      = 8,  
    TMediaAppSharing      = 9,  
    TMediaWebForm         = 10,  
    TMediaWorkItem        = 11,  
    TMediaCustom0         = 100  
} TMediaType;
```

Values

Important

T-Server sets the TMediaVoice value in the messages it generates.

- TMediaVoice — Voice (PSTN) call
- TMediaVoIP — Voice over IP
- TMediaEMail — Electronic Mail
- TMediaVMail — Voice Mail
- TMediaSMail — Scanned Mail
- TMediaChat — Chat Session
- TMediaVideo — Video
- TMediaCobrowsing — Cobrowsing
- TMediaWhiteboard — Whiteboard
- TMediaAppSharing — Application Sharing
- TMediaWebForm — WebForm
- TMediaWorkItem — Work item (generic)

- TMediaCustom0 — All values greater than this one are reserved for custom media types.

Comments

In order to support MediaType in T-Servers that work with multiple media, the field `media_type` is included to indicate the type of media associated with a given party in an interaction. This field appears in extensions of `EventRegistered` and `EventAddressInfo` with the key `mt-%d`.