



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

T-Server Reference Guide

TQueryAddress

Contents

- 1 TQueryAddress
 - 1.1 Description
 - 1.2 Parameters
 - 1.3 Return Values

TQueryAddress

Description

Requests the information specified by the parameter `info_type` about the telephony object specified by the parameter `dn`, or the parameter `queue`, or both. Refer to the type [TAddressInfoType](#). If the query type is supported, the requested information will be returned in `EventAddressInfo`.

Parameters

Name	Description
server	Local server handle to the T-Server in question.
queue	Directory number of the ACD group about which the information is requested (used only if <code>info_type=AddressInfoAgentStatus</code>);).
dn	Directory number of the telephony object in question.
addr_type	Type of telephony object in question. Refer to the type TAddressType .
info_type	Type of the requested information. Refer to the type TAddressInfoType .
extensions	A pointer to an additional data structure.

Return Values

Standard (See [standard-return-values](#).)

Important

If `info_type` is set to `AddressInfoDNStatus`, T-Server will use the available information without sending a request to the switch. This is the only `info_type` supported by all T-Servers.