



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Configuration Layer Objects Reference Guide

CfgAgentInfo

CfgAgentInfo

Description

CfgAgentInfo contains information about an Agent.

Attributes

- **placeDBID** — A unique identifier of the **Place** assigned to this agent by default. The place must belong to the same tenant as the person in question unless this Agent belongs to the tenant Environment (with DBID=1)
- **skillLevels** — A pointer to the list of the agent's skill levels (every item of this list is structured as **CfgSkillLevel**).
When used as an entry in **CfgDeltaAgentInfo** (see below), it is a pointer to a list of skill levels added to the existing list.
- **agentLogins** — A pointer to the list of the agent logins assigned to this agent (every item of this list is structured as **CfgAgentLoginInfo**).
When used as an entry in **CfgDeltaAgentInfo** (see below), it is a pointer to a list of agent logins added to the existing list.
- **capacityRuleDBID** — A unique identifier of the capacity rule (**CfgScript**) associated with this agent.
- **siteDBID** — A unique identifier of Site (**CfgFolder**) with which this Agent is associated.
- **contractDBID** — A unique identifier of Cost Contract (**CfgObjectiveTable**) with which this Agent is associated.