



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Configuration Layer Objects Reference Guide

CfgStatTable

12/14/2025

---

## Contents

- [1 CfgStatTable](#)
  - [1.1 Description](#)
  - [1.2 Filter Keys](#)
  - [1.3 Attributes](#)
  - [1.4 Comments](#)
  - [1.5 XML Representation](#)
  - [1.6 See Also](#)

# CfgStatTable

## Description

*Statistical Tables* are groups of Statistical Days that represent statistically-modeled performances of Agent Groups over a calendar period of up to one year.

Call-processing applications can use Statistical Tables to provide load balancing between Agent Groups when the real-time statistics for those groups are unavailable.

## Filter Keys

| Filter Name   | Type   | Description   |
|---------------|--------|---|
| tenant_dbid   | int    | A unique identifier of a tenant. If specified, Configuration Server will return information only about the tables that are defined within this tenant.                              |
| table_type    | int    | Type of the table. If specified, Configuration Server will return information only about the tables of this type.   |
| group_dbid    | int    | A unique identifier of a group. If specified, Configuration Server will return information only about the tables assigned to this group.  |
| state         | int    | Current state of a stat table (see <a href="#">CfgObjectState</a> ). If specified, Configuration Server will return information only about tables that are currently in this state. |
| dbid          | int    | A unique identifier of a table. If specified, Configuration Server will return information only about this table.   |
| name          | string | Name of a table. Shall be specified as a character string. If specified, Configuration Server will return information only about the table(s) with that name.                       |
| stat_day_dbid | int    | A unique identifier of a stat day. If specified, Configuration Server will return information only about the tables containing this stat  |

---

| Filter Name | Type | Description |
|-------------|------|-------------|
|             |      | day.        |

## Attributes

- DBID — An identifier of this object in the Configuration Database. Generated by Configuration Server and is unique within an object type. Identifiers of deleted objects are not used again. Read-only.
- tenantDBID — A unique identifier of the **Tenant** that this table is defined for. Mandatory. Once specified, cannot be changed.
- name — A pointer to the name of the table. Mandatory. Must be unique within the tenant.
- type — Type of stat table. Once specified, cannot be changed. Refer to **CfgStatTableType**.
- statDayDBIDs — A pointer to the list of identifiers of the **Statistical Days** that constitute the table. When used as an entry in **CfgDeltaStatTable** (see below), it is a pointer to a list of days added to the existing list.
- state — Current object state. Mandatory. Refer to **CfgObjectState**.
- userProperties — A pointer to the list of user-defined properties. Parameter userProperties has the following structure: Each key-value pair of the primary list (TKVList \*userProperties) uses the key for the name of a user-defined section, and the value for a secondary list, that also has the TKVList structure and specifies the properties defined within that section.
- waitThreshold — The time the Universal Routing Server can wait until the corresponding resources become available.
- flatRate — A flat rate measured in cost units.
- agentHourlyRate — The hourly rate for an agent. This value is used only for Variable Rate Contracts.
- useFlatRate — Flag determining whether flatRate (CFGTrue) or agentHourlyRate (CFGFalse) should be selected. Refer to **CfgFlag**.

## Comments

Deletion of Stat Table X will cause the following events set out in the order of arrival:

- Modification of capacityTableDBID or quotaTableDBID of all agent groups that were associated with Stat Table X
- Modification of capacityTableDBID or quotaTableDBID of all place groups that were associated with Stat Table X
- Modification of capacityTableDBID or quotaTableDBID of all DN groups that were associated with Stat Table X
- Deletion of Stat Table X

## XML Representation

### Tip

This XML was created using the Configuration Server 7.5 schema.

```
<CfgStatTable>
  <DBID value="106" />
  <tenantDBID value="101" />
  <name value="az" />
  <type value="5" />
  <state value="1" />
  <userProperties>
    <list_pair key="Property">
      <str_pair key="key" value="value" />
    </list_pair>
  </userProperties>
  <waitThreshold value="0" />
  <flatRate value="0" />
  <agentHourlyRate value="0" />
  <useFlatRate value="2" />
</CfgStatTable>
```

## See Also

[CfgDeltaStatTable](#)

[CfgStatDay](#)