



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

T-Server Reference Guide

[TDeleteFromConference](#)

Contents

- 1 TDeleteFromConference
 - 1.1 Description
 - 1.2 Parameters
 - 1.3 Return Values

TDeleteFromConference

Description

A telephony object specified by `dn` deletes the telephony object specified by `dn_to_drop` from the conference call specified by `conn_id`. The client that invokes this service must be a party on the call in question.

Parameters

| Name | Description |
|-------------------------|--|
| <code>server</code> | Local server handle to the T-Server in question. |
| <code>dn</code> | Directory number of the telephony object that invokes delete-from-the-conference service. |
| <code>conn_id</code> | Connection identifier of the conference call from which the object is requested to be deleted. |
| <code>dn_to_drop</code> | Reference to the telephony object that is requested to be deleted from the conference call. This parameter can be either a <code>dn</code> or a <code>party_id</code> , where <code>party_id</code> is the party identifier given by the switch. |
| <code>reasons</code> | A pointer to a data structure that provides additional information associated with this action. |
| <code>extensions</code> | A pointer to an additional data structure. |

Return Values

Standard (See [standard-return-values](#).)