



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# T-Server Reference Guide

TMakeCall

5/1/2025

---

## Contents

- 1 TMakeCall
  - 1.1 Description
  - 1.2 Parameters
  - 1.3 Return Values

# TMakeCall

## Description

Originates a regular call from the telephony object specified by the parameter `dn` to the called party specified by the parameter `destination`.

## Parameters

Name	Description
<code>server</code>	Local server handle to the T-Server in question.
<code>dn</code>	Directory number of the telephony object from which the call is requested to be made.
<code>destination</code>	Directory number of the party that should be dialed.
<code>location</code>	Name of the remote location in the form of <code>&lt;SwitchName&gt;</code> or <code>&lt;T-ServerApplicationName&gt;@&lt;SwitchName&gt;</code> .
<code>call_type</code>	Refer to the type <b>TMakeCallType</b> .
<code>user_data</code>	A pointer to the user data that should be attached to the call.
<code>reasons</code>	A pointer to a data structure that provides additional information associated with this action.
<code>extensions</code>	A pointer to an additional data structure.

## Return Values

Standard (See `standard-return-values`.)