



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Mobile Services

8.5.236.01

12/20/2025

# 8.5.236.01

## Genesys Mobile Services Release Notes

Release Date	Release Type	Restrictions	AIX	Linux	Mac	Solaris	Windows
12/21/22	Update			X			X

### Contents

- **1 8.5.236.01**
  - 1.1 Helpful Links
  - 1.2 What's New
  - 1.3 Resolved Issues
  - 1.4 Upgrade Notes

## What's New

This release contains the following new features and enhancements:

- GMS now support two new command line parameters to manage a backup Config Server during startup:
  - -backuphost: the hostname/IP address for backup Config Server and
  - -backupport: the port for backup Config Server.

Example:

```
./launcher -host primaryhost -port primaryport  
-backuphost backuphost -backupport backupport -app  
"GMS236"
```

(GMS-8792)

- Cross-Origin Resource Sharing (CORS) can be now customized by editing the **launcher.xml** file instead of configuring Jetty. See [Possible Values for Access-Control-Allow-Origin Header \(CORS\)](#) for more information. (GMS-8828)

## Helpful Links

### Releases Info

- [List of 8.5.x Releases](#)
- [8.5.x Known Issues](#)

### Product Documentation

[Genesys Mobile Services](#)

### Genesys Products

[List of Release Notes](#)

## Resolved Issues

This release contains the following resolved issues:

---

When Context Services is disabled, GMS does not register the Configuration Business Attributes object changes reducing unnecessary Configuration cache updates. (GMS-8814)

---

GMS now includes the `_CB_T_CALLBACK_ACCEPTED`, `_CB_T_SERVICE_START`, and `_CB_T_CALLBACK_OFFERED` KVPs in the **RequestUpdateUserData** event when the customer is not connected during callback. (GMS-8697)

---

The GMS Callback Strategy can now manage HTTP requests with a retry option (in Disaster Recovery usecases) instead of using DFM that lacks the retry mechanism. A new option is available to use DFM in callback service definition, if needed:

- **\_enable\_gms\_dfm** = true (the default value). Set the value to false to manage HTTP requests. (GMS-8753)
-

## Upgrade Notes

No special procedure is required to upgrade to release 8.5.236.01.