



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Softphone

9.0.004.10

9.0.004.10

Genesys Softphone Release Notes

9.x Genesys Softphone is part of 9.x starting in **9.0.001.01**.

Release Date	Release Type	Restrictions	AIX	Linux	Solaris	Windows
12/21/18	General					X

What's New

This release contains the following new feature and enhancement:

- Support for TLS, up to version 1.2. (SOFTPHONE-534)

Resolved Issues

This release contains the following resolved issues:

During SIP Registration with FQDN, Genesys Softphone now correctly maintains a sticky registration session with one data center if the DNS resolution for SRV contact is significantly delayed. (SOFTPHONE-568)

Genesys Softphone no longer insecurely stores connectivity credentials. (SOFTPHONE-564)

You can now specify the path to the Genesys Softphone log file through the Connector interface by specifying the path in the 'sipendpoint.system.diagnostics.log_file' option in the Workspace application object. Previously, environment variables were not correctly interpreted if the path was

Helpful Links

Releases Info

- [List of 9.0.x Releases](#)
- [9.0.x Known Issues](#)

Product Documentation

- [Genesys Softphone](#)

Genesys Products

- [List of Release Notes](#)

specified with backslashes instead of forward slashes. (SOFTPHONE-561)

Genesys Softphone now correctly displays audio device names that are defined with 2-byte characters (for example, Japanese characters) in the 'devices' view of the user interface. Previously, these audio device names were not displayed in the Softphone user interface. (SOFTPHONE-547)

TLS transport now works correctly when the SIP Register address is specified by an SRV record. (SOFTPHONE-533)

The processing of SIP events is no longer delayed if it takes extra time to establish the audio layer for a particular call. Previously, in this scenario, a call could be dropped by the peer due to a lack of response to a later event. (SOFTPHONE-529)

Upgrade Notes

No special procedure is required to upgrade to release 9.0.004.10.