



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

SIP Server Deployment Guide

Deleting Party From Conference

Deleting Party From Conference

Contents

- [1 Deleting Party From Conference](#)
 - [1.1 Feature Configuration](#)
 - [1.2 Feature Limitations](#)

SIP Server now supports `TDeleteFromConference` requests in multi-site deployments in the same way as in single-site deployments; that is, any agent can remove any other party from the conference using a `TDeleteFromConference` request containing a targeted party DN.

Feature Configuration

To enable `TDeleteFromConference` requests support in multi-site deployments, configure the SIP Server Application, as follows:

1. In the `TServer` section, set the following configuration options:
 - `sip-enable-call-info`—Set this option to `true`.
The Call Participant Info functionality must be activated, enabling SIP Server to maintain an `LCTParty` list containing DNs and their locations for all parties present in the call. The `LCTParty` list is distributed to a `TLibrary` client in `EventUserEvent`.
 - `sip-remote-del-from-conf`—Set this option to `true`.
2. In the `extrouter` section, set the `use-data-from` configuration option to `current`. This enables Party Events propagation.

`sip-remote-del-from-conf`

Default Value: `false`

Valid Values: `true`, `false`

Changes Take Effect: Immediately

Related Option: `sip-enable-call-info`

In multi-site deployments, when this option is set to `true`, SIP Server processes a `TDeleteFromConference` request to remove a remote party (specified in `OtherDN`) from a conference. The `OtherDN` attribute of the `TDeleteFromConference` request must contain the party ID received in the `LCTParty` list. When this option is set to `false`, this feature is disabled.

Feature Limitations

- In a multi-site conference in which two DNs have identical names, if `TDeleteFromConference` is requested to remove a DN with the duplicate name, either one or both parties can be deleted from the conference.
- In multi-site scenarios, real-time statistics related to call supervision (particularly `CallObserved`) may be incorrect if the supervisor is released from the call before the call is finished. See Stat Server documentation for details.