



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workbench User's Guide

Workbench Kibana Application Type

12/14/2025

Contents

- 1 Workbench Kibana Application Type
 - 1.1 General Section
 - 1.2 Deployment Section
 - 1.3 Logging Section
 - 1.4 Workbench Kibana Identifiers

Workbench Kibana Application Type

General Section

Editable Option

Workbench Application Name

Default Values: "Workbench_Kibana_Primary"
Valid Values: Any String name (i.e. "WB_Kibana_Pri")
Changes Take Effect: Immediately
Description: The name of the Workbench Kibana application

Read Only Options

Workbench Application Type

Default Values: Workbench Kibana
Valid Values: Valid Workbench Application Type
Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup
Description: Workbench Application Type

Workbench Version

Default Values: "9.x.xxx.xx"
Valid Values: WB Version
Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup
Description: The Workbench Application Version

Associated Workbench Agent Application

Default Values: "WB_Kibana_Primary"
Valid Values: Name of associated Workbench Agent application
Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup
Description: The name of the Workbench Agent associated with this application/host

Data-Center

Default Values: default
Valid Values: Read-Only
Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup
Description: The name of the Data-Centre associated with this application; a preparatory setting that

will evolve in WB 9.x

Host Name

Default Values: *Hostname* of the Workbench Kibana application associated host (i.e. "LAB-WB-VM1")

Valid Values: Valid Hostname

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup

Description: The Hostname of the host where this Workbench Kibana application is running

Host IP Address

Default Values: *IP Address* of the Workbench Kibana application associated host (i.e. "10.20.30.40")

Valid Values: Valid IP address

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup

Description: The IPv4 Address of the host where this Workbench Kibana application is running

Host Time-Zone

Default Values: *Time-Zone* of the Workbench Kibana application associated host (i.e. "Europe/London")

Valid Values: Valid Host Time-Zone

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup

Description: The Time-Zone of the host where this Workbench Kibana application is running

Deployment Section

Read Only Options

Installation Directory

Default Values: "<WORKBENCH_HOME>\Kibana"

Valid Values: Valid Path (i.e. C:\Program Files\Workbench_9.x.xxx.xx\Kibana")

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup

Description: Absolute path of the folder where this application is installed

Configuration Directory

Default Values: "<WORKBENCH_HOME>\Kibana\config"

Valid Values: Valid Path (i.e. C:\Program Files\Workbench_9.x.xxx.xx\Kibana\config")

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup

Description: Absolute path of the folder where the configuration file of this application is located

Logging Section

Editable Options

Log File Folder

Default Values: "<WORKBENCH_HOME>\Kibana\logs\kibana.log"

Valid Values: Valid folder path

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") restart

Description: Absolute path of the log file location

Verbose Log

Default Values: False

Valid Values: True, False

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") restart

Description: Set the value of this setting to true to log all events, including system usage information and all requests.

Silent Log

Default Values: False

Valid Values: True, False

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") restart

Description: Set the value of this setting to true to suppress all logging output.

Quiet Log

Default Values: False

Valid Values: True, False

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") restart

Description: Set the value of this setting to true to suppress all logging output other than error messages.

Important

- Only enabled 1 of the "Verbose Log", "Quiet Log" or "Silent Log" options above; else the Workbench Kibana component could fail to start.

Warning

- Kibana does not provide Kibana log file rotation.
- Therefore please monitor/manage this Kibana log file accordingly to ensure it does not grow indefinitely and negatively impact the host and/or its applications

Workbench Kibana Identifiers

Editable Options

HTTP Port

Default Values:

- For WB 9.0 to 9.2 the default port is: 8181 (or the port number given at custom installation time)
- For WB 9.3 the default port is: 8182 (or the port number given at custom installation time)

Valid Values: Valid free port integer

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") restart
Description:

- For WB 9.0 to 9.2 - the main UI 8181 port for incoming HTTP Chrome Browser requests.
- For WB 9.3 - changed to 8182 by default

Warning

- Restart of Workbench Kibana and Workbench Heartbeat is required when changing this option.
- The new Workbench URL would be `http://<WB_Primary_Host>:<THE_NEW_HTTP_PORT>`.

Workbench Elasticsearch Host

Default Values: "http://<HOSTNAME>:9200 (i.e. "`http://MY-WB-VM:9200`")

Valid Values: Valid Elasticsearch Hostname and Port)

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") restart

Description: IPv4 address of the host where Elasticsearch (to which Kibana is going to connect) is running

Read Only Options

Host Name

Default Values: Hostname of the Workbench Kibana application associated host (i.e. "LAB-WB-VM1")

Valid Values: Valid Hostname

Changes Take Effect: After Workbench Kibana application (i.e. "WB_Kibana_Primary") startup

Description: The Hostname of the host where this Workbench Kibana application is running.