Microsoft Skype for Business Deployment Guide

Configuring Skype for Business Application Endpoints

4/11/2025

Configuring Skype for Business Application Endpoints

You can configure Skype for Business application endpoints using the Management Shell.

Using the procedures described in Microsoft documentation, complete the following steps:

1. Create **Trusted Application Endpoints** for Routing Points.
   For example:
   ```
   New-CsTrustedApplicationEndpoint -ApplicationId "Connector_app"
   -TrustedApplicationPoolFqdn "trustedpool.skype.lab" -SipAddress
   "sip:RP1@skype.lab" —LineURI TEL:16505551212
   ```

   - where the value of the parameter `SipAddress` must correspond to the name of the Routing Point DN object in the Genesys configuration environment.

2. Create **Trusted Application Endpoints** for External Routing Points.
   For example:
   ```
   New-CsTrustedApplicationEndpoint -ApplicationId "Connector_app"
   -TrustedApplicationPoolFqdn "trustedpool.skype.lab" -SipAddress
   "sip:ERP1@skype.lab" —LineURI "TEL:14155551212"
   ```

   - where the value of the parameter `SipAddress` must correspond to the name of the External Routing Point DN object (in the Genesys configuration environment) and the <number> in the parameter LineURI must correspond to the `Association` field of that External Routing Point object.

3. Create **Trusted Application Endpoints** for conference services.
   The endpoint names must be created based on the pattern in the **uri-pattern** option and their quantity must match the **count** option set on the Switch object.

   For example: If `uri-pattern=sip:conf{DD}@skype.lab` and count=99, then you must create 99 endpoints with names from `sip:conf01@skype.lab` to `sip:conf99@skype.lab`, where numbers from 1-99 are endpoint numbers.

   See also how to work with conference resource pools

Trusted Application Endpoints for conference services

See Conference Resource Pools for details.