

# **GENESYS**<sup>®</sup>

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Events and Models Reference

**Registration Events** 

4/2/2025

# Contents

- 1 Registration Events
  - 1.1 EventRegistered
  - 1.2 EventUnregistered

# Registration Events

# EventRegistered

#### Description

The application has been registered to send requests and receive events regarding the telephony object specified by ThisDN.

#### Contents

Event Attribute	Туре
AgentID <sup>a</sup>	Optional
CustomerID	Optional
Event	Mandatory
Extensions <sup>b</sup>	Mandatory
InfoStatus.AddressType	Optional
InfoType=AddressInfoAddressType	Mandatory
ReferenceID	Mandatory
Server	Mandatory
ThisDN	Mandatory
time	Mandatory


a. The AgentID attribute can only be present for objects of AddressTypePosition or AddressTypeDN. See the contents of Extensions.

b. The Extensions attribute contains the same information as in EventAddressInfo:

- For objects of AddressTypePosition or AddressTypeDN, see the corresponding InfoType=TAddressInfoDNStatus.
- For objects of AddressTypeQueue, AddressTypeRouteDN, or AddressTypeRouteQueue, see InfoType=TAddressInfoQueueStatus.

#### **Registration Events**

#### Example



EventRegistered Feature Example

### EventUnregistered

#### Description

The application's registration to send requests and receive events regarding the telephony object specified by ThisDN has been canceled.

#### Contents

Event Attribute	Туре
CustomerID	Optional
ErrorCode	Optional
ErrorMessage	Optional
Event	Mandatory
ReferenceID <sup>a</sup>	Optional
Server	Mandatory
ThisDN	Mandatory
time	Mandatory
Extensions	Optional

a. The ReferenceID attribute is mandatory in most cases, but not present if the switch configuration has been changed while the CTI link was down or if T-Server configuration has been changed dynamically through Configuration Manager. Meanwhile, the cause of unregistration is specified by the attributes ErrorCode and ErrorMessage.

## Example



EventUnregistered Feature Example