



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Events and Models Reference

Subscribing to Transaction Monitoring

5/4/2025

Contents

- 1 Subscribing to Transaction Monitoring
 - 1.1 TTransactionMonitoring
 - 1.2 Subscription Rules

Subscribing to Transaction Monitoring

To initiate transaction monitoring, your code must call the following function.

TTransactionMonitoring

This function requests a T-Server to start, stop, or modify a subscription to the Transaction Monitoring Feature notifications. If a request is successful (EventACK), EventTransactionStatus (EventTransactionStatus) is distributed to the requestor.

Syntax

```
int TTransactionMonitoring (
    TServer
    TSubscriptionOperationType
    const char
    const TKVList
    tserver_handle,
    subscription_operation,
    * subscription_identifier,
    * subscription_rules
);
```

Parameters

- tserver_handle—Local server handle to the T-Server in question.
- subscription_operation—This parameter represents an operation on a subscription to Transaction Monitoring Feature notifications. Its value is one of TSubscriptionOperationType. A value of this parameter should be provided by the T-Server client.
- subscription_identifier—This parameter represents a subscription identifier. A value should be NULL for the operation SubscriptionStart. For other operations its value should be taken from the message EventACK. It is generated by a T-Server on a creation of a new subscription.
- subscription_rules—This parameter contains subscription rules. A value of this parameter should be provided by the T-Server client. Its value should be NULL for the operation SubscriptionStop. See [Subscription Rules](#) for details.

Return Values

The Transaction Monitoring Feature return value is a standard return value for the T-Library API:

- >0—Reference number (ReferenceID) assigned to this request by the T-Library API.
- <0—Error condition.

Subscription Rules

Subscription rules are provided by T-Server clients and passed as part of a `notify` key-value pair in the `Extensions` attribute for `RequestTransactionMonitoring`. They are represented as a key-value list.

Every subscription rule key-value pair contains a notification mode for one element. The key represents the name of the element. The value represents the requested notification mode. If no key has as its name a given element, then that element's default notification mode is used. See [Transaction Monitoring Elements](#) for the list of all default notification modes.

Example

The following is an example `RequestTransactionMonitoring` with subscription rules included:

```
AttributeReferenceID reference-id-1
AttributeSubscriptionOperation SubscriptionStart
AttributeExtensions
  notify (list)
    class.name always
    object.local-id always
    iscc.transaction.state always
    iscc.direction.role once
    iscc.is-link-creation never
```

The local attribute `object.local-id` represents a unique identifier of the Local Transaction Instance. The value of this attribute is different from the value of the Global Identifier attribute.