



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

T-Server for CSTA Connector Deployment Guide

Debug Log Options

12/17/2025

Debug Log Options

The options in this section enable you to generate Debug logs containing information about specific operations of an application.

x-conn-debug-all

x-conn-debug-all

Default Value: 0 (zero)

Valid Values:

0	Log records are not generated.
1	Log records are generated.

Changes Take Effect: After restart

Generates Debug log records about open connection, socket select, timer creation and deletion, write, security-related, and DNS operations, and connection library function calls. This option is the same as enabling or disabling all of the previous x-conn-debug-<op type> options.

Warning: Use this option only when requested by Genesys Technical Support.

x-conn-debug-api

x-conn-debug-api

Default Value: 0 (zero)

Valid Values:

0	Log records are not generated.
---	--------------------------------

1	Log records are generated.
---	----------------------------

Changes Take Effect: After restart

Generates Debug log records about connection library function calls.

Warning: Use this option only when requested by Genesys Technical Support.

x-conn-debug-dns

x-conn-debug-dns

Default Value: 0 (zero)

Valid Values:

0	Log records are not generated.
1	Log records are generated.

Changes Take Effect: After restart

Generates Debug log records about DNS operations.

Warning: Use this option only when requested by Genesys Technical Support.

x-conn-debug-open

x-conn-debug-open

Default Value: 0 (zero)

Valid Values:

0	Log records are not generated.
---	--------------------------------

1	Log records are generated.
---	----------------------------

Changes Take Effect: After restart

Generates Debug log records about *open connection* operations of the application.

Warning: Use this option only when requested by Genesys Technical Support.

x-conn-debug-security

x-conn-debug-security

Default Value: 0 (zero)

Valid Values:

0	Log records are not generated.
1	Log records are generated.

Changes Take Effect: After restart

Generates Debug log records about security-related operations, such as Transport Layer Security and security certificates.

Warning: Use this option only when requested by Genesys Technical Support.

x-conn-debug-select

x-conn-debug-select

Default Value: 0 (zero)

Valid Values:

0	Log records are not generated.
---	--------------------------------

1	Log records are generated.
---	----------------------------

Changes Take Effect: After restart

Generates Debug log records about *socket select* operations of the application.

Warning: Use this option only when requested by Genesys Technical Support.

x-conn-debug-timers

x-conn-debug-timers

Default Value: 0 (zero)

Valid Values:

0	Log records are not generated.
1	Log records are generated.

Changes Take Effect: After restart

Generates Debug log records about the timer creation and deletion operations of the application.

Warning: Use this option only when requested by Genesys Technical Support.

x-conn-debug-write

x-conn-debug-write

Default Value: 0 (zero)

Valid Values:

0	Log records are not generated.
---	--------------------------------

1	Log records are generated.
---	----------------------------

Changes Take Effect: After restart

Generates Debug log records about the *write* operations of the application.

Warning: Use this option only when requested by Genesys Technical Support.