



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Workforce Management Administrator's Guide

WFM Data Aggregator Options

4/25/2025

WFM Data Aggregator Options

From the Options tab you can modify the default WFM Data Aggregator configuration settings. The tab contains four sections. The options in each of these sections are described below.

Client Section

[+]

CfgServerRequestTimeout

Type: Mandatory

Default Value: 10

Valid Values: Any positive integer

Dependencies: None

Specifies the number of seconds to wait for a response from Configuration Server before timing out. This key is used when requesting the list of objects from Configuration Server for synchronization purposes. The value should be increased in configurations with a high number of objects or slow network connections.

SOAPTimeout

Type: Mandatory

Default Value: 90

Valid Value: Any positive integer

Dependencies: None

Specifies the SOAP connection timeout, in seconds.

[Back to Top](#)

Identity Section

[+]

ApplicationType

Type: Optional in a Framework 8.x environment.

Default Value: WFMDataAggregator

Valid Value: WFMDataAggregator

Dependencies: None

Specifies the Workforce Management component for which this application is used. Configure this option only if you are using an application of the type ThirdPartyServer.

[Back to Top](#)

Logs Section

[+]

verbose

Type: Mandatory

Default Value: all

Valid Values: all, trace, standard, none, yes (= all), no (= none)

Dependencies: None

Filters output of log messages based on their assigned priority. All enables output of all messages to the log file. Setting the option value to:

- trace—Enables informational and error messages and disables debug messages.
- standard—Enables error messages only and disables informational and debug messages.
- none—Disables all messages.

buffering

Type: Mandatory

Default Value: no

Valid Values: yes, no

Dependencies: None

Turns system file buffering on (yes) or off (no).

segment

Type: Mandatory

Default Value: no

Valid Values: no, <number>, <number>KB, <number>MB, <number>Hr

Dependencies: None

Sets the maximum size (in KB, MB, or hours) of the log file segment, after which a new segment is created. The default size is in KB. The number cannot be less than 100 KB or less than one hour. Setting this option value to no indicates no segmentation of the log file.

expire

Type: Mandatory

Default Value: no

Valid Values: no, <number>, <number> file, <number> day

Dependencies: None

Sets the Expiration mode for old segments. The number to be stored cannot be less than 1 file or 1 day or more than 100 files or 100 days. Setting this option value to no indicates that files do not expire.

messagefile

Type: Mandatory

Default Value: wfmdataaggregator.lms

Valid Value: wfmdataaggregator.lms

Dependencies: None

Sets the name of the file that stores application-specific log messages. The only valid value is wfmdataaggregator.lms.

standard

Type: Mandatory

Default Value: stdout

Valid Values (log output types): stdout, stderr, syslog, network, <filename>

Dependencies: None

Specifies that log events of the Standard level are to be sent to the listed outputs. For centralized logging, set this option value to network. You can use a local file name or stdout, as well as network.

trace

Type: Mandatory

Default Value: stdout

Valid Values (log output types): stdout, stderr, syslog, network, <filename>

Dependencies: None

Specifies that log events of the Trace level are to be sent to the listed outputs. For centralized logging, set this option value to network. You can use a local file name, stdout, as well as network.

debug

Type: Mandatory

Default Value: stdout

Valid Values (log output types): stdout, stderr, syslog, network, <filename>

Dependencies: None

Specifies that log events of the Debug level are to be sent to the listed outputs.

Warning

Do not use network unless requested by Genesys Professional Services, because it generates extremely heavy message loads that can degrade system performance.

all

Type: Mandatory

Default Value: stdout

Valid Values (log output types): stdout, stderr, syslog, network, <filename>

Dependencies: None

Specifies that log events of all levels, Standard, Trace, and Debug, are to be sent to the listed outputs.

Warning

Do not use network unless requested by Genesys Professional Services, because it generates extremely heavy message loads that can degrade system performance.

x-DBWriterTrace

Type: Optional

Default Value: No default value

Valid Values: yes, no

Dependencies: None

When set to yes (or true or 1), this option enables an additional logging option that is used by Data Aggregator to record how a statistic's records are being stored in the database.

x-LogAgentEventTrace

Type: Optional

Default Value: No default value

Valid Values: yes, no

Dependencies: None

Specifies whether or not Data Aggregator writes agent event data to a log file. This option is used for debugging only.

x-LogConfigServerConnectionTrace

Type: Optional

Default Value: No default value

Valid Values: yes, no

Dependencies: None

Specifies whether or not Data Aggregator writes Configuration Server connection data to a log file. This option is used for debugging only.

x-LogConfigServerTrace

Type: Optional

Default Value: No default value

Valid Values: yes, no

Dependencies: None

Indicates whether Data Aggregator should write Configuration Server process data to a log file. This option is used for debugging only.

x-LogSynchronizationTrace

Type: Optional

Default Value: No default value

Valid Values: yes, no

Dependencies: None

Specifies whether or not Data Aggregator writes Configuration Server synchronization data to a log file. This option is used for debugging only.

x-LogWFMServerTrace

Type: Optional

Default Value: No default value

Valid Values: yes, no

Dependencies: None

Specifies whether or not Data Aggregator writes WFM Server process data to a log file. This option is used for debugging only.

[Back to Top](#)

Options Section

[+]

AcceptZeroSkillLevel

Type: Optional

Default Value: false

Valid Value: true, false

Dependencies: None

Specifies whether or not WFM Data Aggregator can set an agent skill level to 0. When this option is set to `true` it enables Data Aggregator to set an agent skill level to 0. When set to `false` it prevents (disables) Data Aggregator from setting an agent skill level to 0.

DBDumpFile

Type: Optional

Default Value: No default value

Valid Value: Any valid file name

Dependencies: None

Specifies a file to which WFM Data Aggregator writes its current data if it loses its connection to the database. When Data Aggregator is restarted or the connection to the database is restored, it locates the dump file, retrieves the data, writes it to the database, and then deletes the dump file. If you do not specify a file name, the file is `DBdump.dat` located in `\\...\Workforce Management\Data Aggregator`.

HandleTimeWriteBack

Type: Optional

Default Value: No default value

Valid Value: 1-12

Dependencies: None

Enables you to add average handling time (AHT) to a prior timestep if no calls were handled in the current timestep. This option prevents WFM Data Aggregator from setting AHT to zero for timesteps in which agents performed after call/contact work (ACW) for calls that had occurred in a prior timestep.

If this key is present and has an integer value between 1 and 12, WFM Data Aggregator searches for a prior timestep in which at least one call was handled. If it finds such a timestep, it updates that timestep's statistics to incorporate ACW performed in the current timestep.

This key's value determines the number of timesteps that WFM Data Aggregator searches back. Therefore, the ACW must occur within 12 timesteps, or 3 hours, after the call's completion. A value of 0 (zero) disables this option.

Important

Some calls are brief enough to be considered short-abandoned calls, but they begin and end in different timesteps and thus require special handling to avoid skewing Call Center data. WFM Data Aggregator can identify a call like this because the timestep where it ends has an associated `HandleTime` statistic but no `HandleVolume` statistic. WFM Data Aggregator uses the value of the `HandleTimeWriteBack` option when searching for the beginning of a short-abandoned call like this, to adjust the prior timestep where that call began. See the topic "Configuration > Activities > Statistics Configuration for Activities" in [WFM Configuration Utility Help](#).

ReasonCodeKeyName

Type: Optional

Default Value: ReasonCode

Valid Value: Any valid reason-code key name

Dependencies: None

Specifies the reason (aux)-code key used in the enterprise. It is not necessary to configure this option if you do not use reason codes. Data Aggregator can process reason codes that come from hard and/or soft phones. To receive reason codes from hard phones, or in a mixed hard/soft phone environment, set the Data Aggregator Application's ReasonCodeKeyName option value to ReasonCode in Configuration Manager.

Important

You can only use reason codes from hard phones if you are using Stat Server 7.x.

ReasonCodeWaitTime

Type: Optional

Default Value: 15

Valid Value: 2-600

Dependencies: None

Necessary only if you are using a pre-6.5 release of Stat Server and are using reason codes. It specifies how long, in seconds, Data Aggregator delays processing information during a timestep while waiting for reason code information. This parameter is useful when Stat Server and/or the network are busy enough to delay reason code data.

ScheduleLookAheadMinutes

Type: Optional

Default Value: No default value

Valid Value: 0-1440

Dependencies: None

Specifies how many additional minutes of agent schedules should be loaded from WFM Server for adherence calculations. Should be used only in environment where agent schedules and configuration are updated infrequently.

SynchronizeUnassignedAgents

Type: Optional

Default Values: true, yes

Valid Value: true, yes, false no

Dependencies: None

Specifies whether or not WFM Data Aggregator should synchronize agents who are not assigned to any site. If more than one WFM Data Aggregator is configured to perform synchronization on the same database, then Genesys recommends that you set this option to yes for only one WFM Data Aggregator.

[Back to Top](#)