

Gplus Adapter 5.4

for IEX WFM

Installation and Configuration Guide

The information contained herein is proprietary and confidential and cannot be disclosed or duplicated without the prior written consent of Genesys Telecommunications Laboratories, Inc. Copyright © 2014 Genesys Telecommunications Laboratories, Inc. All rights reserved.

About Genesys

Genesys is the world's leading provider of customer service and contact software - with more than 4,000 customers in 80 countries. Drawing on its more than 20 years of customer service innovation and experience, Genesys is uniquely positioned to help companies bring their people, insights and customer channels together to effectively drive today's customer conversation. Genesys software directs more than 100 million interactions every day, maximizing the value of customer engagement and differentiating the experience by driving personalization and multi-channel customer service - and extending customer service across the enterprise to optimize processes and the performance of customerfacing employees. Go to <u>www.genesys.com</u> for more information.

Each product has its own documentation for online viewing at the Genesys Documentation website.

Notice

Although reasonable effort is made to ensure that the information in this document is complete and accurate at the time of release, Genesys Telecommunications Laboratories, Inc. cannot assume responsibility for any existing errors. Changes and/or corrections to the information contained in this document may be incorporated in future versions.

Your Responsibility for Your System's Security

You are responsible for the security of your system. Product administration to prevent unauthorized use is your responsibility. Your system administrator should read all documents provided with this product to fully understand the features available that reduce your risk of incurring charges for unlicensed use of Genesys products.

Trademarks

Genesys and the Genesys logo are registered trademarks of Genesys Telecommunications Laboratories, Inc. All other company names and logos may be trademarks or registered trademarks of their respective holders. © 2014 Genesys Telecommunications Laboratories, Inc. All rights reserved.

Technical Support from VARs

If you have purchased support from a value-added reseller (VAR), please contact the VAR for technical support.

Ordering and Licensing Information

Complete information on ordering and licensing Genesys products can be found in the <u>Genesys Licensing Guide</u>.

Released by: Genesys Telecommunications Laboratories, Inc. http://www.genesys.com/

Document Version: 54gp_icg_iex-wfm_05-2014_v5.4.001.00



Table of Contents

Preface	Preface	7
	About Gplus Adapter for IEX WFM	7
	Intended Audience	7
	Making Comments on This Document	8
	Contacting Genesys Customer Care	8
	Related Documentation Resources	8
	Document Conventions	9
	Document Version Number	9
	Type Styles	9
Chapter 1	Product Description	11
	Historical Reports	11
	Real Time Adherence (RTA)	12
Chapter 2	Installation and Setup	
	Installation and Windows Permissions	13
	Included Files	13
	Logging, FTP and Report Directories	15
	Adding an Adapter Instance to the Configuration Server	16
	Java Virtual Machine	17
	Configuration Server Connection	23
	Solution Control Server Integration	
	Logging Configuration	29
	Initial Start Up Test	32
	License File	
Chapter 3	Application Options	35
	alarmCodes Section	35
	application Section	
	attachedDataFilter Section	43
	callTypes.custom Section	
	chat Section	45
	email Section	48

	event.properties Section	51
	filter: <filtername> Section</filtername>	54
	genesys.agentGroups Section	55
	genesys.placeGroups Section	56
	genesys.queueGroups Section	57
	historical.ftp Section	
	historical.reports Section	62
	historical: <streamname> Section</streamname>	65
	interactionCodeMappings Section	66
	interactionTargets Section	67
	ixnProcessObjects Section	68
	media: <name> Section</name>	69
	outbound Section	77
	readyCodeMappings Section	78
	reasonCodeMappings Section	79
	rta Section	80
	rta: <streamname> Section</streamname>	82
	voice Section	83
Chapter 4	Additional Configuration	
	Adding T-Servers and Interaction Servers	
	Threshold Time Format	
	Adding Annex Data for Virtual Queues and Skills	
	Adding A PlaceGroup to a Site	90
Chapter 5	Setting Up Secure File Transfer	
	Generating the Private-Public Key Pair	91
	Client Configuration	
	Server Configuration	92
Chapter 6	Outbound Voice Campaigns	
	Predictive and Progressive Campaigns	
	Preview and Push Preview Campaigns	
	Non Campaign Outbound Calls	96
Chapter 7	Streams and Filters	
	Multiple Streams	97
Appendix A	Time Zone ID List	99
Appendix B	Secure File Transfer Problems	106

Appendix C	Managing Windows Service	111
Appendix D	Log Files	116
Appendix E	Windows Installation Script	

Table of Contents



Welcome to the Gplus Adapter for IEX WFM - Installation and Configuration Guide. This document describes the Gplus Adapter for IEX WFM (the Gplus Adapter) and lists the steps required to install and configure the components of this Adapter.

This document is valid only for the 5.4 release(s) of this product.

Note: For versions of this document created for other releases of this product, visit the Genesys Technical Support website.

For information about related resources and about the conventions that are used in this document, see the supplementary material starting on page 8.

About Gplus Adapter for IEX WFM

The *Gplus* Adapter for IEX WFM is a software solution that provides integration between an IEX TotalView Workforce Management (WFM) system and Genesys routing solutions. Genesys event data is filtered and aggregated to provide interval activity data and a real-time data feed for IEX TotalView.

Intended Audience

- This document is primarily intended for system administrators or other individuals who will be installing the G*plus* Adapter and have a basic understanding of the following:
 - Computer-telephony integration (CTI) concepts, processes, terminology and applications.
 - TCP/IP networking fundamentals including routing and client/server application communications via TCP sockets.

- IEX TotalView conventions and reports.
- The network configurations used in the installation computing environment.
- The following Genesys applications and solutions:
 - Framework 7.0 8.x
 - Configuration Manager
 - Universal Routing 7.0 8.x

Making Comments on This Document

If you especially like or dislike anything about this document, feel free to e-mail your comments to <u>Techpubs.webadmin@genesys.com</u>.

When you send us comments, you grant Genesys a nonexclusive right to use or distribute your comments in any way it believes appropriate, without incurring any obligation to you.

Contacting Genesys Customer Care

If you have purchased support directly from Genesys, see the <u>Contact Information</u> on the Customer Care website. Before contacting Customer Care, refer to the <u>Genesys Care</u> <u>Program Guide</u> for complete contact information and procedures.

Related Documentation Resources

The following resources provide additional information that is relevant to this software. Consult these additional resources as necessary:

- The *Gplus WFM Adapter 5.4 Hardware and Software Requirements*, which will help in ensuring that the Adapter is installed with sufficient resources.
- The *Framework 8.1 Configuration Manager Help*, which will help when using Configuration Manager.
- The *Genesys 8.1 Security Deployment Guide*, which will help when configuring secure connections to the TServer(s), SIP Server(s), Interaction Server(s) and Configuration Server(s).
- The *Genesys Technical Publications Glossary*, which ships on the Genesys Documentation Library CD and which provides a comprehensive list of the Genesys and CTI terminology and acronyms used in this document.

• The Release Notes and Product Advisories and Genesys product documentation for this product are available on the Genesys Documentation website at http://docs.genesys.com/Documentation.

Document Conventions

This document uses certain stylistic and typographical conventions—introduced here—that serve as shorthand for particular kinds of information.

Document Version Number

A version number appears at the bottom of the inside front cover of this document. Version numbers change as new information is added to this document. Here is a sample version number:

54gp_icg_iex-wfm_06-2014_v5.4.001.00

You will need this number when you are talking with Genesys Technical Support about this product.

Type Styles

The Type Styles table describes and illustrates the type conventions that are used in this document.

Type Styles

Type Style	Used For	Examples
Italic	 Document titles Emphasis Definitions of (or first references to) unfamiliar terms 	Please consult the <i>Genesys</i> <i>Migration Guide</i> for more information. Do <i>not</i> use this value for this option.
Monospace font (Looks like teletype or typewriter text)	 All programming identifiers and GUI elements. This convention includes: The <i>names</i> of directories, files, folders, configuration objects, paths, scripts, dialog boxes, options, 	Select the Show variables on screen check box. In the Operand text box, enter your formula. Click OK to exit the Properties dialog box. T-Server distributes the error

	 fields, text and list boxes, operational modes, all buttons (including radio buttons), check boxes, commands, tabs, CTI events, and error messages. The values of options. Logical arguments and command syntax. Code samples. Also used for any text that users must manually enter during a configuration or installation procedure, or on a command line. 	messages in EventError events. If you select true for the inbound-bsns-calls option, all established inbound calls on a local agent are considered business calls. Enter exit on the command line.
Angle brackets (<>)	A placeholder for a value that the user must specify. This might be a DN or a port number specific to your enterprise.	smcp_server -host ≺confighost>



Chapter

1 Product Description

Historical Reports

The IEX Historical reports are contained in one file with the start and end of each report indicated by delimiting lines in that file:

- Contact Queue Report Customer interaction interval report
- Agent Contact Queue Report Agent/customer interval report
- Agent System Performance Report Agent activity interval report
- Agent Sign-On/Sign-Off Report Agent daily sign-on report

A file containing the first three reports is generated on either a 15 or 30 minute interval depending upon the client preference. The daily Agent Sign-On/Sign-Off report is added to the file with the other three reports at midnight.

Real Time Adherence (RTA)

RTA tracks agent state to ensure that the agents are in compliance with their set schedules. IEX does not stipulate a standard set of RTA states so the states tabulated below have been selected as the "standard" used by the *Gplus* Adapter for IEX WFM.

Agent States	Voice States	Email States
SignOut	CallInbound	EmailInbound
NotReady	DirectCallInbound	EmailReply
Available	CallOutbound	EmailOutbound
DndOn	CallInternal	AfterEmailWork
	CallOnHold	
	CallConsult	
	Conference	
	AfterCallWork	
iWD/OpenMedia States	Outbound States	Chat States
InteractionInbound	OutboundPreview	ChatInbound
InteractionInternal	OutboundCampaignCall	ChatInternal
AfterInteractionWork		AfterChatWork

Note: While IEX supports a synchronous and asynchronous connection protocol for the RTA connection, this version of the adapter only supports the asynchronous option.



Chapter

2 Installation and Setup

Installation and Windows Permissions

File and folder permissions can be a factor when installing the *Gplus* Adapter on Windows Server versions. It is recommended that the same User with Administrator privileges install the adapter files, the Java instance and the Adapter as a Windows Service. The installed service may fail to start if the access permissions are not aligned.

Included Files

The application installation package contains all of the required components with the exception of the Java Runtime Environment (JRE). Installation of the application is a matter of copying the distribution files into a suitable directory. An example is shown below:

Folders

- GPLusAdapter/config
- GPlusAdapter/lib
- GPlusAdapter/ftp
- GPlusAdapter/licenses
- GPlusAdapter/logs
- GPlusAdapter/res
- GPlusAdapter/recovery
- GPlusAdapter/scripts
- GPLusAdapter/wrappers

- configuration files and license file
- application jar files
- reports folders
- third party software licenses
- log files
- report templates
- recovery log files
- Windows and "unix" scripts
- Java Windows Service wrappers

Files

GPlusAdapter\

• bootstrap.jar – start up jar file

GPlusAdapter\scripts\windows\

- windows_install.bat installation script
- encryptPassword.bat.example password encryption script
- serverHostName.bat.example hostname script
- startup.bat.example console start up script
- svcinstall.bat.example service installation script

Note: The scripts\windows folder contains a subroutines folder that holds the scripts called by windows_install.bat. There is nothing to configure in this folder and it should not be tampered with.

GPlusAdapter/scripts/unix_bash/

- encryptPassword.sh.example password encryption script
- serverHostName.sh.example hostname script
- shutdown.sh
 - startup.sh.example start up script

GPlusAdapter\config

•

•

•

.

- GPLusWFM.properties Configuration Server connection
- product.properties
- jvm.properties
 - log4j.xml.example logging configuration
- License.txt
- GPlusAdapter\res\reportTemplates

Agent Contact Queue report template

– license file

- shut down script

IexAso.tpl

IexAcq.tpl

IexAsp.tpl

- Agent SignOn/SignOff report template
- Agent System Performance report template

- Adapter name and version

– JVM location, memory and type

IexCq.tpl – Contact Queue report template

Logging, FTP and Report Directories

A default set of folders for log files and historical reports are included as part of the installation package. These folders (with the exception of the recovery folder) do not have to be used and the configuration options allow for alternatives.

Logging

- Default Logs folder
- The number, size and location of the adapter log files are set in the Log4j.xml file contained in the config folder.
- The default service install script for Windows creates the AdapterService, service-stdout and service-stderr log files in the Logs folder but their location can be changed.

Reports

- Default ftp/reports folder
- Option historical.reports/directory
- Reports folders for historical streams are automatically created as subfolders of the reports folder using the stream name as the subfolder name.
- Normal operation sees the report files transferred to a remote server and the local copy removed from the reports folder.
- The number of days that the report files are retained if they are not transferred is set with the historical.reports/reportRetentionDays Option.

FTP Source

- Default ftp/reports folder
- Option historical.ftp/localSourceDirectory
- The G*plus* Adapter attempts to transfer all of the files contained in this folder immediately after the report generation task has ended.

FTP Backup

- Default ftp/reportsBackup folder
- Option historical.ftp/localBackupDirectory
- Backup folders for historical streams are automatically created as subfolders of the backup folder using the stream name as the subfolder name.
- The number of days that the FTP backup files are retained is set as an application option in the historical.ftp section.

Recovery

- Default recovery folder
- This folder contains the archived logs of all of the events received by the *Gplus* Adapter instance for the last seven days.
- Neither the folder nor the log files should be tampered with as the *Gplus* Adapter replays the last day's events at startup to recover the state prior to shutting down.

Adding an Adapter Instance to the Configuration Server

The Adapter does not use a wizard application to simplify the installation but rather requires manual steps to add the application to the Configuration Server and complete the configuration. The present version of the Adapter does not support installation with the Genesys Administrator and its meta-data files. It is recommended that the Adapter be installed using the Genesys Configuration Manager.

Importing the Application Template

The templates folder contains the GPlus_Adapter_IEX_54.apd file that defines the properties for the adapter's Application Template. This file should be moved to a location accessible by the computer running the Genesys Configuration Manager so that it can be imported into the Configuration Server.

Once the Application Template has been imported, the name should be confirmed prior to saving it. GPLus_Adapter_IEX_54 is one possibility but alternatives are also acceptable as long as the template name is unique.

Creating the Application in the Configuration Layer

An empty application can be created after the Application Template has been added to the Configuration Layer.

- 1. Select the Applications folder and right click in the right frame to bring up the menu.
- 2. Select New ... Application.
- 3. Select the recently imported Gplus Adapter template.

Once the template is selected, an Application Properties window will appear. Once again, a unique name should be entered for the Adapter instance. At this point, one option would be to continue with the configuration of the new application object but it is suggested that new application be saved by selecting the OK button. Saving the new Application object requires that something be added to the fields in the Start Info tab. Periods ('.') will suffice until the start information is properly configured.

Java Virtual Machine

The *Gplus* Adapter is a Java application that runs in a Java Virtual Machine (JVM) that isolates the application from the underlying operating system. The significant benefit is that the same code runs on more than one operating system. One downside is that there is some configuration required to properly start the application in the JVM. There are two steps to successfully starting the *Gplus* Adapter:

- Invoking the Java application launcher to load and run the Adapter application in the JVM.
- Connecting to the Genesys Configuration Server to obtain the saved application configuration options.

The first of these two steps differs slightly between Windows and "unix" installations. Additionally, a *Gplus* Adapter instance installed on a Windows server can be started as a console application or as a Windows Service.

Note:	"unix" is used as a generic description for either the Solaris or Linux
	operating systems.

JRE or JDK Java Version

The Java Runtime Environment (JRE) is not bundled with the Adapter installation files and the actual location of the JRE is a parameter that is specified in the startup scripts. Confusingly, there are two Java versions available from Oracle: a JRE version that contains the executables and library files to run a Java application and the Java Development Kit (JDK) version that contains additional tools not available in the JRE version. It is recommended that the JDK version of Java 1.6 or higher be installed rather than the JRE version.

Windows

Note:	The Windows script files are located in the scripts\windows
	folder of the Adapter installation.

windows_install.bat

New with the 5.4 version is the addition of the windows_install.bat script file that performs the following installation tasks as a single menu driven script. This script file is described in <u>Appendix E</u> below and it is the recommended way to install the *Gplus* Adapter as a Windows Service.

This script incorporates many of the steps discussed below and it is also recommended that the following steps be read for background. It should be noted that the Gplus Adapter can still be installed as described below using the listed script files.

startup.bat and svcinstall.bat

Both the startup.bat file and the svcinstall.bat Windows script files have common parameters that must be set to identify the JRE that will be used as well as the allocated memory limit for the running *Gplus* Adapter instance.

Setting WFM_JAVA_HOME

The WFM_JAVA_HOME parameter has to set to a base folder in the Java installation as shown in the example below.

set WFM_JAVA_HOME=../java/jdk1.6

JVM Memory

The memory setting configures the maximum amount of memory that the JVM will allocate on startup. The default is 1024 MB and it should be sufficient for all but the very largest call centers.

set JVM_MEM=1024m

The maximum memory available to the JVM in a Window 32 bit OS varies but it should not be set higher than 1.3 GB. In the unlikely event that more memory than those limits is required, a 64 bit version of the JVM can be used. The memory available on a 64 bit OS would be constrained by the amount of memory on the server. It should be noted that the memory requirements actually increase with a 64 bit OS as the memory pointer size doubles.

startup.bat Script

The Windows batch file startup.bat is immediately executable as soon as the .example suffix has been removed. A console window will be opened and the program will continue to run as long as that window is open. This is fine for debugging and testing the application but is not a viable mode for running a server application. Once the application has been set up and tested using the startup.bat file, it should be converted into a Windows service or invoked directly with the Genesys Solution Control Server.

The following is an excerpt from the Windows startup.bat script showing part of the command to start the adapter:

%WFM_JAVA_HOME%\bin\java.exe -Xms%JVM_MEM%m ...

The java.exe file is the executable that starts the JVM. The file path created by the concatenation of the WFM_JAVA_HOME parameter and the rest of the file path, \bin\java.exe, must point to the actual Java executable.

svcinstall.bat and jvm.dll

When the Adapter is installed as a Windows service, it does not use the java.exe file but rather links to the jvm.dll file. There is a server version of that file available and this is the recommended version to use with the Gplus Adapter. The excerpt shown below is taken from the svcinstall.bat file and the file path assumes that the server version is being used:

...%WFM_JAVA_HOME%\jre\bin\server\jvm.dll ...

Again, the combination of the WFM_JAVA_HOME parameter and the file path must identify an actual file in the Java installation.

Installing a Windows Service

The following description discusses installing the adapter as a Windows service using the Apache CommonsTM *daemon* TM *procrun* Java service wrapper.

The included svcinstall.bat file must reference the installed JRE in exactly the same way that the startup.bat file was configured with the WFM_JAVA_HOME parameter. An additional parameter, SVCNAME, must be set to identify the new service in the Services Console as shown below:

set SVCNAME=GPlusAdapter_WFM_P

The service name must match the Configuration Server application name of the Adapter instance that is configured in the GPlusWFM.properties file described <u>below</u>.

One point to note is the location of the jvm.dll file as described above. The other is that it is also possible to modify the logging of the service process. The installation script has the following service logs enabled:

- AdapterService.YEAR-MONTH-DAY.Log
- service-stdout.YEAR-MONTH-DAY.Log
- service-stderr.YEAR-MONTH-DAY.Log

The logging can be disabled by removing the parameters or using the <u>prunmgr</u> application.

This script file must be run once to install the adapter instance as a service after the parameters have been set. As part of the service installation, the prunsrv.exe file is copied and given the name of the new service e.g. GPLusAdapter_WFM_P.exe.

32 bit or 64 bit Service Installation

If a 64 bit JRE is being used to run the Adapter, then it must be installed as a 64 bit service. The only reason to use a 64 bit instance is to increase the memory beyond the limits of the 32 bit JVM.

The default installation uses the following line to rename the prunsrv.exe executable but there are three versions of that file available depending on the Windows version and JRE type:

COPY prunsrv.exe %RENAMED_EXE%

Copies of the versions have been placed in the three folders contained in the wrappers folder. The *ia64* version is specific to a 64 bit machine using an ItaniumTM processor with the *amd64* version used for all other 64 bit processors. The appropriate file should be placed in the main folder prior to executing the svcinstall.bat script.

- wrappers/32_bit default 32 bit JRE version
- wrappers/amd64 default 64 bit JRE version
- wrappers/ia64 64 bit JRE on Itanium™ version

Modifying an Existing Service Installation

After a successful installation, the adapter will automatically start as a service when the server boots up and the service can be stopped or started through the Windows Services Console. For most installations, there is no need to change the JVM parameters from the defaults set in the svcinstall.bat script but it is possible to change the start up parameters for the JVM if required using the included prunmgr.exe application. This is discussed in detail in <u>Appendix C</u>.

Removing an Existing Service Installation

Uninstalling the service can be carried out with the following command (using the example service given above):

prunsrv.exe //DS//GPlusAdapter_WFM_P

bash Shell Scripts

Note: The *bash* script files are located in the scripts\unix_bash folder of the Adapter installation.

The startup.sh.example and shutdown.sh files are standard *bash* shell scripts. The startup script has to be renamed to remove the .example suffix and then both files have to be made executable with the chmod command. An example is given below:

chmod 751 ./startup.sh

The startup.sh script file starts up the Adapter as a background process that will continue to run until the shutdown.sh script is executed. The process ID for the running adapter is contained in the WFM_PID file and this file should not be tampered with or that particular process will have to be stopped manually.

Setting WFM_JAVA_HOME

The WFM_JAVA_HOME parameter has to set to a base folder in the Java installation as shown in the example below.

WFM_JAVA_HOME=../java/jdk1.6

JVM Memory

The memory setting configures the maximum amount of memory that the JVM will allocate on startup. The default is 1024 MB and it should be sufficient for all but the very largest call centers.

JVM_MEM=1024m

The maximum memory available for a Linux 32 bit installation is 2.0 GB. In the unlikely event that more memory than those limits is required, a 64 bit version of the JVM can be used. The memory available on a 64 bit OS would be constrained by the amount of memory on the server. It should be noted that the memory requirements actually increase with a 64 bit OS as the memory pointer size doubles.

Configuration Server Connection

Former versions of the *Gplus* Adapter had configured the connection to the Configuration Server in the startup scripts but the connection parameters should now defined in the GPlusWFM.properties file contained in the config directory of the adapter installation. The adapter will still accept the parameters defined in the script files but using the new properties file is recommended.

Identifying the Adapter's Application Object

This property references the previously created Application object in the Configuration Server so that the proper configuration information can be acquired and used by the associated adapter instance.

appName=<applicationName>

Setting the Application Type

Applications registering with the Configuration Server have to identify their application type as part of establishing the connection. The *Gplus* Adapter has been configured as a ThirdPartyServer in the application template discussed above. The cmeAppType parameter has been set properly and can be ignored in most cases.

```
cmeAppType=ThirdPartyServer
```

Applications configured as a ThirdPartyServer application type can register with the Genesys Configuration Server once without specifying a username or password. Multiple registrations with the same Application Name (appName) are not allowed.

The properties file still has the username and password parameters listed although they are not usually required and they are only used if the application type is set to ThirdPartyApplication.

```
cmeUser=
cmePass=
```

Configuring the Adapter instance as a ThirdPartyApplication would allow for multiple connections to the Configuration Server using the same credentials

Encrypting the Configuration Server Password

If the application type is set to ThirdPartyApplication, it is possible to encrypt the password for the CME user. The encryptPassword script files will encrypt the provided password and store it in the enc file contained in the config folder. The Adapter will check for this file at startup and use the encrypted password as the user's credentials when connecting to the Configuration Server.

The scripts start a small Java application and the JRE to be used to run the application must be identified with the WFM_JAVA_HOME parameter. The script file must be run from the console as it does not prompt for the password but rather expects the password as the only parameter.

Example:

encryptPassword.bat cmePassword

Setting Configuration Server Connection Parameters

The next set of properties specifies the connection parameters for the Genesys Configuration Server.

Socket Parameters

The parameters below are mostly self explanatory. The Adapter instance will be attempting to connect to the Configuration Server through a socket defined by a host name and port number.

```
cmeHost=<hostName>
cmePort=2020
cmeBackupHost=
cmeBackupPort=
```

Note: The host name is the actual server host name or IP address.

The backup Configuration Server host and port can also be added if there is a backup. If there is no backup server, the backup parameters should be set to the primary Configuration Server. The connection parameters defined in the following sections will be shared by both the primary and backup Configuration Server connections.

Setting Registration Timeout and Delay

The next three connection properties configure how the G*plus* Adapter registers for notifications after connecting (or reconnecting) to the Configuration Server. These parameters were added to reduce the load on the Configuration Server in a busy call center when a number of applications may be attempting to reconnect and register requests at the same time.

configTimeout=10m registrationMinDelay=5m registrationMaxDelay=15m

The first parameter (configTimeout) sets the amount of time the Adapter will wait before attempting to reregister a request for which it has not received a response. The default is 10 minutes and that should be more than sufficient for most call centers but it can be increased if required.

The other two parameters set the bounds for when the Adapter instance will randomly attempt to register for notifications after reconnecting to the Configuration Server. The delay will be random time longer than registrationMinDelay but less than registrationMaxDelay. Again, these parameters would only be relevant if a large number of Adapters were connected to the same Configuration Server.

Setting addp Protocol

The next set of parameters configures the addp connection protocol. This protocol acts as a *heartbeat* for the connection and each side of the connection can be notified if the connection is inadvertently dropped.

```
addpEnabled=false
addpLocalTimeout=45
addpRemoteTimeout=75
addpTraceMode=full
```

Both timeouts are in seconds and should be set to different values with the remote timeout greater than the local timeout.

It is recommended that if addp is enabled, the addpTraceMode should be set to full which is the equivalent of Trace On Both Sides. This setting will ensure that the Adapter is notified if the connection to the Configuration Server is disconnected.

Enabling Transport Layer Security (TLS)

This connection parameter enables the Adapter to use Transport Layer Security (TLS) when connecting to the Configuration Server. The actual configuration for TLS occurs on the server side.

Setting up the Configuration Server for TLS and providing a security certificate for the adapter are well beyond the scope of this document. The *Genesys 8.0 Security - Deployment Guide* does discuss the steps required to set up TLS.

```
tls=false
```

Note: The secure port on the Configuration Server may not be the default and the cmePort parameter has to be set to that secure port if TLS is enabled.

Solution Control Server Integration

Note: SCS integration also requires a Local Control Agent (LCA) instance installed on the server hosting the G*plus* Adapter and a properly configured Host object in the Configuration Server.

The *Gplus* Adapter can be started and stopped using the Solution Control Interface for both the Windows and "unix" versions by invoking the Java executable with the command line arguments. Additionally, an adapter instance installed as a Windows Service can also be controlled by adding two Options to the Adapter instance's Annex Data.

Invoking the Application Directly

The following fields in the Start Info tab of the Adapter's Configuration Properties must be set as described for the Solution Control Server to start and stop the application.

Working Directory

The working directory is set to the root of the adapter installation files:

/Applications/GPlus_WFM_Adapter

Command Line

The command line starts up the JVM with the j ava command as in this example:

```
/java/jdk1.6_33/jre/bin/java
```

It is also possible to just invoke the startup.bat file in the case of a Windows installation if that file was configured properly:

```
startup.bat
```

Command Line Arguments

If the command line does not use the startup script, then the command line arguments are given below:

-Xms1024m -Xmx1024m -jar bootstrap.jar com.ariasolutions.iconnect.BootStrap

The only variable set in the command line arguments is the JVM memory size and both the minimum (-Xms) and the maximum (-Xmx) should be set to the same amount. The other parameters should not be changed from the example above which shows the allocated memory set to 1024 MB.

Start and Stopping a Windows Service

The following instructions are relevant if the Adapter instance has been installed as a Windows Service and the Service is to be started and stopped through the Solution Control Server.

Note: The LCA version should be 8.1.200.07 or higher and the Solution Control Server should be an 8.1.x version to be compatible with the LCA.

Working Directory

The working directory is still set to the root of the adapter installation files. The directory that contains the renamed prunsrv.exe as described <u>above</u>:

/Applications/GPlus_WFM_Adapter

Command Line

The command line just identifies the renamed prunsrv.exe that was created when the Service was installed:

GPlusAdapter_WFM_P.exe

Command Line Arguments

The command line arguments field can be left blank.

Adding Options to the Adapter's Annex Tab

A new Section, start_stop, has to be added to the Adapter's Annex Tab. Two options, start_command and stop_command, are added with their Values containing the commands that explicitly start and stop the Windows Service installed for the Adapter instance. The example below shows the configuration for a Service instance named GPLusAdapter.

GPlusAdapter [gen81:2020] Properties					
General	Server	Info	Start Info	Connections	Options
Annex			Security	Depen	dency
start_stop		Value	D 🗙 🔜 🕸	• 😰	
Enter text here		Enter text here		7	
<u>abc</u> start_command <u>abc</u> stop_command		"net start GPlus "net stop GPlus			

Logging Configuration

The G*plus* Adapter has three types of logs and the first two are configurable beyond being enabled or disabled.

- 1. TServer and Interaction Server events with the adapter state changes associated with those events.
- 2. A summary of errors also logged in the first log.
- 3. The recovery log.

Event and Error Logs

log4j.xml File Location

The first two log types are configured using the parameters found in the log4j.xml.example file contained in the configuration directory (./config). This file will not be the active logging configuration until the name is changed to log4j.xml.

ROLLING Appender - No Compression

The following is an excerpt from the log4j.xml file showing some of the parameters that can be set for the ROLLING appender. This appender logs the events to a set of files that are continuously updated.

</appender>

The log file destination folder and name are specified by the File parameter. In the example above, the file (GPlusAdapterWFM.log) will be created and updated in the logs directory that was created when the application was installed. The destination folder could have been set to any folder accessible from the installation.

The ROLLING log files are set to roll over when the file size of the current file (GPLusAdapterWFM.log) reaches the MaxFileSize (50MB). The older files are indicated by an integer appended to the file name. The MaxBackupIndex is set to 2 in the example so only two backup files would be kept: the most recent, GPLusAdapterWFM.log.1 and the previous file, GPLusAdapterWFM.log.2. By

adjusting these two parameters and depending upon the call volume, the uncompressed files could keep an hour or two of the recent activity for review.

GZIP Appender - Compressed

The events log records all of the events received by the *Gplus* Adapter as well as operational states. The logs can become quite large and for that reason the GZIP appender was added. The GZIP appender continuously archives the logging information to compressed files. This file space saving feature enables the uncompressed files built by the ROLLING appender to serve as a recent snapshot of adapter activity and the GZIP files provide the longer term archive.

The log file destination is specified by the Prefix parameter for the GZIP appender. In the above examples, the logging directory has been set to the logs directory that was created when the application was installed but it could have been set to any folder accessible from the installation.

The GZIP appender is configured to start a new file hourly with the RollOverField parameter set to hour. The MaxBytes parameter specifies the maximum number of storage bytes used for all of the zipped log files. When the MaxBytes limit is exceeded, the adapter will start deleting the oldest zipped files until the limit is not exceeded. Each file name will have the date and time that the file was created appended to the Prefix specified in the configuration file.

ROLLING_ERROR Appender

The ROLLING_ERROR appender is essentially the ROLLING appender with the logging threshold level set to error. The errors will still be logged to the ROLLING and GZIP logs but the error log file allows for a quick check to see if the adapter is running error free rather than having to search through the event logs.

Logging Levels

Logging levels for the log4j library are limited to six levels with fatal being the least verbose and trace being the most. The default level set in the log4j.xml.example file is debug. In production or when detailed log entries are no longer required, the logging threshold could be increased but this can be set easily in the Configuration Layer with the application/logThreshold option discussed <u>below</u>. Adding or removing appenders

The example file includes a definition for a STDOUT appender that has been left commented out. This appender allows logging to the console and it is not practical for a production instance. The following excerpt from the example file shows that the STDOUT appender is not included in the logging but the ROLLING, ROLLING_ERROR and GZIP appenders are included:

The xml comment tags ($\langle !-- - \rangle$) can be used to exclude any of the logging appenders.

Windows Service Logs

The parameters for installing the adapter as a Windows Service include specifying that stdout and stderr for the adapter are redirected to two log files: service-stdout*.log and service-stderr*.log. Usually both log files will be empty but in the event of a fault with the JVM, that fault should be logged in the err.log file.

If the STDOUT appender is enabled, the adapter logs will be directed to the service-stdout*.log file. This is not recommended as the file is not "managed" and it will continue to grow until the available disk space is consumed.

Recovery Log

The recovery log will be contained separately in the recovery folder. This log has no configuration options and is managed automatically by the *Gplus* Adapter. The log files contain enough information to restart the adapter after a mishap without losing the data recorded prior to the mishap. It should not be tampered with.

If data contained in the recovery log prevents the adapter from starting up, the log files can be removed from the recovery folder to allow the application to start.

Initial Start Up Test

The application has not been configured in the Configuration Manager but it should now start up and create a log file before failing. This test requires the startup script to be run and then a confirmation that a brief log file has been created listing the exceptions generated from starting without configuration. The log file(s) should be created in the directory specified in the log4j configuration.

In the case of the *bash* shell scripts, shutdown.sh has to be run to ensure that the stalled run state has cleared. Both shell script files should have been modified to be executable during the initial setup of the application.

License File

A temporary license file (license.txt) is included in the config folder of the Gplus Adapter installation. This license will allow the adapter to run on any server for a limited amount of days. The expiry date is listed in the license file. When a production license has been purchased, the temporary license file must be replaced with the new file.

While the temporary license allows the Adapter instance to run on any host server, the purchased permanent licenses are created with permanent fields that cannot be altered. Changing any of these fields requires creating a new license e.g. moving the Adapter to a new server would require a new license. The following fields are required and restrict the Adapter to being installed on one host server and acquiring its configuration from an existing Application object in the Configuration Server:

- Host name
- Adapter application name in Configuration Server
- Vendor (IEX)
- Number of seats

Determining the Host Name

Depending upon the host operating system and network configuration, the required host name may be either a simple hostname or a qualified hostname:

- Simple adapterhost • •
 - Qualified qualified.domain.adapterhost

The JRE libraries are used to check the licensed hostname in the Adapter and those libraries are also used with the provided serverHostName script file. Executing the script file will display the required hostname in the console window. There are Windows and bash versions of these script files. The scripts start a small Java application and the JRE to be used to run the application must be identified with the WFM_JAVA_HOME parameter.

The .example extension has to be removed from the script name and the bash version has to be made executable.



Chapter

3 Application Options

Each of the G*plus* Adapter application options is discussed in this chapter. To change the application options, open the Adapter Application in the Configuration Manager and select the Options tab.

alarmCodes Section

This Option Section deals with the alarm codes sent to the Genesys Message Server. The alarm codes sent must match up with the Log Event IDs defined in the Alarm Conditions contained in the Configuration Server.

diskWriteFailure

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	diskWriteSuccess

This option identifies the integer Alarm Code sent to the Message Server when the Gplus Adapter encounters a problem writing the event logs, the recovery logs or the historical reports to the disk drive.

diskWriteSuccess

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	diskWriteFailure

This option identifies the integer Alarm Code sent to the Message Server when the problem that generated a diskWriteFailure Alarm Code has been cleared.

ftpFailure

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	ftpSuccess

This option identifies the integer Alarm Code sent to the Message Server when the G*plus* Adapter encounters a problem sending the generated report files to the remote WFM server.

ftpSuccess

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	ftpFailure

This option identifies the integer Alarm Code sent to the Message Server when the problem that generated a ftpFailure Alarm Code has been cleared.

reportFailure

Туре:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	reportSuccess

This option identifies the integer Alarm Code sent to the Message Server when the Gplus Adapter encounters a problem generating the report files.

reportSuccess

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	reportFailure

This option identifies the integer Alarm Code sent to the Message Server when the problem that generated a reportFailure Alarm Code has been cleared.

rtaConnected

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	rtaDisconnected

This option identifies the integer Alarm Code sent to the Message Server when the connection problem that generated a rtaDisconnected Alarm Code has been cleared.

rtaDisconnected

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	rtaConnected

This option identifies the integer Alarm Code sent to the Message Server when the *Gplus* Adapter's RTA connection to the IEX server was terminated by either side.

rtaConnected:<streamName>

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	rtaDisconnected: <streamname></streamname>

This option identifies the integer Alarm Code sent to the Message Server when the connection problem that generated a rtaDisconnected:<streamName> Alarm Code has been cleared.

rtaDisconnected:<streamName>

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	rtaConnected: <streamname></streamname>

This option identifies the integer Alarm Code sent to the Message Server when the Gplus Adapter's RTA connection associated with the Stream identified by $\langle streamName \rangle$ was terminated by either side.

serverConnected

Type:	Optional
Default Value:	Not set
Valid Values: Dependencies:	Alarm Condition/Detect Event/Log Event IDs serverDisconnected

This option identifies the integer Alarm Code sent to the Message Server when the connection problem that generated a serverDisconnected Alarm Code has been cleared.

serverDisconnected

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	serverConnected

This option identifies the integer Alarm Code sent to the Message Server when one the Genesys Server (TServer, SIPServer or Interaction Server) connections has been disconnected.

serverConnected:<serverName>

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	serverDisconnected: <servername></servername>

This option identifies the integer Alarm Code sent to the Message Server when the connection problem that generated a serverDisconnected Alarm Code has been cleared.

serverDisconnected:<serverName>

Type:	Optional
Default Value:	Not set
Valid Values:	Alarm Condition/Detect Event/Log Event IDs
Dependencies:	serverConnected: <servername></servername>

This option identifies the integer Alarm Code sent to the Message Server when the Genesys Server (TServer, SIPServer or Interaction Server) connection identified by <serverName> has been disconnected.

application Section

This Option Section deals with the general options for the Adapter instance.

agentIdMode

Type:	Mandatory
Default Value:	personUserName
Valid Values:	agentLogin - Switch Login ID field personEmployeeId - Employee ID field personUserName - User Name field
Dependencies:	None

This option identifies which of the Genesys Person fields will be reported as the agent identifier in G*plus* Adapter reports. In multi-site implementations, it is recommended this option be set to personUserName or personEmployeeId to avoid duplicated agentLogin IDs across PBXs. In email and chat implementations, only personUserName or personEmployeeId option values can be used as no PBX switch is involved.

annexSection

Type:	Optional
Default Value:	Not set
Valid Values:	Any text string acceptable as an Annex Section name.
Dependencies:	None

This option identifies the name of the Annex Section that will contain the G*plus* specific options added to a Place Group, VQ or Skill object in the Configuration Server. It is most commonly used when multiple primary G*plus* Adapter applications are configured for site-based reporting. More than one Annex Section containing a site name can be configured for a particular Place Group.

Note: Contact Professional Services prior to configuring this option.

callType

Type: Default Value:	Mandatory queueNumber	
Valid Values:	skill	list of Skill Names.
	queueNumber	list of Virtual Queue Numbers.
	queueAlias	list of Virtual Queue Aliases.
	custom	list contained in callTypes.custom
Dependencies:	genesys.queueGi	roups, callTypes.custom

This option specifies the Configuration Object type (or in the case of Virtual Queues, the field within the type) that will be used as the contact ID for each voice call. The *Gplus* Adapter uses the appropriate Configuration Objects to create a list of contact IDs. There are two consequences of this setting:

- 1. The created list of contact IDs must correspond to the contact/queues expected by the IEX server in the Contact Queue report.
- 2. It must be possible to parse the contact ID from the attributes of an EventQueued received from one of the monitored DNs.

The use of the <u>event.properties/callType.determiner</u> allows the event parsing to be customized. This should minimize the need for any changes to the Genesys environment. In addition, if one of the queue values has been selected, all Virtual Queues to be included in the list of reported contact types must be included in the genesys.queueGroup Section of the G*plus* Adapter application.

When the contact types used by the WFM application do not map to either Skills or Virtual Queues, a custom option value must be used and a callTypes.custom Section containing a list of the reported contact types must be added to the application options.

countUnattachedACW

Type:	Optional
Default Value:	false
Valid Values:	true, false
Dependencies:	None

This option is applicable to environments where the soft-phone/hardset allows an agent to choose the ACW (AfterCallWork) state at any time. When set to true, an agent choosing the ACW state in a login session with no previous routed calls to associate with that state (e.g. Login, ACW and Logout) will have the time counted as ACW Time against a default callType in the G*plus* Adapter reports. If set to false, any ACW time in a login session with no previous handled routed calls will be reported as NotReady/Aux time.

defaultAnnexSection

Type:	Deprecated
Default Value:	Not set
Valid Values:	Any valid Annex section name
Dependencies:	None

This option specifies an Annex section name to be used by the adapter in the event that the default Annex section name, GPLUS_WFM, cannot be used. This option is applicable to all of the configuration objects used by the adapter.

inheritOptionsFromApp

Type:	Optional
Default Value:	Not set
Valid Values:	Any GPlus adapter application name.
Dependencies:	None

This option would typically be set when configuring a backup *Gplus* Adapter application. The backup application will inherit relevant options from the adapter instance identified by the specified application name. Any options set for the backup adapter instance will override those set for the primary instance.

logThreshold

Type:	Mandato	ry
Default Value:	debug	
Valid Values:	fatal	Least verbose level
	еггог	
	warn	
	info	
	debug	
	trace	Most verbose level
Dependencies:	None	

The logging level of the application at startup is set to the level defined in the config/log4j.xml file. This option defines the logging level that the application will use after the configuration information is read from the Configuration Server.

<u>Appendix D</u> discusses different log file examples based on the configured logThreshold.

siteBased

Type:	Optional
Default Value:	false
Valid Values:	true, false
Dependencies:	Site name added to Place Group Annex tab.

This option allows the information presented in the historical reports to be grouped by Sites in a multi-site environment. Sites used by the *Gplus* Adapter are defined by adding Site names to the Annex section options of the Place Group configurations. The Site name will then prefix the Queue name in the CQ column in the Contact Queue and Agent Contact Queue reports.

This Option only applies to the stream defined in the historical.reports Section. In the case of multiple streams, each additional historical stream has its own siteBased Option.

Note: Contact Professional Services prior to enabling this option.

tenantDbid

Type:	Optional
Default Value:	101 (Resources)
Valid Values:	A dbid of a configured Tenant
Dependencies:	Configuration Server tenant type

This option must be set if the G*plus* Adapter is connected to a Genesys Multi-Tenant Configuration Server and the Adapter will be monitoring a different Tenant than the default Resources Tenant that usually corresponds to a dbid of 101.

timeZone

Type:	Optional
Default Value:	Time zone of the application's host server.
Valid Values:	Listed in Appendix A.
Dependencies:	None.

This option is used to report data for a time zone other than the time zone where the Gplus Adapter instance is installed. It is not required if the server time zone is correct for the locale.

Note: See Appendix A - Time Zone ID List.

useLocalTime

Type:	Optional
Default Value:	auto
Valid Values:	auto, true,false
Dependencies:	None

The useLocalTime option allows the *Gplus* Adapter to set the event time for received events using the local server time. This provides coordination between two or more servers where the event times create synchronization problems. One example would be with the Interaction Server that retains event time in seconds while voice TServers maintain event time to a resolution of milliseconds. Synchronization between the two server types is necessary for monitoring events in Outbound Push Preview campaigns.

If the option is left as auto, the adapter will automatically use local time if it is connected to both an Interaction Server and a voice TServer. This can be disabled by setting the option to false.

Note: Contact Professional Services prior to configuring this option.

attachedDataFilter Section

This Option Section is used to remove sensitive or private information from the received events prior to those events being processed or logged. Key/value pairs can be removed from the following Key/Value List attributes:

- UserData
- Reasons
- Extensions

The only allowed Option value is exclude and the Option name is the event attribute to excluded. Nested attributes will be removed if their *root* is identified in Option name.

It should be noted that the attribute will not be available to the Adapter if removed. For example, if a UserData.VQ_Name attribute was being used to identify a target for a customer's queued call and all of the UserData had been removed, the target determiner would fail.

GPlusAdapter [gen81:2020] Pr	operties 🛛 🔍
General Server Info Start Info	Connections Options Security Dependency
sttachedDataFilter	💿 👌 🗋 🗙 🔜 🎐 🎼 🎐
Name 📥	Value
Enter text here	P Enter text here
bc Extensions.Customer_ID	"exclude"
Beasons.BadReasonCode	"exclude"
abs UserData.Customer SSN	"exclude"

callTypes.custom Section

This optional Section is only used if the application/callType Option has been set to custom. The section contains a list of WFM voice contact type/queue names that will be reported by the *Gplus* Adapter. This list is required when there is no one-to-one mapping of expected WFM contact types/queues to specific Configuration Objects (Skills or Virtual Queues).

The Option Name (or shortName) must match the exact value generated by the Gplus Adapter when applying the event filter specified by the callType.determiner Option against the TServer queued events. The Option Value can be left blank or a configuration text string specified. Since this is essentially a custom list of contact types rather than Genesys Configuration Objects, the serviceLevelThreshold (see <u>Threshold</u> <u>Format</u>) and/or a shortname can be set in a manner similar to that of the <u>Virtual Queues</u>.

If no serviceLevelThreshold is specified, the G*plus* Adapter will use the defaultServiceThreshold Option from the voice Section of the adapter Options. If no shortname is specified, the G*plus* Adapter will report the Option Name.

Туре:	Optional
Default Value:	Section is not used
Valid Values:	serviceLevelThreshold and shortName
Dependencies:	application/callType,
	event.properties/callType.determiner

🙀 GPlusAdapter [gen81:2020] Proper	rtie	s	
General Server Info Start Info Conr	nect	tions Options Security Dependency	
🔪 call Types.custom 🗸 🔊 👔			
Name 📤		Value	
Enter text here	7	Enter text here	
abc Collections	_	"shortName='PaymentArrangements"	
LustomerService		"serviceLevelThreshold='20s', shortName='CS'''	
abc Sales		"serviceLevelThreshold='60s"	

chat Section

chatACWReason

Type:	Optional
Default Value:	ACW
Valid Values:	Any unique text value.
Dependencies:	Agent's chat client must be able to set the Reason field
-	when going NotReady.

This option allows users to specify a NotReady ReasonCode that will be reported as the equivalent of ACW for the chat statistics and will be reported as the AfterChatWork RTA state..

The text string must be contained in the Reason.ReasonDescription attribute of a chat NotReadyForMedia event.

defaultAbandonedThreshold

Type:	Optional
Default Value:	0s
Valid Values:	See Threshold Format
Dependencies:	None

This option specifies the default abandoned threshold for the Abandoned In Threshold column in the Contact Queue report. This option is set when a single abandoned threshold is used for all chat targets. Individual abandoned thresholds can be set for each chat target/queue by <u>adding Annex Data</u> to the chat Virtual Queues included in the genesys.queueGroups Section.

defaultServiceThreshold

Type:	Optional
Default Value:	0s
Valid Values:	See Threshold Format
Dependencies:	None

This option specifies the default service threshold for the service level calculations that form part of the interval reports. A chat is considered *serviced* at the time that the agent first joins the chat session with a customer.

This option should be set when a single service threshold is used as a default for all chat targets. Individual service thresholds can be set for each chat target/queue by adding Annex Data to the chat Virtual Queues as shown in a later <u>section</u> or adding the threshold to an Interaction Queue as described in the <u>interactionTargets</u> Section. These individual thresholds will override the default specified by this option.

defaultTarget

Type:	Optional
Default Value:	UnknownTarget
Valid Values:	Any text
Dependencies:	application/countUnattachedACW

This option allows users to define a separate chat target/queue other than the default value used by the G*plus* Adapter to report on an agent's time outside of actual chat activity (including unattached ACW) when that time cannot be associated with an actual chat target/queue.

It should be noted that the default for this Option is the same as that for voice and email (UnknownTarget). If the adapter is monitoring multiple media and the defaults are retained, the calls or interactions that cannot be allocated to a proper target will be combined under UnknownTarget in the Contact Queue report.

enabled

Type:	Mandatory
Default Value:	false
Valid Values:	true, false
Dependencies:	A connection to a Genesys Interaction Server.

Set to true to capture and report on chat activity (historical and RTA) in the contact center.

interaction.reason.determiner

Туре:	Optional
Default Value:	Not set
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	chat/enabled, rta/enabled

This option specifies the attribute of a chat Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:

- EventPartyAdded
- EventPropertiesChanged while the agent is a party to a routed chat.

Certain implementations may require that the combination of an InRoutedChat RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>interactionCodeMappings</u> Section.

Note: Contact Professional Services before using this option.

reason.notReady.determiner

Туре:	Optional
Default Value:	eventAttribute: ReasonDescription
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	chat/enabled, rta/enabled

This option specifies the attribute of a chat Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:

- EventNotReadyForMedia
- EventMediaStateReasonChanged while the agent is NotReady to receive a routed chat.

Certain implementations may require that the combination of an Unavailable RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>reasonCodeMappings</u> Section Note: Contact Professional Services before using this option.

reason.ready.determiner

Type:	Optional
Default Value:	Not set
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	chat/enabled, rta/enabled

This option specifies the attribute of a chat Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:

• EventReadyForMedia

Certain implementations may require that the combination of an Available RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>readyCodeMappings</u> Section.

Note: Contact Professional Services before using this option.

email Section

defaultServiceThreshold

Type:	Optional
Default Value:	Øs
Valid Values:	See Threshold Format
Dependencies:	None

This option specifies the default service threshold for the service level calculations that form part of the interval reports. An email is considered *serviced* at the time that the agent sends the reply to a customer.

This option should be set when a single service threshold is used as a default for all email targets. Individual service thresholds can be set for each email target/queue by adding Annex Data to the email Virtual Queues as shown in a later <u>section</u> or adding the threshold to an Interaction Queue as described in the <u>interactionTargets</u> Section. These individual thresholds will override the default specified by this option.

defaultTarget

Type:	Optional
Default Value:	UnknownTarget
Valid Values:	Any text
Dependencies:	application/countUnattachedACW

This option allows users to define a separate email target/queue other than the default value used by the G*plus* Adapter to report on an agent's time outside of actual email activity (including unattached ACW) when that time cannot be associated with an actual email target/queue.

It should be noted that the default for this Option is the same as that for voice and chat (UnknownTarget). If the adapter is monitoring multiple media and the defaults are retained, the calls or interactions that cannot be allocated to a proper target will be combined under UnknownTarget in the Contact Queue report.

emailACWReason

Туре:	Optional
Default Value:	ACW
Valid Values:	Any unique text value.
Dependencies:	Agent's email client must be able to set the Reason field
	when going NotReady.

This option allows users to specify a NotReady ReasonCode that will be reported as the equivalent of AfterCallWork for the email statistics in the reports and will be reported as the AfterEmailWork RTA state..

The text string must be contained in the Reason.ReasonDescription attribute of an email NotReadyForMedia event.

enabled

Type:	Mandatory
Default Value:	false
Valid Values:	true, false
Dependencies:	A connection to a Genesys Interaction Server.

Set to true to capture and report on email activity (historical and RTA) in the contact center.

interaction.reason.determiner

Type:	Optional
Default Value:	Not set

Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	email/enabled, rta/enabled

This option specifies the attribute of an email I Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:

- EventPartyAdded
- EventPropertiesChanged while the agent is a party to a routed email.

Certain implementations may require that the combination of a ReadingCustomerEmail or ReplyingToCustomerEmail RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>interactionCodeMappings</u> Section.

Note: Contact Professional Services before using this option.

reason.notReady.determiner

Type:	Optional
Default Value:	eventAttribute: ReasonDescription
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	email/enabled, rta/enabled

This option specifies the attribute of a email I Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:

- EventNotReadyForMedia
- EventMediaStateReasonChanged while the agent is NotReady to receive a routed email.

Certain implementations may require that the combination of an Unavailable RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>reasonCodeMappings</u> Section

Note: Contact Professional Services before using this option.

reason.ready.determiner

Type:	Optional
Default Value:	Not set
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	email/enabled, rta/enabled

This option specifies the attribute of an email I Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:

• EventReadyForMedia

Certain implementations may require that the combination of an Available RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>readyCodeMappings</u> Section.

Note: Contact Professional Services before using this option.

event.properties Section

callType.determiner

Type:	Optional	
Default Value:	eventAttribute: ThisQueue	
Valid Values:	<pre>eventAttribute: {EventQueued attribute name}</pre>	
	class: {custom Java class name}	
Dependencies:	voice/enabled, application/callType	

This option specifies what part (attribute) of an EventQueued will be used to determine the contact queue/call target for a routed inbound call.

Examples:

eventAttribute: ThisQueue eventAttribute: UserData.VQ_Name

campaignTarget.determiner

Type:	Optional	
Default Value:	eventAttribute:	UserData.GSW_CAMPAIGN_NAME

Valid Values:	eventAttribute:	{EventQueued attribute name}
Dependencies:	outbound/enabled	

This option specifies what part (attribute) of an event on an agent's outbound campaign call will be used to determine the contact queue/call target for that call. There will rarely be a reason to use anything other than the default.

See Outbound Campaign Calls for more information.

Note: Contact Professional Services prior to configuring this option.

ignoreAbandonOnRinging

Type:	Optional
Default Value:	false
Valid Values:	true, false
Dependencies:	None

This option specifies whether the adapter will continue to track an inbound voice call that is Abandoned while ringing at an agent's Place. Normal behavior would see the call records terminated at that point but in certain *Route On No Answer* (RONA) situations, the Abandoned event is generated when the call is pulled back and requeued. This option allows for those calls to be reported correctly.

Note: Calls that are actually abandoned by the customer releasing the call while ringing will be counted incorrectly because the call is not terminated if this option is enabled. This option should only be enabled after considering the effect on the report data.

ignoreRONAEventAttribute

Type:	Optional
Default Value:	Not set
Valid Values: Dependencies:	UserData. {RONA identifier field name} None

This option specifies the attached data field that the *Gplus* Adapter will look for to avoid double counting calls in a Route on No Answer (RONA) scenario. This option is required when a RONA call is answered at the agent's desktop and immediately transferred back to the queue to reroute the call. Attaching

and removing this UserData field for specific events is critical for the accurate reporting of routing with RONA calls.

Note: Contact Professional Services prior to configuring this option.

interactionTarget.determiner

Type:	Optional
Default Value:	eventAttribute: ThisQueue
Valid Values:	<pre>eventAttribute: {EventPlacedInQueue attribute name}</pre>
	class: {custom Java class name}
Dependencies:	chat/enabled, email/enabled

This option specifies how an email and/or chat target is determined from the attributes associated with the Interaction event.

Examples:	eventAttribute:	ThisQueue
	eventAttribute:	interactionProperties.interactionQueue
	eventAttribute:	UserData.VQ_Name

reason.logout.determiner

Type:	Optional
Default Value:	eventAttribute: Extensions.ReasonCode
Valid Values:	<pre>eventAttribute: {EventAgentLogout attribute name}</pre>
Dependencies:	voice/enabled,rta/enabled

This option specifies one of the attributes of a voice EventAgentLogout that identifies the reason code associated with an agent logging out. This Reason Code will be reported as the Sign-Off reason in the Agent Sign-On/Sign Off report and included as the reason code that forms part of the RTA state transition associated with the logout event.

reason.notReady.determiner

Туре:	Optional	
Default Value:	eventAttribute: Reasons.ReasonCode	
Valid Values:	<pre>eventAttribute: {EventAgentNotReady attribute name}</pre>	
	class: {custom Java class name}	
Dependencies:	voice/enabled,rta/enabled,reasonCodeMappings	

This option specifies attribute(s) of an EventAgentNotReady that identify the reason associated with an agent entering an Unavailable RTA state. Certain implementations may require that the combination of EventAgentNotReady and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>reasonCodeMappings</u> Section

Note: Contact Professional Services before changing this option from its Default Value.

serviceDate.determiner

Туре:	Optional
Default Value:	Not set
Valid Values:	<pre>eventAttribute: {attribute name}</pre>
Dependencies:	None

This option specifies attribute of in a queued event that contains a "to be serviced by" timestamp for the queued interaction. If the attribute is not present, then the defaultServiceThreshold for the media or the configured serviceLevelThreshold for the queue will be used.

The attribute value is a date/time combination that indicates the time that interaction must be serviced by to meet the Service Level expectations. The attribute string must be in the following format and the time is assumed to GMT rather than the local time:

- Format "YYYY-MM-DDThh:mm:ssZ"
- Example "2013-12-31T09:30:00Z"


filter:<filterName> Section

There can be more than one instance of this Section type and each is differentiated and made unique by the <filterName> portion of the Section name. The purpose of this Section is to define a subset of the monitored objects that have already been defined in the <u>genesys.agentGroups</u>, <u>genesys.placeGroups</u> and <u>genesys.queueGroups</u> Sections. Filters combined with the Stream configurations (<u>historical</u> and/or <u>rta</u>) allow the *Gplus* Adapter to support multiple IEX TotalView servers if required.

The filter is equivalent to the group sections listed above with Agent Groups, Place Groups and VQ DN Groups included or excluded as required. The addition of the loginQueue option provides an alternative method for including or excluding groups of Agents. The site option allows a set of Place Groups to be defined in much the same way. Sites and Place Groups are discussed <u>below</u>. The syntax for the group options is as follows:

•	agentGroup.≺AgentGroupName>	:	include or exclude
•	loginQueue.≺ACDQueue DN≻	:	include or exclude
•	placeGroup. <placegroupname≻< th=""><th>:</th><th>include or exclude</th></placegroupname≻<>	:	include or exclude

- site.<SiteName> : include or exclude
- targetGroup.<DNGroupName> : include or exclude
- **Note:** The groups that are included or excluded must correspond to groups already included in the three genesys.*Groups Sections. This will require attention as to how the AgentGroups, PlaceGroups and DNGroups (VQs) are defined. The loginQueue option(s) is the exception as each option references a DN rather than an AgentGroup.



genesys.agentGroups Section

This Section is a list of the Agent Groups that will be included in or excluded from the group of agents being monitored by the G*plus* Adapter. Valid Option names are either an asterisk (*) or the name of an Agent Group defined in the Configuration Server. The Option value is the action to be taken with respect to the named Agent Group: include or exclude.

*	
Type:	Optional
Default Value:	include
Valid Values:	include
Dependencies:	None

OR

<agent group="" name=""></agent>	
Type:	Optional
Default Value:	None
Valid Values:	include, exclude
Dependencies:	Configuration Server Agent Groups.

The Option Name determines the agents that the Gplus Adapter will report upon. An agent that is a member of an excluded or not included Agent Group will have no activity statistics reported in the Agent Contact Queue, Agent System Performance or Agent Sign-on/Sign-off reports. Additionally, an excluded agent's call activity will not be included in the Contact Queue report; a queued call would still be counted as "Offered" but it would not be counted as "Handled".

An excluded agent's activity will not be reported in the RTA data stream.

The asterisk (*) as the Option Name can be considered to be an Agent Group containing all of the Persons configured as an Agent with an enabled state in the Configuration Server. Including all of the agents is the default configuration and there is little reason to change that unless there is a specific configuration requirement.

The only alternative is to have an Option Name that corresponds to one of the defined Agent Groups in the Configuration Server. Any of those Agent Groups can be excluded or included.

genesys.placeGroups Section

This Section is a list of the Place Groups that will be included in or excluded from the group of Places being monitored by the *Gplus* Adapter. Valid Option names are either an asterisk (*) or the name of a Place Group defined in the Configuration Server. The Option value is the action to be taken against the named Place Group: include or exclude.

*		
Type:	Optional	
Default Value:	include	
Valid Values:	include,	exclude
Dependencies:	None	

OR

<place group="" name=""></place>	
Type:	Optional
Default Value:	None
Valid Values:	include, exclude
Dependencies:	Configuration Server Place Groups.

The Option Name determines the Place Group that the G*plus* Adapter will monitor or not monitor. This will mean that all of the DNs associated with the Places in those groups will be registered with the connected Voice TServer(s) and all of the Places will be registered with the connected Interaction Server(s).

Specifying an asterisk (*) as the Option Name can be considered to be a Place Group containing all of the Places configured in the Configuration Server. The only alternative is to have an Option Name that corresponds to one of the defined Place Groups in the Configuration Server.

Place Groups have two roles in the configuration of the *Gplus* Adapter: identifying the Places that are to be monitored by the application and associating groups of Places with Site names. Sites and Place Groups are discussed in another <u>section</u>.

Note: When IVR Ports or other non-Agent Places are defined within the Configuration Server it is common to exclude these places with the use of a Place Group so that IVR (non-Agent) activity is not reported.

genesys.queueGroups Section

This Section is a list of the DN Groups that will be included in or excluded from the group of Virtual Queue DNs (VQs) being monitored by the G*plus* Adapter. Valid Option names are either an asterisk (*) or the name of a DN Group defined in the Configuration Server. The Option value is the action to be taken against the named DN Group: include or exclude.

* (Option Name)	
Type:	Optional
Default Value:	include
Valid Values:	include
Dependencies:	None

OR

 <VQ DN Group Name>

 Type:
 Optional

 Default Value:
 None

 Valid Values:
 include, exclude

 Dependencies:
 VQ DN Groups in the Configuration Server.

The Option Name determines the VQs that the G*plus* Adapter will monitor. Specifying an asterisk (*) as the Option Name can be considered to be a DN Group containing all of the VQ DNs configured in the Configuration Server. The only alternative is to have an Option Name that corresponds to one of the defined DN Groups in the Configuration Server.

This option is used to specify monitored VQs that are defined for an actual Switch object in the Configuration Server. VQs defined on a Multimedia_Switch can be included but multimedia Interaction Queues defined in a Business Process routing strategy cannot.

historical.ftp Section

This section lists the configuration options for transferring historical report files from the server hosting the *Gplus* Adapter to a folder on the server hosting the WFM Application that uses those files. These options allow the transfer protocol to be configured as plain FTP or to use SSH (Secure Shell) to transfer the files.

With the addition of multiple <u>Streams</u>, this Section should be set up to transfer the report files associated with the Stream defined in the <u>historical.reports</u> Section.

backupRetentionDays

Type:	Mandatory
Default Value:	30
Valid Values:	Any positive integer
Dependencies:	localBackupDirectory

This option determines the number of days that historical report files created by the *Gplus* Adapter will be retained in the directory specified in the localBackupDirectory Option. The report files are removed permanently from the back up folder as they expire.

connectionMode

Type:	Optional
Default Value:	active
Valid Values:	active, passive
Dependencies:	Ignored if secureTransfer is enabled.

This option specifies the ftp connection mode used by the ftp client to connect to the remote ftp server. Some network firewalls will not allow active ftp connections and the connection mode can be changed to passive to allow the report files to transfer through the firewall.

enabled

Type:	Mandatory
Default Value:	true
Valid Values:	true, false
Dependencies:	None

This option can disable the ftp client that forwards the report files to the WFM server. This option is often set to false for backup G*plus* Adapter applications that do not need to send report files on a continuous basis but only in the event of a mishap.

keyPath

Type:	Optional
Default Value:	Not set
Valid Values:	Path to SSH private key file
Dependencies:	secureTransfer

This option defines the full path (including the file name) for the private key file used to establish the SSH connection with the remote server when the secureTransfer Option is enabled. The key file should usually be placed in the Adapter's config folder.

keyPassphrase

Type:	Optional
Default Value:	Not set
Valid Values:	Valid text string.
Dependencies:	secureTransfer

This pass phrase provides additional security for the SSH connection as establishing the connection requires the providing the pass phrase as well as possessing the private key file. The pass phrase must be specified when the SSH keys are created.

localBackupDirectory

Type:	Mandatory
Default Value:	ftp/reportsBackup
Valid Values:	Any existing folder on the Gplus Adapter server.
Dependencies:	None

This option identifies the directory on the *Gplus* Adapter server where copies of the historical report files will be saved after those files have been successfully transferred. If the option value is left blank, the report files will be deleted locally after being transferred to the remote WFM server.

localSourceDirectory

Type:	Mandatory
Default Value:	ftp/reports
Valid Values:	Any existing folder path.
Dependencies:	historical.reports/directory

This option identifies the directory where files will be temporarily stored at each reporting interval prior to being transferred to the WFM Server and subsequently moved to the backup directory or deleted if the backup directory is not configured.

The default location is the default report location specified in the historical.reports Option section and setting the two options to the same folder is how the association between the ftp client and the historical Stream is established.

remoteDestinationDirectory

Type:	Mandatory
Default Value:	./
Valid Values:	Any folder path on the remote server relative to the ftp user's default directory
Dependencies:	None

This option identifies the relative directory on the remote WFM Server where the G*plus* Adapter report files will be transferred. This directory is relative to the configured default directory for the ftp user identified in the userName Option.

Note: The ftp user must have sufficient access privileges to write the transferred files to the folder identified by the relative path.

remoteHost

Туре:	Mandatory
Default Value:	Not set
Valid Values:	Host Name or IP Address of the WFM Server
Dependencies:	None

This option specifies the host name or IP address of the server to which the report files will be transferred.

remotePort

Type:	Mandatory
Default Value:	21
Valid Values:	FTP or SSH Port on the remote WFM Server
Dependencies:	secureTransfer Option

This option allows users to define the port on the remote WFM Server to something other than the default FTP port of 21. For instance, the default SSH port is 22 and the option should be set to that when secureTransfer is enabled.

secureTransfer

Type:	Mandatory
Default Value:	false
Valid Values:	true, false
Dependencies:	keyPath, keyPassphrase, remotePort

This option specifies that the file transfer will be made over an SSH (Secure Shell) connection to the remote server rather than the default FTP protocol. A private key file must be created and stored on the server hosting the *Gplus* Adapter and the public key must be registered on the server hosting the WFM reporting application. Configuring an SSH connection is discussed <u>below</u> and <u>Appendix B</u> contains troubleshooting tips when problems occur.

userName

Type:	Mandatory
Default Value:	Not set
Valid Values:	Any alphanumeric user name registered on the remote
	server.
Dependencies:	None

This option specifies the username used to log in to the destination FTP server.

userPassword

Type:	Mandatory
Default Value:	Not set
Valid Values:	Any alphanumeric password
Dependencies:	User identified by userName.

This option specifies the password for the user identified by the userName Option and is required to establish the connection to the ftp server.

historical.reports Section

countIrregularIncoming

Type:OptionalDefault Value:falseValid Values:true, falseDependencies:None

This option specifies whether non-routed calls received by an agent will be reported in the Agent System Performance report as internal calls and their handle time allocated toward internal call time. The default adapter behavior is to report only incoming calls with the Genesys CallType of CallInternal as internal calls. If this option is set to true, all non-routed incoming calls received by the agent are counted as internal no matter what their Genesys CallType (CallInbound, CallConsult, etc.).

dailyReportEnabled

Type:	Optional
Default Value:	true
Valid Values:	true, false
Dependencies:	None

This option specifies whether the daily Agent Sign-on/Sign-off report will be generated by the *Gplus* Adapter. Daily reports are not required for all WFM integrations since some are replaced by RTA applications or require that optional WFM modules be purchased. This report will be the first report in the multiple report file that is generated at midnight.

directory

Type:	Mandatory
Default Value:	ftp/reports
Valid Values:	Any valid folder on the Gplus Adapter server
Dependencies:	None

This option specifies the directory where the report files will be saved as they are generated. Typically, this will be the directory monitored by the Adapter's file transfer client and the files will be immediately transferred to the remote server.

enabled

Type:	Mandatory
Default Value:	true
Valid Values:	true, false
Dependencies:	None

This option allows users to disable all historical reports for this particular Stream when only RTA data is required from the G*plus* Adapter.

filter

Type:	Optional
Default Value:	Not set
Valid Values:	A filterName (filter: <filtername> Section)</filtername>
Dependencies:	A filter Section must be defined.

This option allows users to associate the options defined in this Section with a defined filter section by setting the value to filterName. If multiple streams are not defined or the reports are going to include all of the Agents, Places and VQs defined in the genesys.*Groups Sections, then this option can be left blank.

iex.version

Type:	Optional
Default Value:	Not set
Valid Value:	4.x
Dependencies:	Version of IEX TotalView application

This option specifies which version of the IEX TotalView application is receiving the report files. The length of two report fields was increased in the transition to TotalView Version 4.0 and this option allows both the 4.x versions and the previous versions to be supported.

This option affects the length of the Queue and Agent fields in the four reports:

•	Queue		
	0	Previous	40 characters
	0	4.x	100 characters
•	Agent		
	0	Previous	40 characters
	0	4.x	256 characters

includeOutboundInternalInNOC

Type:	Optional
Default Value:	false
Valid Values:	true, false
Dependencies:	None

This option specifies which non-routed calls made by an agent will be reported on agent reports as outbound calls. The default behavior is report only the Genesys CallType of CallOutbound (external to the switch) as outbound calls. If this option is set to true, all non-routed calls (e.g. CallInternal) dialed by the agent are considered outbound calls.

intervalReportEnabled

Type:	Mandatory
Default Value:	true
Valid Values:	true, false
Dependencies:	None

This option specifies whether the following three reports will be included in the report file generated by the G*plus* Adapter on the interval specified by the intervalReport.interval Option:

- Contact Queue Report
- Agent Contact Queue Report
- Agent System Performance Report

intervalReport.interval

Type:	Mandatory
Default Value:	15
Valid Values:	15, 30
Dependencies:	None

This option specifies the period in minutes between interval reports. This option should be set to whatever the duration the WFM solution has been configured for. The reports are generated at set times in the hour depending upon the interval so a 15 minute interval would see reports created at 0:00, 0:15, 0:30 and 0:45 in each hour.

reportRetentionDays

Type:	Mandatory
Default Value:	30
Valid Values:	Any positive integer
Dependencies:	historical.ftp/localBackupDirectory

This option specifies the number of days that copies of the historical reports will be retained in the LocalBackupDirectory after the originals have been transferred to the remote server. If the LocalBackupDirectory has not been set, the local copies of the report files will not be backed up after being successfully transferred.

historical:<streamName> Section

This Section is optional and is used when the *Gplus* Adapter instance is providing more than one Stream. This Section is used to configure the historical component of the data feed to the IEX TotalView Server. The Options contained in this section combine the Options from both the <u>historical.reports</u> and <u>historical.ftp</u> Sections with a few additions. The Options are listed below and the additions are discussed.

Report Options

- countIrregularIncoming
- dailyReportEnabled
- <u>enabled</u>
- <u>filter</u>
- <u>iex.version</u>
- includeOutboundInternalInNOC
- intervalReportEnabled
- intervalReport.interval
- <u>reportRetentionDays</u>
- siteBased

The <u>application/siteBased</u> Option only applies to the stream defined in the historical.reports Section. This stream Option allows the site based reports to be configured on a stream by stream basis.

There is no directory option for the Stream configuration as the adapter automatically creates subdirectories in the directory configured by the <u>historical.reports/directory</u> Option. The created stream directory uses this Section's streamName as its name.

FTP Options

- <u>ftp.backupRetentionDays</u>
- <u>ftp.connectionMode</u>
- ftp.enabled

This Option is the surrogate for the historical.ftp/enabled Option that enables (value = true) or disables (value = false) the transfer of the historical reports to the remote IEX server.

- <u>ftp.keyPath</u>
- <u>ftp.keyPassphrase</u>
- <u>ftp.localBackupDirectory</u>
- <u>ftp.localSourceDirectory</u>
- <u>ftp.remoteDestinationDirectory</u>
- <u>ftp.remoteHost</u>
- <u>ftp.remotePort</u>
- <u>ftp.secureTransfer</u>
- <u>ftp.userName</u>
- <u>ftp.userPassword</u>

interactionCodeMappings Section

This section is optional and must be added manually as it is not included in the Application Template. When the section is included, the reasons parsed by the interaction.reason.determiner(s) will be compared against the Option key names in this section. If there is a match, the parameters listed in the Option value will be used. There are two possible parameters:

1. idnew RTA state.2. namenew reason code.

The id field can be the new RTA State Name as defined in the <u>RTA State table</u>. The name field is the new Reason that will be included with the RTA state message sent to the TotalView server.

The $\langle null \rangle$ Option key signifies an event with no reason attached and it is used to configure a default behavior for the *Interaction* events.

Note: Contact Professional Services before configuring this section.

🙀 GPlusAdapter [gen81:2020] Prope	rties
General Server Info Start Info Conr	nections Options Security Dependency
sinteractionCodeMappings	🧿 🗈 🗙 🔄 🕸 🕼 🐠
Name 📥	Value
Enter text here	The second secon
abe <null></null>	"name='Normal"
مهد billing_segment	"id='Billing"

interactionTargets Section

This Section is optional but it is required when Interaction Queues are used within Business Process Routing Strategies as the reporting objects. If only Virtual Queues defined on a Switch are used as reporting objects, this Section is not required. The situation is slightly different for email or other media where the interactions must also be tracked after they leave the agent's desktop. In that situation, outbound queues or Quality Assurance queues must also be monitored. This is explained in more detail in the following section.

The Gplus Adapter will report on the list of Interaction Queues contained within this section. Each Option name represents the specific name of an actual Interaction Queue defined in the Configuration Server. For each Interaction Queue, the Option value can be used to specify the serviceLevelThreshold (See <u>Threshold Format</u>) and the shortName for the Interaction Queue that will be used in the reports sent to the WFM application. It should be noted that the shortName field does not actually have to be shorter than the Interaction Queue name.

Туре:	Optional		
Default Value:	Not Set		
Valid Values:	See example belo	OW	
Dependencies:	email/enabled,	chat/enabled,	media: <name>/enabled</name>

	GPlusAdapter [gen8]	1:2020	Properties	
L I	General Server Info S	Start Info	O Connections Options Security Depend	dency
	sinteraction Targets		- 😼 🗋 🗙 🔜	۵ 🙀 🕲
	Name 🔺		Value	
	Enter text here	Y	Enter text here	7
Installation and Con	<u>ملە</u> CustomerService ملە QA_Queue ملە Sales_IQ		"serviceLevelThreshold='1h', shortName='CS' "serviceLevelThreshold='10m', shortName='Q "shortName='Sales""	

ixnProcessObjects Section

The Gplus Adapter uses the list of Interaction Queues contained in this Section to determine how to report on media activity at various routing stages. The Option values categorize the monitored Interaction Queues as to their role in the Genesys Business Process Routing Strategies.

Each Option name within this section represents the specific name of an Interaction Queue configured as a Script in the Configuration Server. The Option Value associates the queue with one of the routing strategy roles defined by the G*plus* Adapter.

All Interaction Queues involved with outbound media interactions, transferring a routed media interaction or holding an interaction for quality assurance routing must be added and categorized in this Section with one exception: Interaction Queues where media interactions are parked and waiting to be routed to an agent (e.g. an InboundQueue) should only be added if Interaction Queues instead of Virtual Queues will be used as the reporting "queue" object on the interval report.

Type: Default Value:	Mandatory for email Not Set
Valid Values:	InboundQueue, OutboundQueue, QAQueue, AgentWorkbin, AgentGroupWorkbin, PlaceWorkbin, PlaceGroupWorkbin
Dependencies:	email∕enabled, chat∕enabled, media: <name>⁄enabled</name>

눩 GPlusAdapte	r [gen81:20	20] Pro	perties		×
Annex			Security	Depen	dency
General	Server In	fo	Start Info	Connections	Options
vn Process	sObjects		▼ 🤌 Value	🗋 🗙 🚍 🕉) 🕞 🕲
Enter text her	e	7	Enter text here		7
abc Customer abc Out_Q abc QA_Q abc Sales_IQ	Service_IQ		"InboundQueue "OutboundQueu "QAQueue" "InboundQueue	je"	

media:<name> Section

The present version of the *Gplus* Adapter has defined configuration Options for each of the following media:

- voice
- email
- outboundpreview
- chat

This section allows configuration for a generic media supported by the Interaction Server that may be unique to one call center. The <name> portion of the section name must correspond to the Media Type attribute contained in the Interaction Server events.

Besides a straightforward configuration of how the adapter will deal with the new media, this section also has options that define associations with the other configured media types. It should be noted that this section should be used to configure the media that wraps or initiates the associated media interactions.

Note:	ThisMedia is used as an identifier in the following discussion for the media that is configured within this section. OtherMedia
	describes any media that may be associated with ThisMedia in multiple media interactions.

acwReason


Туре:	Optional
Default Value:	ACW
Valid Values:	Any text string
Dependencies:	NotReady Reason is attached by agent desktop

This option identifies the Reason string attached to a NotReady event that will signify the start of a Wrap (AfterInteractionWork) state rather than an Unavailable state.

associationType

Type: Optional Default Value: none Valid Values: handle, work, target or none Dependencies: OtherMedia

The diagram below demonstrates two associated media interactions and the time intervals defined by the association. This diagram will be used to clarify the alternative values that deal with the non-overlapping time (A and C) for the two media.



- none
 - there is no association with the OtherMedia type
 - all of the interaction time for ThisMedia is reported as handle time
 - all of the interaction time for OtherMedia is reported as handle time if that interaction was routed
- handle
 - non-overlapping time (A and C) will be reported as handle time for ThisMedia
- work
 - non-overlapping time (A and C) will be reported as wrap up (AfterInteractionWork) time for ThisMedia
- target
 - the target determined for ThisMedia interaction will be used for the OtherMedia interaction
 - none of the non-overlapping time (A and C) will be reported

Note: Contact Professional Services prior to configuring this option as it will require a detailed understanding of the association between the two related media.

defaultAbandonedThreshold

Type:	Optional
Default Value:	0s
Valid Values:	See Threshold Format
Dependencies:	historical.reports/serviceLevelFormula

This option specifies the default abandoned threshold for the service level calculations that form part of the interval reports. It is also quite possible that there is no mechanism to actually abandon a ThisMedia interaction and this option can be ignored.

This option should be set when a single abandoned threshold is used as a default for all ThisMedia targets. Individual abandoned thresholds can be set for each ThisMedia target/queue by adding Annex Data to the ThisMedia Virtual Queues as shown in a later <u>section</u> or adding the threshold to an Interaction Queue as described in the <u>interactionTargets</u> Section. These individual thresholds will override the default specified by this option.

defaultServiceThreshold

Type:	Optional
Default Value:	Øs
Valid Values:	See Threshold Format
Dependencies:	markServicedOn

This option specifies the default service threshold for the service level calculations that form part of the interval reports. A ThisMedia is considered *serviced* at either the start or the end of the agent's involvement with the interaction depending on the markServicedOn Option.

This option should be set when a single service threshold is used as a default for all ThisMedia targets. Individual service thresholds can be set for each ThisMedia target/queue by adding Annex Data to the ThisMedia Virtual Queues as shown in a later <u>section</u> or adding the threshold to an Interaction Queue as described in the <u>interactionTargets</u> Section. These individual thresholds will override the default specified by this option.

defaultTarget

Type:	Optional
Default Value:	UnknownTarget
Valid Values:	Any text string
Dependencies:	application/countUnattachedACW

This option allows users to define a separate target/queue for this media other than the default value used by the *Gplus* Adapter to report on unattached wrap

up (AfterInteractionWork) time. This option is only applicable when the application/countUnattachedACW Option is set to true.

Unattached wrap up time is defined as the time that the agent spends in an AfterInteractionWork state when the agent has not yet received a routed interaction of the ThisMedia type since logging in.

deleteOnTransfer

Type:	Optional
Default Value:	false
Valid Values:	true, false
Dependencies:	OtherMedia,
	associationType

This option deals with a transfer scenario where the OtherMedia interaction is transferred to another agent but there is no "End of Interaction" event received for ThisMedia. If this option is set to true, the ThisMedia interaction will be terminated when the transfer is completed.

Note: Contact Professional Services prior to configuring this option as it will require a detailed understanding of the association between the two related media.

enabled

Type:	Mandatory
Default Value:	false
Valid Values:	true, false
Dependencies:	None

This option must be set to true to capture and report on historical ThisMedia activity in the contact center. It is possible to disable the tracking of media activity if required.

interaction.reason.determiner

Type:	Optional
Default Value:	Not set
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	enabled, rta/enabled

This option specifies the attribute of a ThisMedia Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:

• EventPartyAdded

• EventPropertiesChanged while the agent is a party to a routed interaction of the ThisMedia type.

Certain implementations may require that the combination of a RoutedOpenMediaWork RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the interactionCodeMappings Section.

Note: Contact Professional Services before using this option.

markServicedOn

Type:	Mandatory	
Default Value:	answered	
Valid Values:	answered,	released
Dependencies:	None	

This option indicates when an interaction of the ThisMedia type is considered to be serviced for the Service Level Threshold calculations. Either when the agent first *answers* the interaction or when the agent has completed handling the interaction.

otherIdDeterminer

Type:	Optional
Default Value:	Not Set
Valid Values:	Any valid determiner.
Dependencies:	OtherMedia,
	associationType, thisIdDeterminer

This option identifies the determiner used to uniquely identify the OtherMedia interaction and provide the association back to the ThisMedia interaction that forms the other half of connected interactions.

Note: Contact Professional Services prior to configuring this option as it will require a detailed understanding of the association between the two related media.

otherMediaTypes

Optional

Default Value:	Not Set
Valid Values:	Comma delimited list of media names.
Dependencies:	OtherMedia,
	associationType

This option lists the names of the OtherMedia that could be associated with ThisMedia.

Note: Contact Professional Services prior to configuring this option as it will require a detailed understanding of the association between the two related media.

reason.notReady.determiner

Type:	Optional
Default Value:	eventAttribute: ReasonDescription
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	enabled, rta/enabled

This option specifies the attribute of a ThisMedia Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:

- EventNotReadyForMedia
- EventMediaStateReasonChanged while the agent is NotReady to receive a routed interaction of a ThisMedia type.

Certain implementations may require that the combination of an Unavailable RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>reasonCodeMappings</u> Section

Note: Contact Professional Services before using this option.

reason.ready.determiner

Type:	Optional
Default Value:	Not set
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	enabled, rta/enabled

This option specifies the attribute of a ThisMedia Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:


• EventReadyForMedia

Certain implementations may require that the combination of an Available RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>readyCodeMappings</u> Section.

Note: Contact Professional Services before using this option.

reportingType

Type:	Optional	
Default Value:	thisInteraction	
Valid Values:	thisInteraction,	otherInteraction
Dependencies:	OtherMedia,	
	associationType	



This option determines whether the ThisMedia or the OtherMedia activity is reported upon for the overlapping interval (B) in the offered and handled metrics.

Note: Contact Professional Services prior to configuring this option as it will require a detailed understanding of the association between the two related media.

rta.routedInteractionState

Type:	Optional
Default Value:	InteractionInbound
Valid Values:	Any valid text string no more than 20 characters
Dependencies:	rta.nonRoutedInteractionState,
	rta.acwInteractionState

This option identifies the agent state value that will be passed to the IEX RTA server when the agent is handling a ThisMedia interaction that was routed through a monitored queue to that agent.

rta.nonRoutedInteractionState

Type:	Optional
Default Value:	InteractionInternal
Valid Values:	Any valid text string no more than 20 characters
Dependencies:	rta.routedInteractionState,
	rta.acwInteractionState

This option identifies the agent state value that will be passed to the IEX RTA server when the agent is handling a ThisMedia interaction that was not routed through a monitored queue to that agent.

rta.acwInteractionState

Type:	Optional
Default Value:	AfterInteractionWork
Valid Values:	Any valid text string no more than 20 characters
Dependencies:	rta.routedInteractionState,
-	rta.nonRoutedInteractionState

This option identifies the agent state value that will be passed to the IEX RTA server when the agent is wrapping up a concluded ThisMedia interaction that was routed through a monitored queue to that agent.

targetProperty

Type:	Mandatory
Default Value:	eventAttribute: interactionProperties.interactionQueue
Valid Values:	Any valid Interaction target determiner.
Dependencies:	None

This option identifies the event attribute that the adapter will use to identify the target/queue for the ThisMedia in the same way as the event.properties/interactionTarget.determiner is defined for email.

thisIdDeterminer

Type:	Optional
Default Value:	Not Set
Valid Values:	Any valid determiner
Dependencies:	OtherMedia,
	associationType, otherIdDeterminer

This option identifies the determiner used to uniquely identify the ThisMedia interaction and provide the association back to the OtherMedia interaction that forms the other half of connected interactions.

Note: Contact Professional Services prior to configuring this option as it will require a detailed understanding of the medias' association.

outbound Section

defaultTarget

Type:	Optional
Default Value:	UnknownTarget
Valid Values:	Any text
Dependencies:	application/countUnattachedACW

This option allows users to define a separate outbound target/queue or campaign name other than the default value used by the *Gplus* Adapter for all media. This value is used to report on an agent's time outside of actual outbound activity (including unattached ACW) when that time cannot be associated with an actual outbound target/queue or campaign name.

dialingDN

Type:	Optional
Default Value:	Not Set
Valid Value:	Name of an actual Trunk Group
Dependencies:	Predictive or Progressive Campaign Type

This option specifies the name of the Trunk Group that is used in either Predictive or Progressive campaigns to dial the outbound calls.

dialingRouteGroup

Type:	Optional
Default Value:	Not Set
Valid Value:	Name of an actual Routing Point DN Group
Dependencies:	Predictive or Progressive Campaign Type

This option specifies the name of the DN Group that contains the Routing Points (RPs) used in either Predictive or Progressive campaigns to dial the outbound calls.

enabled

Type:	Mandatory
Default Value:	false
Valid Values:	true, false
Dependencies:	event.properties/campaignTarget.determiner.

This option allows users to enable reporting of outbound campaign calls in the Contact Queue and Agent Contact Queue reports. See <u>Outbound Campaign</u> <u>Calls</u> for more information.

recordProcessedOnRelease

Type:	Optional
Default Value:	true
Valid Values:	true, false
Dependencies:	Predictive or Progressive Campaign Type
	OCS OCServer/record_processed Option

This option sets when the Gplus Adapter considers the Outbound Contact Server (OCS) outbound call record to be finished. If this option is set to true, then the record is marked as processed when the outbound call is released. If the option is set to false, the record is considered processed when a specific EventUserEvent is received after the call has been released.

readyCodeMappings Section

This section is optional and must be added manually as it is not included in the Application Template. When the section is included, the reasons parsed by the reason.ready.determiner(s) will be compared against the Option key names in this section. If there is a match, the parameters listed in the Option value will be used. There are four possible parameters:

1.	id	new RTA state.
2.	name	new reason code.

Annex			Security	Depen	dency
General	Server Inf	0	Start Info	Connections	Options
Name 🔺			Value		
Name 🗖			Value		
Enter text here)	7	Enter text here		7
abe <null></null>			"name='voice"		

The id field can be the new RTA State Name as defined in the <u>RTA State table</u>. The name field is the new Reason that will be included with the RTA state message sent to the TotalView server.

The $\langle null \rangle$ Option key signifies an event with no reason attached and it is used to configure a default behavior for the *Ready* events.

Note: Contact Professional Services before configuring this section.

reasonCodeMappings Section

This section is optional and must be added manually as it is not included in the Application Template. When the section is included, the NotReady reasons parsed by the reason.notReady.determiner will be compared against the Option key names in this section. If there is a match, the parameters listed in the Option value will be used. There are three possible parameters:

1		i	d	

- 2. name
- 3. state

new RTA state. new NotReady reason code. NotReady or ACW

Annex			Security	Depe	endency
General	Server	Info	Start Info	Connections	Options
🦢 reasonCode	Mappings			🗋 🗙 🔜 (D 🙀 🖉
‱ reasonCode Name ▲	Mappings	•	▼ Ø	🗋 🗙 🔜 (9 🕞 🕑
Name 🔺	Mappings	J	Value	🗋 🗙 🛃 (
	Mappings	7		· · ·	9 🗟 🖉

The id field if defined, must be the new RTA State Name as listed in the <u>RTA State table</u>. The name field is the new Reason that will be included with the RTA state message sent to the WFM server. The state field allows the event to be interpreted as either Unavailable or ACW in the historical reports.

The <null> Option key signifies an event with no reason attached and it is used to configure a default behavior for the NotReady events.

Note:

Contact Professional Services before configuring this section.

rta Section

enabled

Type:	Mandatory
Default Value:	true
Valid Values:	true, false
Dependencies:	None

The option allows users to disable the RTA data stream for G*plus* Adapter installations where RTA data is not required.

filter

Type:OptionalDefault Value:Not set

Valid Values:	A filterName (filter: <filtername> Section)</filtername>
Dependencies:	A filter Section must be defined.

This option allows users to associate the options defined in this Section with a defined filter section by setting the value to filterName. If multiple streams are not defined, then this option can be left blank and the RTA stream will be associated with the Agents, VQs and Places defined by the genesys.*Groups sections.

iex.listenPort

Type:MandatoryDefault Value:6999Valid Values:Any open port on Gplus Adapter hostDependencies:None

This option sets the port that the *Gplus* Adapter listens on while waiting for a connection request from the IEX RTA application

iex.password

Type:OptionalDefault Value:IEXValid Values:Any alphanumeric password.Dependencies:iex.userName

The listen port can be configured to require a password from the connecting IEX RTA application. This option specifies the password for a valid socket request.

iex.userName

Type:OptionalDefault Value:Blank (empty text string)Valid Values:Any alphanumeric user name.Dependencies:iex.password

The listen port can be configured to require a user name from the connecting IEX RTA application. This option specifies the user name for a valid socket request.

reportDndAsNotReady

Type:OptionalDefault Value:trueValid Values:true, falseDependencies:None

The default behavior is for the Adapter to report Do Not Disturb time as the NotReady RTA state. This option allows the Adapter to report that time as the DndOn RTA state if set to false.

stateTransformer.class

Type:MandatoryDefault Value:com.ariasolutions.iconnect.rta.lexBaseRTAStateTransformerValid Values:com.ariasolutions.iconnect.rta.lexBaseRTAStateTransformerDependencies:None

This option specifies the Java class that defines the mapping of Genesys events to state transitions in the RTA data stream. There is a standard mapping for each vendor that is defined by the behavior of the state transformer class.

rta:<streamName> Section

This Section is optional and is used when the *Gplus* Adapter instance is providing more than one data Stream. This Section is used to configure the Real Time Adherence (RTA) component of the data feed to the IEX TotalView Server. The Options are listed below but are not discussed here as they directly correspond to those listed in the <u>rta</u> section.

Options

- <u>enabled</u>
- <u>filter</u>
- <u>iex.listenPort</u>
- iex.password
- iex.userName
- <u>reportDndAsNotReady</u>
- <u>stateTransformer.class</u>

voice Section

defaultAbandonedThreshold

Type:	Optional
Default Value:	0s
Valid Values:	See Threshold Format
Dependencies:	None

This option specifies the default abandoned threshold for the Abandoned In Threshold column in the Contact Queue report. This option is set when a single abandoned threshold is used for all voice targets. Individual abandoned thresholds can be set for each voice target/queue by <u>adding Annex</u> <u>Data</u> to the voice Virtual Queues included in the genesys. queueGroups Section.

defaultServiceThreshold

Type:	Optional
Default Value:	0s
Valid Values:	See Threshold Format
Dependencies:	None

This option specifies the default service threshold for the service level calculations that form part of the interval reports. An inbound voice call is considered *serviced* at the time that the agent answers the call.

This option should be set when a single service threshold is used as a default for all inbound voice call targets. Individual service thresholds can be set for each inbound voice call target/queue by adding Annex Data to the voice Virtual Queues as shown in a later <u>section</u>. These individual thresholds will override the default specified by this option.

defaultTarget

Type:	Optional
Default Value:	UnknownTarget
Valid Values:	Any text string
Dependencies:	application/countUnattachedACW

This option allows users to define a separate contact type/queue other than the default value used by the *Gplus* Adapter to report on unattached After Call Work time. This option is applicable if the application/countUnattachedACW Option in the application Section is set to true.

Unattached AfterCallWork time is defined as the time that the agent spends in a NotReady state initiated by an EventAgentNotReady containing a WorkMode attribute of 3 during the portion of a login session when the agent has not yet answered a routed call.

enabled

Type:	Mandatory
Default Value:	false
Valid Values:	true, false
Dependencies:	None

This option is set to true to capture and report on inbound voice call activity in the contact center. It is possible to disable the tracking of voice activity if the *Gplus* Adapter was installed to only track the agents other media interactions.

interaction.reason.determiner

Type:	Optional
Default Value:	Not set
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	voice/enabled, rta/enabled

This option specifies the attribute of a TServer/SIPServer voice Event that will be included as the Reason field of an RTA state message generated by one of the following events:

- EventEstablished
- EventHeld
- EventPartyAdded
- EventPartyChanged
- EventPartyDeleted
- EventRetrieved

Certain implementations may require that the combination of a voice call RTA state and its reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>interactionCodeMappings</u> Section.

isAfterCallWork.class

Type:	Optional
Default Value:	Not Set
Valid Values:	Check with Technical support.
Dependencies:	None

The option overrides the default behavior for determining whether an agent has entered an ACW state. One, PresumptiveAfterCallWorkProperty, can be used to report all NotReady time as After Call Work.

parallelQueuesEnabled

Type:	Optional
Default Value:	false
Valid Values:	true, false
Dependencies:	Routing strategy

This option is set to true to report a call against a different queue than the first monitored queue in one particular circumstance. Genesys routing can place a call in additional queues to broaden the target agent group if the call has been waiting in the original queue for a set period. This option, if set to true, allows the target for the customer call to be associated with the queue that the call was diverted from rather than defaulting to the original queue.

Note: Contact Professional Services prior to changing this option.

reason.notReady.determiner

Type:	Optional
Default Value:	eventAttribute: Reasons.ReasonCode
Valid Values:	eventAttribute: {Event attribute name}
	class: {custom Java class name}
Dependencies:	voice/enabled, rta/enabled

This option specifies the attribute of a voice TServer/SIPServer event that will be included as the Reason field of an RTA state message generated by one of the following events:

EventAgentNotReady

Certain implementations may require that the combination of an Unavailable RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>reasonCodeMappings</u> Section

Note: Contact Professional Services before using this option.

reason.ready.determiner

Type:	Optional
Default Value:	Not set
Valid Values:	<pre>eventAttribute: {Event attribute name}</pre>
	class: {custom Java class name}
Dependencies:	enabled, rta/enabled

This option specifies the attribute of a ThisMedia Interaction Server Event that will be included as the Reason field of an RTA state message generated by one of the following events:

• EventAgentReady

Certain implementations may require that the combination of an Available RTA state and the reason code map to a different RTA state and reason text string. This mapping can be configured in the <u>readyCodeMappings</u> Section.

Note: Contact Professional Services before using this option.



Chapter

4 Additional Configuration

Adding T-Servers and Interaction Servers

The application establishes connections with the TServers, SIP Servers, Interaction Servers and Message Servers listed under the Connections tab of the Properties window. Adding a server is accomplished in exactly the same way that any other Genesys application would add connections to servers in the Genesys environment.

Select the Add button and then the Browse button at the end of the Server line on the Connection Info Properties window. The adapter supports connections to multiple TServers/SIP Servers/Interaction Servers and using the addp connection protocol for those connections. Only the Primary servers should be added to the Connections tab, as the Backup servers will be identified from the Primary's configuration and included automatically.

Transport Layer Security (TLS) can also be added to a server connection by checking the Secure checkbox. This assumes that the *Security Deployment Guide* has been followed to properly install certificates etc.

Threshold Time Format

The service level calculations are based upon calls/interactions that meet or do not meet configured service or abandoned time thresholds. These thresholds can be set as a default per media or added to the following configuration objects: Skills, Virtual Queues and interactionTargets. The default for setting the threshold time is to specify it in milliseconds. However, a more user friendly version is also available where the threshold time is specified in terms of days, hours, minutes and seconds. A typical call center would have a service (answered) threshold for inbound calls that would be in the range of 20 to 30 seconds whereas a threshold for emails may be measured in hours or days. The following format allows a range of time values to be specified without having to calculate the millisecond equivalent:

{0-31}d{0-24}h{0-60}m{0-60}s

Examples:

15000	15000 milliseconds
60s	60000 milliseconds
45m	2700000 milliseconds
1d12h30m	131400000 milliseconds

Note: Each field size is restricted to two characters so none of the numbers can be larger than 99. It would be advisable to use the ranges specified above.

Adding Annex Data for Virtual Queues and Skills

This section discusses adding individual configuration to a Skill or Virtual Queue with the end result being additional configuration of the associated call/interaction target. Three parameters can be added to these Configuration Objects to modify the reported results:

- abandonedThreshold
- serviceLevelThreshold
- shortName

The Contact Queue report deals with statistics for each Contact Group and the two thresholds can differ between Groups as the business expectations for each type of customer call will vary. Associating the thresholds with a specific Skill or Virtual Queue allows the reports to take into account the different response expectations.

Configuring abandoned thresholds for an email Virtual Queue while allowed would have little effect as emails are not abandoned.

The figure below shows an example with the opened Annex tab for a Virtual Queue object in the Configuration Manager. Adding the threshold settings to a Skill object is essentially the same process. The question of which of the two object types will be configured with the thresholds is answered by the <u>application/callType</u> Option.

CustomerService_VQ [gen81:2020] Properties			
General Advanced Default DNs Annex Security Dependency			
🍆 GPlus_WFM 🔹 🎓 📔 🗙 🛛 🔂			
Name A Value			
Enter text here	?		
absc abandoned Threshold "15s" absc service Level Threshold "5m30s" absc short Name "CS"			

The following steps should be followed to add a serviceLevelThreshold or abandonedThreshold to a Virtual Queue.

- 1. Select the Virtual Queue in the Configuration Manager and open the Properties frame.
- 2. Select the Annex tab.
- 3. Add a GPlus_WFM Section or if the <u>application/annexSection</u> Option has been set, add a Section with the name configured there.
- 4. In the new Section, add an Option with the Name set to serviceLevelThreshold or abandonedThreshold with value equal to the new threshold as described <u>above</u>.

If the Skill or Virtual Queue (Number or Alias fields) name exceeds the report field size or the WFM application requires something different than the actual name, the shortName option can be added to the Annex tab of the Virtual Queue as follows:

- 1. Create a GPlus_WFM section in the Annex tab if it does not exist already.
- 2. Add a new option to this section named shortName with the Value set to the new text string.
- 3. This value will now be used in place of the original Virtual Queue/Skill name in all reports.

Adding A PlaceGroup to a Site

All of the reports can include Site information if required. The G*plus* Adapter creates an association between Place Groups and Sites by adding a siteName option to a Place Group's Annex Data. Only the Place Groups included in the genesys.placeGroups Section of the Options will be included and, therefore, only those Place Groups should be modified.

To add a Site name for use in reporting:

- 1. Add a GPlus_WFM Section or if the <u>application/annexSection</u> Option has been set, add a Section with the name configured there.
- 2. Add a new option to this section named siteName with the new Site name as the value.
- 3. This name will be used as the Site identifier in the reports



Chapter

5 Setting Up Secure File Transfer

The file transfer protocol that forwards the historical reports to the remote WFM server can be configured to use SSH (Secure Shell) as the underlying network channel. Three options are included in the <u>historical.ftp</u> section of the application configuration to set up the *Gplus* Adapter as an SSH client. The configuration of the client side of the SSH channel is reasonably simple as most of the complexity is reserved for the configuration of the server side.

A description of some of the possible errors due to a misconfigured client or server has been included as Appendix B.

Generating the Private-Public Key Pair

The authentication of the SSH login to the remote server can be carried out using a public-private key pair. The private key is stored on the G*plus* Adapter server and the public key is stored on the remote IEX server. When the keys are generated, it is also possible to specify a key passphrase to further limit access to the private key.

The embedded SSH client supports SSH2 RSA keys. The SSH2 protocol does not specify a standard key format and there are key formats that are not compatible with the SSH client used in the Adapter. Keys generated by the PuTTY gen key generation tool are not compatible. Keys generated by the OpenSSH ssh-keygen tool are compatible. Tools using the following ciphers should be compatible:

- aes256-ctr
- aes192-ctr
- aes128-ctr
- aes256-cbc

- aes192-cbc
- aes128-cbc
- 3des-ctr
- arcfour
- arcfour128
- arcfour256

As mentioned, the private key is stored with the Gplus Adapter where the embedded SSH client can access it. This key is usually stored in the config folder of the Adapter installation.

Storing the public key will be specific to the SSH server that has been used on the IEX server. The public key will have to be placed in a certain folder and the key will have to be registered with the SSH server. Both of these actions are implementation specific and should be fully described in the SSH server documentation.

Client Configuration

The following options in the historical.ftp section must be configured or at least considered:

enabled	true or the files are not transferred
remoteHost	host name of the destination server
remotePort	host port on the destination server
secureTransfer	true to use SSH as a secure connection
userName	user registered on the destination server
userPassword	password for the user identified by userName
keyPath	path and name of the private key file
keyPassphrase	pass phrase that allows access to the private key

Server Configuration

The SSH server should support configuration for the authentication modes that it allows and which mode it will attempt first. The two supported options for the Adapter are public key or password. Password authentication is not as secure because the userPassword option is retained as plain text in the Configuration Manager. The public key authentication is more secure and more difficult to implement.



Chapter

6 Outbound Voice Campaigns

The G*plus* Adapter now supports the Outbound Campaign types that did not fit the original inbound voice call model used to define a customer call. This chapter will discuss the Outbound Campaign types and how the Adapter classifies the calls associated with the campaigns.

There are four types of Genesys outbound campaigns that can be monitored by the *Gplus* Adapter:

- 1. Predictive
- 2. Progressive
- 3. Preview
- 4. Push Preview

The first two, Predictive and Progressive, are routed to the agent after being dialed by the dialer while the second two, Preview and Push Preview are essentially dialed from the agent's phone. All four types have a campaign name included in the event attributes that the event.properties/campaignTarget.determiner can parse.

Predictive and Progressive Campaigns


Both the Predictive and Progressive campaign types have call flows that start as a dialing event on a Routing Point, queued on a Virtual Queue, diverted to and then answered by an available agent with an optional ACW interval after the call is released. The adapter does not differentiate between the two campaign types.

The Adapter attempts to determine the campaign name at two points in the call flow: first by parsing the dialing event associated with the monitored Routing Point and if that fails, parsing the queued event on the monitored Vintual Queue. It is still important that the Vintual Queue associated with the targeted Agent Group also be monitored. The time that the call waits in queue for an available agent is still required for the Contact Queue report.

The Figures below illustrate the reason for including the <u>recordProcessedOnReleased</u> Option depending upon the events generated at the conclusion of the call. This Option specifies whether the Outbound Contact Server (OCS) record associated with the call is closed at the conclusion of the call or at a subsequent point marked by a record processed UserEvent.


recordProcessedOnReleased = true

The first Figure shows the record being processed at the conclusion of the call. There is no wrap time associated with an open OCS record and any disposition codes must be attached to the call prior to the call being released.




recordProcessedOnReleased = false

The second Figure shows the record being processed after the conclusion of the call. There is wrap time associated with an open OCS record and also ACW time associated with the call that is counted after the record is processed. Any disposition codes must be added to the call prior to the record being processed.



recordProcessedOnReleased = false - Record Closed Prematurely

The third Figure shows the record being closed on an error generated by the OCS when the agent goes into a Ready state rather than marking the OCS record as done. Any errors caused by state changes or problems with the OCS will result in the Adapter considering the record closed. There is wrap time associated with an open OCS record up to the agent state change but any disposition codes attached to the call after the state change are discarded by OCS.



Preview and Push Preview Campaigns

The Preview and Push Preview campaign types are restricted to using the campaignTarget.determiner to identify the campaign name. This is the default behavior for the Adapter and the campaign calls will be reported in the Contact Queue and Agent Contact Queue reports.

Non Campaign Outbound Calls

If the both the campaignTarget.determiner and the callType.determiner fail to parse a campaign name or target for an outbound call, the call will not be reported in the Contact Queue report. These calls will be regarded as outbound calls but they will be counted in the Agent System Performance report as non-customer outbound activity.



Chapter

7 Streams and Filters

Multiple Streams

Prior versions of the adapter were limited to a single Stream where there was one set of historical reports generated and one RTA connection supported. Multiple Streams allow subsets of the accumulated data to be sent to different IEX TotalView servers through the use of Filters that identify the data subsets and Streams that identify the destination for that data.

Filters are configured as separate Option Sections in the Gplus Adapter Configuration as described in the <u>filter:<filtername></u> Section. A Filter defines a set of monitored Agents, Places and Virtual Queues (VQs) that any associated Stream will report upon. Only Agents, Places and VQs that are part of the groups configured in the genesys.*Groups Sections are candidates to be included in a filter. It is not possible to include Agent, Place or VQ groups that are not included in the genesys.*Groups Sections.

Streams are associated with Filters with a singular reference to the Filter name but multiple Streams can be associated with a single Filter. The obvious configuration would be a historical and a rta stream "connected" to the same Filter. Another configuration might see two historical streams: one siteBased and the other not.

Appendix 7: Time Zone ID List



Appendix

A Time Zone ID List

The list of acceptable values to specify the G*plus* Adapter timeZone Option mirrors the list of acceptable Time Zone Ids for the Java JVM. For reference the supported option values are listed in the table below. The recommended value is to use one of the Region/Locale formats if possible as they deal with Daylight Savings Time transparently.

ACT	AET	AGT
ART	AST	Africa/Abidjan
Africa/Accra	Africa/Addis_Ababa	Africa/Algiers
Africa/Asmara	Africa/Asmera	Africa/Bamako
Africa/Bangui	Africa/Banjul	Africa/Bissau
Africa/Blantyre	Africa/Brazzaville	Africa/Bujumbura
Africa/Cairo	Africa/Casablanca	Africa/Ceuta
Africa/Conakry	Africa/Dakar	Africa/Dar_es_Salaam
Africa/Djibouti	Africa/Douala	Africa/El_Aaiun
Africa/Freetown	Africa/Gaborone	Africa/Harare
Africa/Johannesburg	Africa/Kampala	Africa/Khartoum
Africa/Kigali	Africa/Kinshasa	Africa/Lagos
Africa/Libreville	Africa/Lome	Africa/Luanda
Africa/Lubumbashi	Africa/Lusaka	Africa/Malabo
Africa/Maputo	Africa/Maseru	Africa/Mbabane
Africa/Mogadishu	Africa/Monrovia	Africa/Nairobi
Africa/Ndjamena	Africa/Niamey	Africa/Nouakchott
Africa/Ouagadougou	Africa/Porto-Novo	Africa/Sao_Tome

Africa/Timbuktu	Africa/Tripoli	Africa/Tunis
Africa/Windhoek	America/Adak	America/Anchorage
America/Anguilla	America/Antigua	America/Araguaina
America/Argentina/Buenos_Aires	America/Argentina/Catamarca	America/Argentina/ComodRivadavia
America/Argentina/Cordoba	America/Argentina/Jujuy	America/Argentina/La_Rioja
America/Argentina/Mendoza	America/Argentina/Rio_Gallegos	America/Argentina/San_Juan
America/Argentina/Tucuman	America/Argentina/Ushuaia	America/Aruba
America/Asuncion	America/Atikokan	America/Atka
America/Bahia	America/Barbados	America/Belem
America/Belize	America/Blanc-Sablon	America/Boa_Vista
America/Bogota	America/Boise	America/Buenos_Aires
America/Cambridge_Bay	America/Campo_Grande	America/Cancun
America/Caracas	America/Catamarca	America/Cayenne
America/Cayman	America/Chicago	America/Chihuahua
America/Coral_Harbour	America/Cordoba	America/Costa_Rica
America/Cuiaba	America/Curacao	America/Danmarkshavn
America/Dawson	America/Dawson_Creek	America/Denver
America/Detroit	America/Dominica	America/Edmonton
America/Eirunepe	America/El_Salvador	America/Ensenada
America/Fort_Wayne	America/Fortaleza	America/Glace_Bay
America/Godthab	America/Goose_Bay	America/Grand_Turk
America/Grenada	America/GuadeLoupe	America/Guatemala
America/Guayaquil	America/Guyana	America/Halifax
America/Havana	America/Hermosillo	America/Indiana/Indianapolis
America/Indiana/Knox	America/Indiana/Marengo	America/Indiana/Petersburg
America/Indiana/Vevay	America/Indiana/Vincennes	America/Indianapolis
America/Inuvik	America/Iqaluit	America/Jamaica
America/Jujuy	America/Juneau	America/Kentucky/Louisville
America/Kentucky/Monticello	America/Knox_IN	America/La_Paz
America/Lima	America/Los_Angeles	America/Louisville
America/Maceio	America/Managua	America/Manaus
America/Martinique	America/Mazatlan	America/Mendoza
America/Menominee	America/Merida	America/Mexico_City
America/Miquelon	America/Moncton	America/Monterrey

America/Montevideo	America/Montreal	America/Montserrat
America/Nassau	America/New_York	America/Nipigon
America/Nome	America/Noronha	America/North_Dakota/Center
America/North_Dakota/New_Salem	America/Panama	America/Pangnirtung
America/Paramaribo	America/Phoenix	America/Port-au-Prince
America/Port_of_Spain	America/Porto_Acre	America/Porto_Velho
America/Puerto_Rico	America/Rainy_River	America/Rankin_Inlet
America/Recife	America/Regina	America/Rio_Branco
America/Rosario	America/Santiago	America/Santo_Domingo
America/Sao_Paulo	America/Scoresbysund	America/Shiprock
America/St_Johns	America/St_Kitts	America/St_Lucia
America/St_Thomas	America/St_Vincent	America/Swift_Current
America/Tegucigalpa	America/Thule	America/Thunder_Bay
America/Tijuana	America/Toronto	America/Tortola
America/Vancouver	America/Virgin	America/Whitehorse
America/Winnipeg	America/Yakutat	America/Yellowknife
Antarctica/Casey	Antarctica/Davis	Antarctica/DumontDUrville
Antarctica/Mawson	Antarctica/McMurdo	Antarctica/Palmer
Antarctica/Rothera	Antarctica/South_Pole	Antarctica/Syowa
Antarctica/Vostok	Arctic/Longyearbyen	Asia/Aden
Asia/Almaty	Asia/Amman	Asia/Anadyr
Asia/Aqtau	Asia/Aqtobe	Asia/Ashgabat
Asia/Ashkhabad	Asia/Baghdad	Asia/Bahrain
Asia/Baku	Asia/Bangkok	Asia/Beirut
Asia/Bishkek	Asia/Brunei	Asia/Calcutta
Asia/Choibalsan	Asia/Chongqing	Asia/Chungking
Asia/Colombo	Asia/Dacca	Asia/Damascus
Asia/Dhaka	Asia/Dili	Asia/Dubai
Asia/Dushanbe	Asia/Gaza	Asia/Harbin
Asia/Hong_Kong	Asia/Hovd	Asia/Irkutsk
Asia/Istanbul	Asia/Jakarta	Asia/Jayapura
Asia/Jerusalem	Asia/Kabul	Asia/Kamchatka
Asia/Karachi	Asia/Kashgar	Asia/Katmandu
Asia/Krasnoyarsk	Asia/Kuala_Lumpur	Asia/Kuching

Asia/Kuwait Asia/Magadan	Asia/Macao Asia/Makassar	Asia/Macau Asia/Manila
Asia/Muscat	Asia/Nicosia	Asia/Manila Asia/Novosibirsk
-		
Asia/Omsk	Asia/Oral	Asia/Phnom_Penh
Asia/Pontianak	Asia/Pyongyang	Asia/Qatar
Asia/Qyzylorda	Asia/Rangoon	Asia/Riyadh
Asia/Riyadh87	Asia/Riyadh88	Asia/Riyadh89
Asia/Saigon	Asia/Sakhalin	Asia/Samarkand
Asia/Seoul	Asia/Shanghai	Asia/Singapore
Asia/Taipei	Asia/Tashkent	Asia/Tbilisi
Asia/Tehran	Asia/Tel_Aviv	Asia/Thimbu
Asia/Thimphu	Asia/Tokyo	Asia/Ujung_Pandang
Asia/Ulaanbaatar	Asia/Ulan_Bator	Asia/Urumqi
Asia/Vientiane	Asia/Vladivostok	Asia/Yakutsk
Asia/Yekaterinburg	Asia/Yerevan	Atlantic/Azores
Atlantic/Bermuda	Atlantic/Canary	Atlantic/Cape_Verde
Atlantic/Faeroe	Atlantic/Faroe	Atlantic/Jan_Mayen
Atlantic/Madeira	Atlantic/Reykjavik	Atlantic/South_Georgia
Atlantic/St_Helena	Atlantic/Stanley	Australia/ACT
Australia/Adelaide	Australia/Brisbane	Australia/Broken_Hill
Australia/Canberra	Australia/Currie	Australia/Darwin
Australia/Eucla	Australia/Hobart	Australia/LHI
Australia/Lindeman	Australia/Lord_Howe	Australia/Melbourne
Australia/NSW	Australia/North	Australia/Perth
Australia/Queensland	Australia/South	Australia/Sydney
Australia/Tasmania	Australia/Victoria	Australia/West
Australia/Yancowinna	BET	BST
Brazil/Acre	Brazil/DeNoronha	Brazil/East
Brazil/West	CAT	CET
CNT	CST	CST6CDT
CTT	Canada/Atlantic	Canada/Central
anada/East-Saskatchewan	Canada/Eastern	Canada/Mountain
Canada/NewfoundLand	Canada/Pacific	Canada/Saskatchewan
Canada/Yukon	Chile/Continental	Chile/EasterIsland

Cuba	EAT	ECT
EET	EST	EST5EDT
Egypt	Eire	Etc/GMT
Etc/GMT+0	Etc/GMT+1	Etc/GMT+10
Etc/GMT+11	Etc/GMT+12	Etc/GMT+2
Etc/GMT+3	Etc/GMT+4	Etc/GMT+5
Etc/GMT+6	Etc/GMT+7	Etc/GMT+8
Etc/GMT+9	Etc/GMT-0	Etc/GMT-1
Etc/GMT-10	Etc/GMT-11	Etc/GMT-12
Etc/GMT-13	Etc/GMT-14	Etc/GMT-2
Etc/GMT-3	Etc/GMT-4	Etc/GMT-5
Etc/GMT-6	Etc/GMT-7	Etc/GMT-8
Etc/GMT-9	Etc/GMT0	Etc/Greenwich
Etc/UCT	Etc/UTC	Etc/Universal
Etc/Zulu	Europe/Amsterdam	Europe/Andorra
Europe/Athens	Europe/Belfast	Europe/Belgrade
Europe/Berlin	Europe/Bratislava	Europe/Brussels
Europe/Bucharest	Europe/Budapest	Europe/Chisinau
Europe/Copenhagen	Europe/Dublin	Europe/Gibraltar
Europe/Guernsey	Europe/Helsinki	Europe/Isle_of_Man
Europe/Istanbul	Europe/Jersey	Europe/Kaliningrad
Europe/Kiev	Europe/Lisbon	Europe/Ljubljana
Europe/London	Europe/Luxembourg	Europe/Madrid
Europe/Malta	Europe/Mariehamn	Europe/Minsk
Europe/Monaco	Europe/Moscow	Europe/Nicosia
Europe/Oslo	Europe/Paris	Europe/Podgorica
Europe/Prague	Europe/Riga	Europe/Rome
Europe/Samara	Europe/San_Marino	Europe/Sarajevo
Europe/Simferopol	Europe/Skopje	Europe/Sofia
Europe/Stockholm	Europe/Tallinn	Europe/Tirane
Europe/Tiraspol	Europe/Uzhgorod	Europe/Vaduz
Europe/Vatican	Europe/Vienna	Europe/Vilnius
Europe/Volgograd	Europe/Warsaw	Europe/Zagreb
Europe/Zaporozhye	Europe/Zurich	GB

GB-Eire	GMT	GMTØ
Greenwich	HST	Hongkong
IET	IST	Iceland
Indian/Antananarivo	Indian/Chagos	Indian/Christmas
Indian/Cocos	Indian/Comoro	Indian/Kerguelen
Indian/Mahe	Indian/Maldives	Indian/Mauritius
Indian/Mayotte	Indian/Reunion	Iran
Israel	JST	Jamaica
Japan	Kwajalein	Libya
MET	MIT	MST
MST7MDT	Mexico/BajaNorte	Mexico/BajaSur
Mexico/General	Mideast/Riyadh87	Mideast/Riyadh88
Mideast/Riyadh89	NET	NST
NZ	NZ-CHAT	Navajo
PLT	PNT	PRC
PRT	PST	PST8PDT
Pacific/Apia	Pacific/AuckLand	Pacific/Chatham
Pacific/Easter	Pacific/Efate	Pacific/Enderbury
Pacific/Fakaofo	Pacific/Fiji	Pacific/Funafuti
Pacific/Galapagos	Pacific/Gambier	Pacific/Guadalcanal
Pacific/Guam	Pacific/Honolulu	Pacific/Johnston
Pacific/Kiritimati	Pacific/Kosrae	Pacific/Kwajalein
Pacific/Majuro	Pacific/Marquesas	Pacific/Midway
Pacific/Nauru	Pacific/Niue	Pacific/Norfolk
Pacific/Noumea	Pacific/Pago_Pago	Pacific/Palau
Pacific/Pitcairn	Pacific/Ponape	Pacific/Port_Moresby
Pacific/Rarotonga	Pacific/Saipan	Pacific/Samoa
Pacific/Tahiti	Pacific/Tarawa	Pacific/Tongatapu
Pacific/Truk	Pacific/Wake	Pacific/Wallis
Pacific/Yap	Poland	Portugal
ROK	SST	Singapore
Turkey	UCT	US/ALaska
US/Aleutian	US/Arizona	US/Central
US/East-Indiana	US/Eastern	US/Hawaii

US/Indiana-Starke	US/Michigan	US/Mountain
US/Pacific	US/Pacific-New	US/Samoa
UTC	Universal	VST
W-SU	WET	Ζυίυ



Appendix

B Secure File Transfer Problems

The following excerpt is an example of the logging generated by a successful file transfer using the Secure File Transfer Protocol. Each line shown was actually prefaced with something similar to the following:

01 Jan 2011 12:00:00,000 0000 [Connect thread gen75 session] DEBUG SftpTransferAgent.class -

Connecting to remote server: Connecting to gen75 port 22 Connection established Remote version string: SSH-2.0-OpenSSH_3.8.1p1 Local version string: SSH-2.0-JSCH-0.1.42 Checking ciphers: CheckCiphers: aes256-ctr, aes192-ctr, aes128-ctr, aes256-cbc, aes192-cbc, aes128-cbc, 3des-ctr, arcfour, arcfour128, arcfour256 aes256-ctr is not available. aes192-ctr is not available. aes256-cbc is not available. aes192-cbc is not available. arcfour256 is not available. Initializing: SSH_MSG_KEXINIT sent SSH_MSG_KEXINIT received kex: server->client aes128-ctr hmac-md5 none kex: client->server aes128-ctr hmac-md5 none SSH_MSG_KEXDH_INIT sent expecting SSH_MSG_KEXDH_REPLY ssh_rsa_verify: signature true Permanently added 'gen75' (RSA) to the list of known hosts. SSH_MSG_NEWKEYS sent SSH_MSG_NEWKEYS received SSH_MSG_SERVICE_REQUEST sent SSH_MSG_SERVICE_ACCEPT received

Iterating through available authentication methods: Authentications that can continue: publickey,keyboard-interactive,password Next authentication method: publickey

Successful on *publickey*: Authentication succeeded (publickey).

```
File transfer:
Attempting to transfer file: 'C:\testFiles\textFile.txt' to 'sftpDestination'
Successfully transferred file: 'C:\testFiles\textFile.txt'
```

Closing connection to remote server: Disconnecting from gen75 port 22 Caught an exception, leaving main loop due to socket closed

Incomplete host information

The following are required for the destination server:

- Host name.
- Port
- Destination path relative to the user default.

Incorrect Host Name

An incorrect host name will see the transfer failing as the client attempts to connect to the remote server.

```
Connecting to remote server:
Connecting to something port 22
Error while connecting to SSH server (host: something user: Administrator port: 22)
com.jcraft.jsch.JSchException: java.net.UnknownHostException: something
```

Incorrect Port

An incorrect port will see the transfer failing as the client attempts to connect to the remote server.

```
Connecting to remote server:
Error while connecting to SSH server (host: 127.0.0.1 user: Administrator port: 1234)
com.jcraft.jsch.JSchException: java.net.ConnectException: Connection refused:
```

Missing Port

If the port has not been specified in the G*plus* Adapter options, the transfer will fail prior to attempting to connect to the remote server.

Incomplete host information. Host, username and destination port must be defined and valid in the CME

Public Key Authentication

Public Key Authentication Not Enabled

Public key authentication was not enabled on the destination SSH server.

Iterating through available authentication methods: Authentications that can continue: keyboard-interactive, password Next authentication method: keyboard-interactive Authentications that can continue: password Next authentication method: password Disconnecting from gen75 port 22 Error while connecting to SSH server (host: gen75 user: Administrator port: 22) com.jcraft.jsch.JSchException: Auth fail

Public Key Authentication Failed

- 1. The generated private key did not use one of the following supported ciphers:
 - aes256-ctr
 - aes192-ctr
 - aes128-ctr
 - aes256-cbc
 - aes192-cbc
 - aes128-cbc
 - 3des-ctr
 - arcfour
 - arcfour128
 - arcfour256
- 2. The public key associated with the private key has not been added to the authorized key file on the SSH server.
- 3. The private key did not have a matching public key on the SSH server.

Iterating through available authentication methods: Authentications that can continue: publickey, keyboard-interactive, password Next authentication method: publickey Authentications that can continue: keyboard-interactive, password Next authentication method: keyboard-interactive Authentications that can continue: password Next authentication method: password Next authentication method: password Disconnecting from gen75 port 22 Error while connecting to SSH server (host: gen75 user: Administrator port: 22) com.jcraft.jsch.JSchException: Auth fail

Incorrect Public Key Path

The private key path configured in the G*plus* Adapter options is incorrect and the transfer will fail prior to attempting to connect to the remote server.

Private key not found at 'wrongPath'

Public Key Passphrase Authentication Failed

The private key was generated with a passphrase but the passphrase was missing from the configuration or it was incorrect.

Iterating through available authentication methods: Authentications that can continue: publickey,keyboard-interactive,password Next authentication method: publickey Disconnecting from gen75 port 22 Error while connecting to SSH server (host: gen75 user: Administrator port: 22) com.jcraft.jsch.JSchException: Auth fail

Username-Password Authentication

Password Authentication Not Enabled

Password authentication was not enabled in the SSH server configuration.

Iterating through available authentication methods: Authentications that can continue: publickey,keyboard-interactive Next authentication method: publickey Authentications that can continue: keyboard-interactive Next authentication method: keyboard-interactive Disconnecting from gen75 port 22 Error while connecting to SSH server (host: gen75 user: Administrator port: 22) com.jcraft.jsch.JSchException: Auth fail

Failed Authentication

- 1. The username configured for the client does not match one of the usernames configured on the SSH server.
- 2. The plain text password configured for the client is incorrect for the user identified by the username.
- 3. The password configured for the client is blank and PermitEmptyPasswords has not been set in the SSH server configuration.

Iterating through available authentication methods: Authentications that can continue: publickey, keyboard-interactive, password Next authentication method: publickey Authentications that can continue: keyboard-interactive, password Next authentication method: keyboard-interactive Authentications that can continue: password Next authentication method: password Next authentication method: password Disconnecting from gen75 port 22 Error while connecting to SSH server (host: gen75 user: Admin port: 22) com.jcraft.jsch.JSchException: Auth fail

Problems with Transfer

Inaccessible Destination Directory or Insufficient Access Privileges

- 1. The destination directory cannot be reached as a sub-directory from the user home directory on the SSH server.
- 2. The user identified by the username has the wrong or insufficient privileges for the destination directory on the SSH server.

```
File transfer:

Attempting to transfer file: 'C:\testFiles\textFile.txt' to 'c:/'

Unable to transfer file: 'C:\testFiles\textFile.txt', check that destination directory exists

Failure

at com.jcraft.jsch.ChannelSftp.throwStatusError(ChannelSftp.java:2289)

....
```

Non-Existent Destination Directory

The destination directory on the SSH server does not exist.

There will be no error indication for a missing destination directory if it was configured as a subdirectory of the user's home directory on the remote server. Despite the logged statements, the file will not have been transferred to the destination directory as the directory will not be created. It is likely that the file was transferred but its location and name may be a combination of the valid and invalid portions of the destination path.

```
File transfer:
Attempting to transfer file: 'C:\testUser\testFiles\textFile.txt' to 'sftpDestination'
Successfully transferred file: 'C:\testUser\testFiles\textFile.txt'
```

Closing connection to remote server: Disconnecting from gen75 port 22 Caught an exception, leaving main loop due to socket closed

Using the above as an example, if the testFiles directory did not exist in the testUser directory, a successful transfer might see a new file, testFilestextFile.txt, located in the testUser directory. The actual file location and name will be dependent upon the portions of the destination path that are incorrect, the type of SSH server and the underlying operating system for the SSH server



Appendix

C Managing Windows Service

prunmgr Application

The Apache CommonsTM *daemon* TM project also provides a Windows GUI application for managing an installed Service without having to resort to editing Register parameters or reinstalling the Service. This *prunmgr* application will be discussed below with respect to the *Gplus* Adapter installation and there is additional information available on the <u>Apache website</u>. The application is contained in the wrappers folder of the Adapter installation and is started with the following:

prunmgr.exe //ES//GPlusAdapterServiceName

Any changes to the configuration can be established by stopping and restarting the Service after applying the changes. The options and parameters appropriate to the Adapter Service wrapper are discussed below.

General Tab

Startup type:

This field should be set to *Automatic* so that the Service will restart if the host server is restarted.

Start, Stop and Restart Buttons

The Service can be started, stopped and restarted. Pausing the Service would have indeterminate results that would probably warrant a restart.

b GPlusWFMAdapt	er Properties				
General Log On L	ogging Java Startup Shutdown				
Service Name:	GPlusWFMAdapter				
Display <u>n</u> ame:	GPlusWFMAdapter				
Description:					
Path to executable	e:				
"C:\Program Files	: (x86)\GCTI\WFMAdapter\GPlusWFMAdapter.exe" //RS,				
Startup type: Manual					
	Automatic Manual				
	Disabled				
Service Status:	Stopped				
<u>S</u> tart	Stop Pause Restart				
	OK Cancel Apply				

Logging Tab

It is possible to log the Adapter Service which is helpful when encountering problems with getting the Service properly installed and running.

Log prefix:

Specifying this parameter will enable logging to the *Log path* folder with the prefix as the start of the log name combined with a .YEAR-MONTH-DAY.log suffix.

Log path:

The default is the Adapter's logs folder but this parameter can be set to another folder if required.

Redirect Stdout: and Redirect Stderr:

Both stdout and stdorr can be redirected to files in the *Log path* folder if there is a need to debug JVM problems that are not logged in the regular adapter logs. Both are set to auto in the svcinstall.bat file and that enables the logging with the default file names.

🏷 GPlus	WFMAda	pter Prop	erties			X
Genera	Log On	Logging	Java	Startup	Shutdown	
<u>L</u> evel	:	Info				-
Log g	ath:					
C: V	rogram File	es (x86)\G	CTI\WFN	1Adapter≬	ogs	
Log p	refix:	Adapt	erService	el]
Pid fil	e:]
Redir	ect Stdout					
auto						
Redir	ect Stderro	r:				
auto)					
				ОК	Cancel	Apply

Java Tab

The *Java* tab configures the operating parameters for the Java Virtual Machine associated with the Service. The default configuration is shown below with the exception of the *Java Virtual Machine* parameter that is installation specific.

Java Virtual Machine:

This parameter identifies the path to the jvm.dll file that will be linked by the Service wrapper to host the Adapter application. The .dll file should be a "server" version as described in <u>Chapter 2</u>.

Java Classpath:

This parameter must not be modified from the default, bootstrap.jar.

Initial memory pool:

This parameter specifies the amount of system memory that will be allocated to the JVM at startup. This parameter is set to the same amount as the *Maximum memory pool* so that all of the required memory is requested at startup and if the system cannot provide it at that time, the JVM shuts down. This avoids memory problems arising hours after startup because there is insufficient system memory.

Default = 1024 MB

Maximum memory pool:

This parameter specifies the maximum amount of system memory that will be requested by the JVM.

Default = 1024 MB

Java Options:

This section allows any number of parameters to be added to the JVM configuration. Presently, the parameters that might be added are related to configuring the memory Garbage Collection (GC) and adding logging of the GC activity.

GPlusWFMAdapter Pr	operties			×
General Log On Loggin	g Java	Startup	Shutdown	
Use default				
Java Virtual Machine:				
c: \Program Files (x86)	\Java\jdk1	.6.0_20\jre	vbin\server\jvm.o	ll
Java Classpath:				
bootstrap.jar				
Java Options:				*
				~
Initial memory pool:	1024		MB	
Maximum memory pool:	1024		MB	
Thread stack size:			KB	
		ОК	Cancel	Apply

Startup Tab

Class:

This field specifies the Java class that contains the main method that will be invoked at startup. This cannot be changed.

Default = com.ariasolutions.iconnect.BootStrap

Working Path:

This field specifies the root folder for the Adapter installation. It is dependent upon the *Path to executable* field on the *General Tab* and should not be changed.

Mode:

The proper operation of the Service wrapper is dependent upon this field remaining set to j vm.

b GPlusWFMAdapter Properties					
General Log On Logging Java Startup Shutdown					
Qlass:					
com.ariasolutions.iconnect.BootStrap					
Image:					
Working Path:					
C:\Program Files (x86)\GCTI\WFMAdapter					
Method:					
Arguments:					
Timeout: sec.					
Mode:					
OK Cancel Apply					



Appendix



Log Files

Depending upon the logging configuration discussed <u>above</u>, there may be more than one set of logs contained in the logging folder. This chapter is concerned with the event logs that also include logging of state changes for Agents and media interactions.. There will typically be two versions of the event logs contained in the Logs folder: ROLLING and GZIP. The actual names of the logs are specified in the Log4j.xml file but unless they have been changed there, the log files will have the prefix of GPLusAdapterWFM.

The default size for each of the ROLLING logs is 50 MB and they will be rolling over quickly in a large call center. These logs give a snapshot of activity at the time that they are checked but may not be suitable for tracking down problems with the adapter if they cover too short an interval. The most recent of the log files will have a name starting with the prefix described above and then the .log extension. Earlier logs will have numbers added to the extension with .log.1 being the next most recent and .log.2 being earlier again.

Each of the zipped logs contain exactly the same information as the ROLLING logs but summarize an hour of activity and the time at the start of that hour is contained in the log file name:

GPLusAdapterWFM.Log.2012.01.01-16.00.00.gz

The time field will always be an even hour except for the log created at startup. That file will have a time stamp indicating when the logging started:

GPlusAdapterWFM.log.2012.01.01-15.50.00.gz

This log will contain useful startup information not available in the other logs. If the Adapter has been running for an extended period of time, the startup log will have been removed as older zipped logs are also deleted to prevent filling up the disk storage.

Description of Fields

The log files are intended as an aid in debugging the application when problems do occur. The files have a simple format that is described below using the first line of the log file as it starts up as an example.

01 Jan 2012 12:00:02,000 · 2000 [main] INFO com.ariasolutions.iconnect.Application - Launching GPlus Adapter

- 1.01 Jan 2012 12:00:02,000
- 2.2000
- 3.[main]
- 4. INF0
- 5. com.ariasolutions.iconnect.Application
- 6. Launching GPlus Adapter

The **first** field shows the date and time that the event or update occurred.

The **second** field shows the number of milliseconds that the application has been running.

The **third** field is the thread name that produced the message.

The **fourth** field is the logging level that the message has been assigned.

The fifth field is the Java class (and stream) that has generated the message.

The sixth field is the description of what has occurred to generate the message.

Logging Threshold and Messages

The logging threshold has more relevance as the types of messages that are generated by the Adapter have been rationalized. The info mode tracks significant events such as report generation and TServer connections but is restricted to logging agent activity by the changes in RTA states. The debug mode adds more detail to the agent activity as well as logging the progress of interactions (voice calls, emails etc.) from monitored queues to the agent desktops. The trace mode provides the most detail with full logging of the incoming events and includes the PlaceListenerLogger and the QueueListenerLogger discussed below.

Both the info and debug modes result in log files that are significantly smaller than those generated with the trace mode.

info mode example

The following is an example of what is logged when the LogThreshold is set to info. It shows the messages generated when an agent receives an inbound customer call.

01 Jan 2014 12:01:00,000 90000 [main] INFO com.ariasolutions.iconnect.rta.StateHolder Stream1 -StateHolder.notifyStateChange: msmith: StateInfo(CallInbound, Mon Jan 01 12:01:00 MDT 2014, null, 2500, VoiceSales_VQ,)

Just the single line is generated showing the change in the agent's state. It should be noted that the stream name of Stream1 has been added to the class name that generated the message. If the message was not associated with a configured stream, then a stream name of default would have been logged.

debug mode example

As can be seen, the debug mode adds call tracking.

```
01 Jan 2014 12:00:45,000 75000 [main] DEBUG
com.ariasolutions.iconnect.eventprocessing.VoiceEventProcessor - Call 00b102420f4e2002 placed in
Queue VoiceSales_VQ
01 Jan 2014 12:00:55,000 85000 [main] DEBUG
com.ariasolutions.iconnect.eventprocessing.VoiceEventProcessor - Call 00b102420f4e2002 ringing on
Place Place_2500 (Agent msmith)
01 Jan 2014 12:00:59,000 89000 [main] INFO com.ariasolutions.iconnect.rta.StateHolder default -
StateHolder.notifyStateChange: msmith: StateInfo(CallInbound, Mon Jan 01 12:00:59 MDT 2014, null,
2500, VoiceSales_VQ, )
01 Jan 2014 12:01:00,000 90000 [main] DEBUG
com.ariasolutions.iconnect.eventprocessing.VoiceEventProcessor - Call 00b102420f4e2002 established
on Place Place_2500 (Agent msmith) Pegged to Queue VoiceSales_VQ
```

trace mode

The trace mode logging for the above example would be several pages long as the full events are logged from the initial queued event to the EventEstablished on the agent's desktop. The extra logging is discussed below in the next three sections.

Events and Server Identification

Events are logged just as they are received from the connected Genesys Server: Interaction Server, SIPServer or TServer. Configuration Server events are logged but not with the detail described below. The following shows a TServer event generated when an Agent answered an incoming call:

```
24 May 2012 21:59:37,183 - 168858 ... - Received event from 'TServer1'
EventEstablished
 ANI: 4032500001
 AgentID: 200000
 CallState: 0
 CallType: Inbound
 ConnID: 00000000005c85e
 EventSequenceNumber: 112318
 GPLusWFM.LocalTime: 1337885977167
 GPLusWFM.RemoteTime: 1337885977201
 GPLusWFM.SourceId: 133
 GPLusWFM.SourceName: TServer1
 GPLusWFM.Time: 1337885977201
 OtherDN: 4032500002
 OtherDNRole: RoleOrigination
 ThisDN: Test 2000
 ThisDNRole: RoleDestination
 ThisTrunk: 9999
 TimeinSecs: 1337885977
 TimeinuSecs: 201000
 UserData.SampleBinary1: [B@1c668df
 UserData.SampleInt1: 1
 UserData.inner.inner sample: sample
 UserData.inner.inner int: 3
 UserData.SampleString1: Sample
```

Some of the enumerated event attributes such as CallType are replaced with the value name to make the logged event easier to read. The adapter also adds attributes with the GPlusWFM prefix for the Adapter's host time (GPlusWFM.LocalTime) and the Genesys Server time (GPlusWFM.RemoteTime). The GPlusWFM.Time attribute indicates which of the two time sources the Adapter is actually using for the event time as selected by the <u>application/useLocalTime</u> configuration option.

The GPLUSWFM.SourceId and GPLUSWFM.SourceName for the originating Genesys Server are also included.

PlaceListenerLogger

Prior to the event listed above, the Adapter added some state change notifications that were associated with the EventEstablished. The first notification is logged by the PlaceListenerLogger and indicates the answering Agent's state:

```
24 May 2012 21:59:37,183 - 168858 ... PlaceListenerLogger - PlaceState updated to:
PlaceState for Place: [PlaceName: Place_2500001, site: Site_1]
LoginSession: [LoginID: 200000, AgentUsername: Agent_200000, DoNotDisturb: off]
MediaSession: [MediaType: voice, ReadyState: Ready]
Interaction: [ID: 0000000005c85e, Target: VQ_Test]
```

Although the receiving agent was not identified in the EventEstablished attributes, the PlaceListenerLogger has identified the Place and its associated Site for the logged in agent. The agent is indicated as in a Ready state for voice calls and is presently handling one call that was queued on a monitored VQ. If the agent was logged in to additional media (email, chat etc.), there would be additional media sessions listed as well as any ongoing interactions associated with those sessions.

Note: The absence of any of the above information (with the exception of Site) would indicate a configuration problem as there was insufficient information to create and maintain the required internal associations.

QueueListenerLogger

The second state change notification associated with the EventEstablished was generated by the QueueListenerLogger which logs the state changes for the incoming call. There is not a lot of detail other than logging the target with which the call had been associated and logging the state of the call in generic terms that apply to routing of any media:

```
24 May 2012 21:59:37,183 - 168858 ... QueueListenerLogger - Interaction 'answered':
QueuedInteraction [id=00000000005c85e, target=VQ_4847]
```

There are six available states for a queued interaction and they are sufficient to indicate the part of a "call flow" the interaction had reached when the event was generated:

- offered
- abandoned
- expired
- answered
- released
- exitQueue

The QueueListenerLogger had already been logging the interaction state of the call prior to the agent answering it:

24 May 2012 21:59:33,613 - 165288 ... QueueListenerLogger -Interaction 'offered': QueuedInteraction [id=00000000005c85e, target=VQ_4847] 24 May 2012 21:59:33,613 - 165288 ... - Received event from 'TServer2' EventQueued CallType: Inbound ConnID: 00000000005c85e EventSequenceNumber: 112574 GPLusWFM.LocalTime: 1337885973613 GPLusWFM.RemoteTime: 1337885973638 GPLusWFM.SourceId: 135 GPLusWFM.SourceName: TServer2 GPLusWFM.Time: 1337885973638 OtherDN: 4032350227 OtherDNRole: RoleOrigination ThisDN: VQ_4847 ThisDNRole: RoleDestination ThisQueue: VQ_4847 TimeinSecs: 1337885973 TimeinuSecs: 638000

Note: The QueueListenerLogger only logs calls or interactions that the adapter has identified as a "customer call". If the logger has not identified an interaction as 'offered' prior to the first queued event for the interaction, then none of the activity for that interaction will be associated with a VQ or target.



Appendix

Ε

Windows Installation Script

Files

The Windows installation script retains the configuration parameters in two files:

- config/jvm.properties
 - contains the location of the jvm.dll and the memory setting
 - o required to install the Adapter as a Windows Service
- config/GPLusWFM.properties
 - contains the Application name and the Configuration Server connection parameters
 - the Application name is required for the Service installation
 - the connection parameters are required for the Adapter to run but not for the Service installation

A third file, config/product.properties, contains the WFM vendor, IEX, as well as the version number for the specific release that has been installed. This file is not modified by the installation script but the vendor and release version are displayed.

The Adapter also displays the relevant contents of the license file.

Invoking the Installation Script

It is important that the script execute with Administrator privileges so that the Windows service can be installed and the properties files modified. This can be accomplished by right clicking on the windows_install.bat file and selecting *Run as administrator*.

Initial Screen and Status Display

There are three main menus that will be displayed depending on the context of the Adapter installation:

- Initial Tasks jvm.dll not set
- Installation Tasks adapter service not installed
- Management Tasks adapter service installed

The first, *Initial Tasks*, will appear until the path to the jvm.dll file has been set at which time the second menu will be used.

Gplus WFM Adapter - IEX 5.4.001
CME Application name = GplusWFM_Adapter Configuration Server Host = Configuration Server Port = 2020
JVM path = not set JVM memory = 1024 MB
localhost name =
License app name = Any License host name = Testing
Expiry date = 2014.Apr.15 License type = Temporary
Initial Tasks - jvm.dll not set
1. Set the Application Name
2. Set the JVM parameters 3. Set the Config Server connection parameters
4. Quit
. Select a menu item

The screenshot above shows the default settings from the properties files as well as the parameters for the temporary license provided with the Adapter release.

Set the Application name

The Application name should be set first. This name must match the name of the G*plus* Adapter's Application object in the Configuration Server. The name will be used for the name of the installed service and the renamed prunsrv.exe (Java service wrapper) that will be copied to the Adapter's main folder.


Application Name		
The Gplus Adapter's CME Application name will also be used as the Adapter Service name and must not contain any spaces. The default Application name initially displayed by this script is taken from the "appName" property in the config\GPlusWFM.properties file. That file will updated if and when a new Application name is specified.		
Press ENTER to accept (GplusWFM_Adapter) or . Type in new application name GplusWFM_54_p_		

The new name is immediately written to the GPLusWFM.properties file and will be displayed in the status section as shown below:

		CME Application name Configuration Server Host Configuration Server Port	= GplusWFM_54_p = = 2020
÷	JVM ;	path = not set	
		JVM memory	= 1024 MB
		localhost name	=
		License app name License host name	
		Expiry date License type	= 2014.Apr.15 = Temporary

Set the JVM parameters

This menu item brings up a second menu that allows the Java Runtime Environment to be configured. Once this has been completed, the Adapter can be installed as a service.



There are two different menu options for finding the path to the jvm.dll file. The first just looks in the default locations that the Oracle installation application will place a 32 bit or 64 bit version while the second option allows a path to be set with all of the subfolders being searched.

Default JVM Locations

The first menu selection will list all of the jvm.dll files found in the default installation locations. Both 32 bit and 64 bit JVM versions will be listed if present on a 64 bit OS. The Adapter will run in either.



CME Application name Configuration Server Host Configuration Server Port	
JVM path = c:\Program Files\Java	jdk1.6.0_20\jre\bin\server\jvm.dll
JVM memory JVM type	
localhost name	= wfm_adapter_host
License app name License host name	
Expiry date License type	= 2014.Apr.15 = Temporary

The change is immediately written to the config\jvm.properties file and the status section reflects the specification of the 64 bit JVM as shown below.


There are two things to note in the status section shown above beyond the fact that the path to the $j \lor m.dll$ file has been identified.

First, a new parameter, JVM type, has been added. This indicates which of the prunsrv.exe service wrappers will be used. In the example above, the 64 bit non-ItaniumTM version will be used.


The second addition is that the localhost name parameter has also been set. This is the host name that should be used when requesting a permanent license for the Adapter installation. Once the JVM path was set, a Java application was run to determine the hostname with exactly the same code that is used to confirm the hostname when validating the license.

Set path to find jvm.dll

If the Java instance has not been installed in a subfolder of either $c:\Program Files$ or $c:\Program Files$ (x86), the script will search for the jvm.dll file in other locations.



The result will be a list of the paths to any found j vm.dll files but there will no indication as to whether the files are 32 bit or 64 bit versions.




The script can determine the bitness of the JVM once it has been selected as shown below where the JVM type has been changed to 32_bit .

JVM path = c:\Program	Files (x86)\Java\jdk1.6.0_20\jre\bin\server\jvm.dll
	JVM memory = 1024 MB JVM type = 32_bit


Set JVM memory

The amount of memory that the JVM will allocate as it starts up can be set to something other than the default of 1024 MBs.



Installation Tasks

Once the path to the jvm.dll file is set, the Gplus Adapter can be installed as a Windows Service. The main menu reflects this change in status with the addition of two more menu options. It is possible to install the service with no issues but starting that service or running the Adapter as a console application will fail if the Configuration Server connection has not be configured.



Set the Config Server connection parameters

Selecting this menu option allows the script to modify the contents of the GPLusWFM.properties file which contains all of the parameters that can set on the connection.


Configuration Server Connection	
Application Type = ThirdPartyServer	
Primary Host = Primary Port = 2020	
Backup Host = Backup Port =	
addp - disabled	
Trace Mode = Local Timeout = not set Remote Timeout = not set	
Transaction Layer Security (TLS) - disabled	
Minimum Registration Delay = 5m Maximum Registration Delay = 15m	
Registration timeout = 10m	
Configuration Server Properties	
1. Set Hosts and Ports 2. Set Application Type 3. Set addp Connection Protocol 4. Enable TLS 5. Set Registration Delays	
6. Return to previous menu	
. Select a menu item	

Hosts and ports

The host and port can be set for the primary Configuration Server and its backup.

Configuration Server - Host and Ports
1. Set Primary Host 2. Set Primary Port
3. Set Backup Host 4. Set Backup Port
5. Return to previous menu
. Select a menu item

The host can be specified as with the hostname or the IP address. If TLS has been enabled, the configured port should be the Configuration Server's secure port rather than the default.



Set Application type


The Adapter's Application type affects the parameters that will be sent to the Configuration Server as part of the Adapter's registration request. A ThirdPartyServer type does not provide a username or password but is only allowed one connection. The alternative, ThirdPartyApplication, requires the username and password but provides better security.



ThirdPartyApplication

Application Type Username Password	ThirdPartyApplication not set
Primary Host Primary Port	
Backup Host Backup Port	

If ThirdPartyApplication is selected as the Application type, the script provides a menu option to set both the username and the password. It should be noted that the password is not saved as plain text.



When the password is set, that string is encrypted and stored in the config/enc file. If that file is present, the script indicates that the password has been *set* but does not display it.



Set addp Connection Protocol

The script provides a menu for configuring the addp connection protocol for the Configuration Server connection.

addp - disabled
Trace Mode = Local Timeout = not set Remote Timeout = not set
Transaction Layer Security (TLS) - disabled
Minimum Registration Delay = 5m Maximum Registration Delay = 15m
Registration timeout = 10m
Configuration Server - addp Parameters
1. Enable addp 2. Set Trace Mode 3. Set Local Timeout 4. Set Remote Timeout
5. Return to previous menu
. Select a menu item

The addp protocol can be enabled or disabled by selecting the first menu option. Both timeouts should be entered as seconds with the Local Timeout being less than the Remote Timeout.

addp Trace mode

The script lists the allowed trace mode settings. It is recommended that the trace mode be set to *full*.


	Configuration Server addp Trace Mode
If the Adapter' the recommended on Both Sides".	s connection to the Configuration Server has addp enabled, Trace Mode setting is "full" which corresponds to "Trace
	Config Server addp Trace Mode
	1. off 2. local 3. remote 4. full
•	Select a value 4

Enable/Disable TLS

TLS (Transaction Layer Security) can be set on the Configuration Server connection but the majority of the configuration work will be on the server side. The extent of the changes on the Adapter side is to enable TLS and set the connection to point to the Configuration Server's secure port.

Set Registration delays

This menu section may be necessary in very busy call centers where there are a number of applications connected to the Configuration Server. In that case, the response to requests may be delayed and it may be necessary to delay those requests when the Configuration Server is restarting after a mishap.



The registration delays are the minimum and maximum bounds of the time that the *Gplus* Adapter will wait before making a registration request of the Configuration Server after the connection has been restored. The Adapter will wait a random time between the two limits.



As mentioned, the response from the Configuration Server can be significantly delayed in very busy call centers. The registration timeout option sets the amount of time that the Adapter will wait generating a new request.



Installing the Adapter as a Service

When the option to install the Adapter as a Service is selected, two actions occur:

- 1. The appropriate version of the prunsrv.exe file is copied to the main Adapter folder from the wrappers folder and renamed to the *CME Application name* e.g. GpLusWFM_54_p.exe.
- 2. The install mode on the renamed prunsrv.exe file is used to install the application as a Windows service with the service name set to the *CME Application name*.

The script will check to see if there is a Service installed with the same name as the *CME Application name*. If that is the case, then the script will display the *Management Tasks* menu.

Management Tasks

	CME Application name = GplusWFM_54_p Configuration Server Host = config_host Configuration Server Port = 2020
	JVM path = c:\Program Files (x86)\Java\jdk1.6.0_20\jre\bin\server\jvm.dll
- 1	JVM memory = 768 MB JVM type = 32_bit
	localhost name = wfm_adapter_host
1	License app name = Any License host name = Testing
a Na tanàna Na taona 2014	Expiry date = 2014.Apr.15 License type = Temporary
	Management Tasks - adapter service installed
	1. Manage Service 2. Remove Service
	3. Set the Config Server connection parameters
	4. Run Gplus Adapter as Java application
	5. Quit
	Select a menu item

The final menu allows for certain tasks to be carried out once the *Gplus* Adapter has been installed as a Service.

Manage Service

Selecting the *Manage Service* option invokes the prunmgr.exe application that is detailed in <u>Appendix C</u>. Changes can be made to the JVM parameters without having to uninstall the service.

Remove Service

Selecting this option removes the installed service and deletes the renamed prunsrv.exe file. The script menu will return to the *Installation Tasks* menu that is detailed above.

Set the Config Server connection parameters

The *Gplus* Adapter reads the parameters from the GPlusWFM.properties file at start up. It is possible to edit the Configuration Server connection parameters, stop the Adapter, restart the Adapter and have the changes take effect.

Run Gplus Adapter as Java application

This option will start the Adapter as a console application using the same configuration as the Windows Service. It is one way to check that the Adapter configuration is correct if there are problems getting the Service to start.

This is not a viable mode for running the Adapter in a production environment but can be useful for debugging the configuration.