



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Engage Digital (eServices)

health-service

4/11/2025

## health-service

- [allow-gms-info](#)
- [log-output-content](#)
- [log-output-proviso](#)
- [log-output-timeout](#)
- [soap-accept-timeout](#)
- [soap-receive-timeout](#)
- [soap-send-timeout](#)

### allow-gms-info

**Default Value:** false

**Valid Values:** true, false

**Changes Take Effect:** Immediately

Enables or disables collecting and provisioning statistics for GMS flex-push activity.

### log-output-content

**Default Value:** set

**Valid Values:** all, new, set

**Changes Take Effect:** Immediately

Specifies which health metrics are printed in the log:

- **all:** All defined metrics.
- **new:** Metrics that were updated after the most recent output to the log.
- **set:** Metrics with non-zero values (the default).

**Attention:** Deleting this option or setting it to an empty value resets the values of all cumulative health metrics to zero.

### log-output-proviso

**Default Value:** update

**Valid Values:** always, update

**Changes Take Effect:** Immediately

Specifies how health metrics are printed in the log:

- **always:** Metrics are printed in the log whenever the timeout specified by "log-output-timeout" expires.
- **update:** Metrics are printed in the log only if they were recently updated.

## log-output-timeout

**Default Value:** 0

**Valid Values:** Any integer from 0-86400

**Changes Take Effect:** Immediately

Specifies, in seconds, the period at the end of which Chat Server outputs health metrics to the log. A value of zero disables output.

## soap-accept-timeout

**Default Value:** 5

**Valid Values:** Any integer from 1-86400

**Changes Take Effect:** After restart

An incomplete accept request that does not finish processing during the allotted time is aborted.

## soap-receive-timeout

**Default Value:** 10

**Valid Values:** Any integer from 1-86400

**Changes Take Effect:** After restart

An incomplete receive request that does not finish processing during the allotted time is aborted.

## soap-send-timeout

**Default Value:** 30

**Valid Values:** Any integer from 1-86400

**Changes Take Effect:** After restart

An incomplete send request that does not finish processing during the allotted time is aborted.