



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Engage Digital (eServices)

iwe-processing Section

4/14/2025

# iwe-processing Section

- [address](#)
- [endpoint](#)

## address

**Default Value:**

**Valid Values:** Any valid e-mail address

**Changes Take Effect:** Immediate

The e-mail address used to fill in the Mailbox field of WebForm-transformed email-in. This address becomes the default from address when replying to web form e-mails, in cases where Web API Server does not already provide a Mailbox key. The value must comply with RFC2822, and therefore must be encoded according to RFC2047. An example of a valid value is legal@mycompany.com

## endpoint

**Default Value:** default

**Valid Values:** A string that matches the name of an endpoint defined in the endpoints:<tenant\_dbid> section

**Changes Take Effect:** Immediately

**Related Options:** [endpoints:<tenant\\_dbid>](#)

Specifies the endpoint name by which E-mail Server identifies the queue to which it will submit a webform. This endpoint name should be defined in the **endpoints:<tenant\_dbid>** section. If this endpoint name is not defined in that section, then E-mail Server uses the default endpoint from the endpoints:<tenant\_dbid> section. If no default endpoint is configured in the endpoints:<tenant\_dbid> section, or if the endpoints:<tenant\_dbid> section does not exist, then E-mail Server works in 7.1 compatibility mode, and uses the email-processing section's default-inbound-queue option.