



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Mobile Services

stat.<statname> Section

stat.<statname> Section

- filter
- metric
- notificationMode
- objectId
- objectType
- tenant
- tenantPassword

filter

Default Value: No default value
Valid Values: Any string
Changes Take Effect: After restart

The business attribute value to use to filter the results.

metric

Default Value: No default value
Valid Values: Any string
Changes Take Effect: After restart

The name of the metric, for example, **TotalLoginTime**. This option defines a Stat Server statistic that can be opened at startup by listing it in the [reporting] startup-statistics configuration option.

notificationMode

Default Value: No default value
Valid Values: NoNotification, Reset, or Immediate
Changes Take Effect: After restart

Notification mode. Mandatory.

objectId

Default Value: No default value

Valid Values: Any string
Changes Take Effect: After restart

Statistic object ID.

objectType

Default Value: No default value
Valid Values: Any string
Changes Take Effect: After restart

Statistic object type; for example, **Agent**.

tenant

Default Value: No default value
Valid Values: Any string
Changes Take Effect: After restart

Tenant name; for example, **Environment**.

tenantPassword

Default Value: No default value
Valid Values: Any string
Changes Take Effect: After restart

Tenant password.