



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Voice Platform

TalkerManager Section

TalkerManager Section

- AckMsgFax
- AckMsgTDD
- EnableTDD
- HangUpAfterBlindXfer
- MinDownLoadSize
- RetryAllocResource
- TimeReconfigMFCMsec
- WaitAnswer2DTMF
- WaitFreeStatusDialOutMsec

AckMsgFax

Default Value: 0

Valid Values:

Changes Take Effect: After restart

Send ACK or NAK responses for each SIP INFO received in Fax operation.

AckMsgTDD

Default Value: 0

Valid Values:

Changes Take Effect: After restart

Send ACK or NAK responses for each SIP INFO received in TDD operation.

EnableTDD

Default Value: 0

Valid Values:

Changes Take Effect: After restart

Calls generated from TDD equipments will be accepted.

HangUpAfterBlindXfer

Default Value: 1

Valid Values:

Changes Take Effect: After restart

Hangup call after blind transfer.

MinDownloadSize

Default Value: 8192

Valid Values:

Changes Take Effect: After restart

MinDownloadSize in bytes

RetryAllocResource

Default Value: 0

Valid Values:

Changes Take Effect: After restart

Number of retries for waiting resources (-1==Forever, 0==Skip, 'n'==n_times).

TimeReconfigMFCMsec

Default Value: 0

Valid Values:

Changes Take Effect: After restart

Time Reconfiguration MFC (msec)

WaitAnswer2DTMF

Default Value: 1

Valid Values:

Changes Take Effect: After restart

Wait answer result before dialing DTMF.

WaitFreeStatusDialOutMsec

Default Value: 0

Valid Values:

Changes Take Effect: After restart

Wait time for free status of dialout channel (msec)